San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

DEC 17 2012

Wendy Garcia
CBUS Ops Inc. (dba Woodbridge Winery)
P O Box 1260
Woodbridge, CA 95258

Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # N-2321
Project # 1113362

Dear Ms. Garcia:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for CBUS Ops Inc. (dba Woodbridge Winery) for its wine production facility located at 5950 E. Woodbridge Road in Acampo, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Attachments
C: Dustin Brown, Permit Services Engineer

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

DEC 17 2012

Gerardo C. Rios, Chief
Permits Office (AIR-3)
U.S. EPA - Region IX
75 Hawthorne St.
San Francisco, CA 94105

Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # N-2321
Project # 1113362

Dear Mr. Rios:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for CBUS Ops Inc. (dba Woodbridge Winery) for its wine production facility located at 5950 E. Woodbridge Road in Acampo, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 45-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Attachments
C: Dustin Brown, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

DEC 17 2012

Mike Tollstrup, Chief
Project Assessment Branch
Air Resources Board
P O Box 2815
Sacramento, CA 95812-2815

Re: Notice of Preliminary Decision - Title V Permit Renewal
District Facility # N-2321
Project # 1113362

Dear Mr. Tollstrup:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for CBUS Ops Inc. (dba Woodbridge Winery) for its wine production facility located at 5950 E. Woodbridge Road in Acampo, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. Please submit your written comments on this project within the 30-day comment period which begins on the date of publication of the public notice.

Thank you for your cooperation in this matter. If you have any questions regarding this matter, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900.

Sincerely,

David Warner
Director of Permit Services

Attachments
C: Dustin Brown, Permit Services Engineer

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

Stockton Record

NOTICE OF PRELIMINARY DECISION
FOR THE PROPOSED RENEWAL OF
THE FEDERALLY MANDATED OPERATING PERMIT

NOTICE IS HEREBY GIVEN that the San Joaquin Valley Air Pollution Control District solicits public comment on the proposed renewal of the Federally Mandated Operating Permit to CBUS Ops Inc. (dba Woodbridge Winery) for its wine production facility located at 5950 E. Woodbridge Road in Acampo, California.

The District's analysis of the legal and factual basis for this proposed action, project #1113362, is available for public inspection at http://www.valleyair.org/notices/public_notices_idx.htm and the District office at the address below. There are no emission changes associated with this proposed action. This will be the public's only opportunity to comment on the specific conditions of the proposed renewal of the Federally Mandated Operating permit. If requested by the public, the District will hold a public hearing regarding issuance of this renewed permit. For additional information, please contact Mr. Jim Swaney, Permit Services Manager, at (559) 230-5900. Written comments on the proposed renewed permit must be submitted within 30 days of the publication date of this notice to DAVID WARNER, DIRECTOR OF PERMIT SERVICES, SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT, 1990 E. GETTYSBURG AVE, FRESNO, CALIFORNIA 93726-0244.

SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation
CBUS Ops Inc (dba Woodbridge Winery)
N-2321

TABLE OF CONTENTS

I. PROPOSAL 2
II. FACILITY LOCATION 3
III. EQUIPMENT LISTING 3
IV. GENERAL PERMIT TEMPLATE USAGE 3
V. SCOPE OF EPA AND PUBLIC REVIEW 3
VI. FEDERALLY ENFORCEABLE REQUIREMENTS 4
VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE 5
VIII. PERMIT REQUIREMENTS 7
IX. PERMIT SHIELD 51
X. PERMIT CONDITIONS 51
XI. ATTACHMENTS 51

A. DRAFT RENEWED TITLE V OPERATING PERMIT
B. PREVIOUS TITLE V OPERATING PERMIT
C. DETAILED FACILITY LIST
D. SIP STRINGENCY ANALYSIS FOR DISTRICT RULE 4702

TITLE V PERMIT RENEWAL EVALUATION

Winery

Engineer: Dustin Brown
Date: December 13, 2012

Facility Number: N-2321
Facility Name: CBUS Ops, Inc. (dba Woodbridge Winery)
Mailing Address: P O Box 1260
Woodbridge, CA 95258

Contact Name: Wendy F. Garcia
Phone: (559) 661-5534

Responsible Official: Mr. Mark Gabrielli
Title: General Manager

Project # : N-1113362
Deemed Complete: September 7, 2011

I. PROPOSAL

CBUS Ops, Inc. (dba Woodbridge Winery), herein referred to as Woodbridge Winery, was issued their initial Title V permit on March 5, 2007. As required by District Rule 2520, the applicant is requesting a permit renewal.

The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

In addition, on August 29, 2012, the facility submitted a name change application to change the name of the facility from RME, Inc. – Woodbridge Winery to CBUS OPS, Inc. (dba Woodbridge Winery). In accordance with District Rule 2520, Section 3.2, this name change application is required to go through an Title V Administrative Permit Amendment. This name change and associated Title V permit administrative amendment will be processed and included along with this Title V renewal project.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Woodbridge Winery is located at 5950 E. Woodbridge Road in Acampo, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit template:

Facility wide SJV-UM-0-3:

The applicant has requested to utilize template # SJV-UM-0-3 for the facility-wide requirements. Based on the information submitted on the Template Qualification Form, the applicant qualifies for the use of this template.

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA or public review:

- Conditions 1-40 of the requirements for permit unit N-2321-0-2.

All other applicable federally enforceable requirements in this Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated

- District Rule 2020, Exemptions
  (amended March 21, 2002 ⇒ amended August 18, 2011)

- District Rule 2201, New and Modified Stationary Source Review Rule
  (amended December 15, 2005 ⇒ amended April 21, 2011)

- District Rule 4311, Flares
  (adopted June 20, 2002 ⇒ amended June 18, 2009)

- District Rule 4603, Surface Coating of Metal Parts and Products, Plastic Parts and Products and Pleasure Crafts
  (amended December 20, 2001 ⇒ amended September 17, 2009)

- District Rule 4606, Wood Products and Flat Wood Paneling Products Coating Operation
  (amended December 20, 2001 ⇒ amended October 16, 2008)

- District Rule 4702, Internal Combustion Engines – Phase 2
  (amended April 20, 2006 ⇒ amended August 18, 2011)

B. Rules Removed

None

C. Rules Added

40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines
(adopted July 11, 2006)

40 CFR Part 60, Subpart JJJJ, Standards of Performance for Stationary Spark Ignition Internal Combustion Engines
(adopted January 18, 2008)

40 CFR Part 63, Subpart ZZZZ, National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines
(adopted January 18, 2008)

D. Rules Not Updated

- District Rule 1080, Stack Monitoring
  (amended December 17,1992)
- District Rule 1081, Source Sampling
  (amended December 16,1993)
- District Rule 2520, Federally Mandated Operating Permits
  (amended June 21, 2001)
- District Rule 4201, Particulate Matter Concentration
  (amended December 17, 1992)
- District Rule 4202, Particulate Matter Emission Rate
  (amended December 17, 1992)
- District Rule 4301, Fuel Burning Equipment
  (amended December 17, 1992)
- District Rule 4694, Wine Fermentation and Storage Tanks (excluding wine fermentation provisions)
  (adopted December 15, 2005)
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM)[1]

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added

None

[1] The requirements of 40 CFR Part 64 have not been updated since the time of the last Title V permitting action. However, the requirements of this part were not previously addressed for most of the permit units in this project. In addition, the NO_X and VOC major source thresholds changed since the time of the last Title V permit renewal. Therefore, even though the requirements have not been updated since the time of the initial Title V permitting action, this part will be discussed in Section VII of this evaluation.

B. Rules Not Updated

- District Rule 1070, Inspections
  (amended December 17, 1992)

- District Rule 4102, Nuisance
  (amended December 17, 1992)

- District Rule 4694, Wine Fermentation and Storage Tanks
  (adopted December 15, 2005)

  The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any facility with VOC emissions in excess of 10 tons per year. For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons. The rule was adopted on December 15, 2005 and submitted to EPA for approval into the State Implementation Plan (SIP).

  On August 18, 2011, the District approved an amended SIP submittal which excludes the fermentation provisions of the rule while maintaining the storage provisions. Therefore, the fermentation provisions are not federally enforceable. All other provisions are federally enforceable and will be discussed in Section VIII of this application review under District Rule 4694.

  For this facility, the following conditions are based on this rule and are not Federally Enforceable through Title V:

N-2321-0-2	*Conditions 42 - 47*
N-2321-97 thru '-649	*Condition 8*
N-2321-652 thru '-792	*Condition 5*

- District Rule 4801, Sulfur Compounds
  (amended December 17, 1992)

- Title 17, California Code of Regulations, Section 93115 - Airborne Toxic Control Measure (ATCM) for Stationary Engines rated at 50 horsepower and greater
  (effective December 8, 2004*)*

- Title 17, California Code of Regulations, Sections 92200, 92500, 92530 and 92540 – Abrasive Blasting Operation Requirements

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit.

A. District Rule 2020 – Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits, and specifies recordkeeping requirements to verify such exemptions. The rule was amended in August 18, 2011. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201– New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this facility's initial Title V permit was issued. This Title V permit renewal does not constitute a modification per section 3.26, defined as an action including at least one of the following items:

1) Any change in hours of operation, production rate, or method of operation of an existing emissions unit, which would necessitate a change in permit conditions.
2) Any structural change or addition to an existing emissions unit which would necessitate a change in permit conditions. Routine replacement shall not be considered to be a structural change.
3) An increase in emissions from an emissions unit caused by a modification of the Stationary Source when the emissions unit is not subject to a daily emissions limitation.
4) Addition of any new emissions unit which is subject to District permitting requirements.
5) A change in a permit term or condition proposed by an applicant to obtain an exemption from an applicable requirement to which the source would otherwise be subject.

Therefore, the updated requirements of this rule are not applicable to the permits being renewed as a part of this project and no further discussion is required.

However, EPA has recently provided the District with comments on other winery Title V permit projects and indicated that the District was issuing permits without appropriate and practical recordkeeping requirements for annual emissions limitations. According to EPA policy, annual emission limits must be practically enforceable, which also goes on to say that to be practically enforceable, annual limits must be enforced on a short-term basis.

The District had previously committed to 12-month rolling recordkeeping to enforce annual limits in all Title V permits. In accordance with that committal, the District has recently developed winery tank conditions to address EPA's concerns regarding practically enforceable annual VOC emission limits. Therefore, the following conditions have been modified and/or added to the permits at this facility.

Compliance is assured with the following conditions:

N-2321-2 and '-7	*Conditions 3 and 4*
N-2321-6	*Conditions 14 and 21*
N-2321-8	*Conditions 16 and 17*
N-2321-10	*Conditions 8 and 9*
N-2321-97 thru '-649	*Conditions 11, 15, 16 and 17*
N-2321-652 thru '-792	*Conditions 11, 15, 16 and 17*

C. District Rule 2520 - Federally Mandated Operating Permits

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

D. District Rule 4311 – Flares

This rule limits the emissions of volatile organic compounds (VOC), oxides of nitrogen (NO_X), and sulfur oxides (SO_X) from the operation of flares. Therefore, the requirements of this rule are applicable to the flare operating under permit N-2321-651.

Section 5.1 applies to flares that are only permitted to operate during an emergency. The proposed flare is not limited to operate only during emergency situations. Therefore, the requirements of this section are not applicable.

Section 5.2 states that a flame shall be present at all times when combustible gases are vented through the flare.

Compliance is assured with the following condition:

N-2321-651	*Condition 3*

Section 5.3 requires the outlet be equipped with an automatic ignition system, or shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. The flare uses a continuous pilot flame.

Compliance is assured with the following condition:

N-2321-651	*Condition 4*

Section 5.4 requires that, except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, or an alternative equivalent device, capable of continuously detecting at least one pilot flame or the flare flame shall be installed or operated. The flare is with a flow-sensing ignition system.

Compliance is assured with the following condition:

N-2321-651	*Condition 8*

Section 5.5 requires that flares that use flow-sensing automatic ignition systems and which do not use a continuous pilot flame shall use purge gas for purging. The flare operated at this facility uses a flow-sensing automatic ignition system.

Compliance is assured with the following condition:

N-2321-651	*Condition 8*

Section 5.6 applies to open flares. This flare is an enclosed flare. Therefore the requirements of this section do not apply.

Section 5.7 establishes emission limits for ground level enclosed flares. The emission limits for flares rated between 10 and 100 MMBtu/hr which do not use steam assist are 0.0027 lb VOC/MMBtu and 0.1330 lb NO_X/MMBtu.

The proposed flare is required to meet emission limits of 0.0027 lb VOC/MMBtu and 0.06 lb NO_X/MMBtu.

Compliance is assured with the following condition:

N-2321-651	*Condition 11*

Section 5.8 states that effective on and after July 1, 2011, flaring is prohibited unless it is consistent with an approved flare minimization plan (FMP), pursuant to Section 6.5, and all commitments listed in that plan have been met.

Compliance is assured with the following condition:

N-2321-651	*Condition 2*

Section 5.9 discusses the petroleum refinery SO_2 performance targets. This facility is not a petroleum refinery. Therefore, the requirements of this section are not applicable.

Section 5.10 states that effective on and after July 1, 2011, the operator of a flare subject to flare minimization requirements pursuant to Section 5.8 shall monitor the vent gas flow to the flare with a flow measuring device or other parameters as specified in the Permit to Operate. The operator shall maintain records pursuant to Section 6.1.7. Flares that the operator can verify, based on permit conditions, are not capable of producing reportable flaring events pursuant to Section 6.2.2 shall not be required to monitor vent gas flow to the flare.

Compliance is assured with the following condition:

N-2321-651	*Condition 9*

Section 5.11 states that effective on and after July 1, 2011, the operator of a petroleum refinery or a flare with a flaring capacity equal to or greater than 50 MMBtu/hr shall monitor the flare pursuant to Sections 6.6, 6.7, 6.8, 6.9 and 6.10. This facility is not a petroleum refinery and the flare has a maximum heat input rating of 11.25 MMBtu/hr. Therefore, the requirements of this section are not applicable.

Section 6.1 states that the following records shall be maintained, retained on-site for a minimum of five years, and made available to the APCO, ARB, and EPA upon request:

- Copy of the compliance determination conducted pursuant to Section 6.4.1.
- Copy of the source testing result conducted pursuant to Section 6.4.2.
- For flares used during an emergency, record of the duration of flare operation, amount of gas burned, and the nature of the emergency situation.
- Operators claiming an exemption pursuant to Section 4.3 shall record annual throughput, material usage, or other information necessary to demonstrate an exemption under that section.

- Effective on and after July 1, 2011, a copy of the approved flare minimization plan pursuant to Section 6.5.
- Effective on and after July 1, 2012, where applicable, a copy of annual reports submitted to the APCO pursuant to Section 6.2.
- Effective on and after July 1, 2011, where applicable, monitoring data collected pursuant to Sections 5.10, 6.6, 6.7, 6.8, 6.9, and 6.10.

As discussed above, this flare is not subject to Sections 5.6 or 6.4.1, is not used as an emergency flare and is not claiming an exemption pursuant to Section 4.3. Therefore, compliance is assured with the following conditions:

N-2321-651	*Conditions 21 and 22*

Section 6.2.1 states that effective on and after July 1, 2011, the operator of a flare subject to flare minimization plans pursuant to Section 5.8 of this rule shall notify the APCO of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, whichever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time. The flare operated by this facility is subject to the requirements of Section 5.8. Therefore, the requirements of this section are applicable.

Compliance is assured with the following conditions:

N-2321-651	*Condition 19*

Section 6.2.2 states that effective on and after July 1, 2012, and annually thereafter, the operator of a flare subject to flare minimization plans pursuant to Section 5.8 shall submit an annual report to the APCO that summarizes all Reportable Flaring Events as defined in Section 3.0 that occurred during the previous 12 month period.

Compliance is assured with the following conditions:

N-2321-651	*Condition 20*

Section 6.2.3 states that effective on and after July 1, 2012, and annually thereafter, the operator of a flare subject to flare monitoring requirements pursuant to Sections 5.10, 6.6, 6.7, 6.8, 6.9, and 6.10, as appropriate, shall submit an annual report to the APCO within 30 days following the end of each 12 month period. The flare operated at this facility is not a petroleum refinery flare and is not rated at greater than 50 MMBtu/hr. Therefore, the flare is not subject to the requirements of Sections 6.6, 6.7, 6.8, 6.9, or 6.10. Therefore, the only reportable monitoring requirements are in accordance with Section 5.10.

Compliance is assured with the following conditions:

N-2321-651	*Condition 20*

Section 6.3.1 states that VOC, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case Method 25a may be used, and analysis of halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422 "Determination of Volatile organic Compounds in Emission from Stationary Sources". The VOC concentration in ppmv shall be converted to pounds per million Btu (lb/MMBtu) by using the following equation:

$$\text{VOC in lb/MMBtu} = \frac{(\text{ppmv dry}) \times (F, \text{dscf / MMBtu})}{(1.135 \times 10^5) \times (20.9 - \% O_2)}$$

Where: F = As determined by EPA Method 19

Section 6.3.2 requires that NO_X emissions in pounds per million BTU shall be determined by using EPA Method 19.

Section 6.3.3 requires that NO_X and O_2 concentrations shall be determined by using EPA Method 3A, EPA Method 7E, or ARB 100.

Section 6.3.4 states that effective on and after July 1, 2011 operators subject to vent gas composition monitoring requirements pursuant to Section 6.6 shall use the following test methods as appropriate, or by an alternative method approved by the APCO, ARB and EPA. As discussed above, the flare operated at this facility is not subject to the requirements of Section 6.6. Therefore, the requirements of Section 6.3.4 are not applicable.

Section 6.3.5 specifies flow verification test methods for units subject to Section 6.2.3.8. As discussed above, the flare operated at this facility is not subject to the requirements of Section 6.2.3.8. Therefore, the requirements of Section 6.3.5 are not applicable.

Compliance with the test method requirements listed above is assured with the following condition:

N-2321-651	*Condition 17*

Section 6.4.1 states that upon request, the operator of flares that are subject to Section 5.6 shall make available, to the APCO, the compliance determination records that demonstrate compliance with the provisions of 40 CFR 60.18, (c)(3) through (c)(5). As discussed above, this flare is not an open flare and is not subject to the requirements of Section 5.6. Therefore, the requirements of this section are not applicable.

Section 6.4.2 states that the operator of ground-level enclosed flares shall conduct source testing at least once every 12 months to demonstrate compliance with Section 5.7. The operator shall submit a copy of the testing protocol to the APCO at least 30 days in advance of the scheduled testing. The operator shall submit the source test results not later than 45 days after completion of the source testing.

Compliance is assured with the following conditions:

N-2321-651	*Conditions 15, 16 and 18*

Section 6.5.1 states that by July 1, 2010, the operator of a petroleum refinery flare or any flare that has a flaring capacity of greater than or equal to 5.0 MMBtu/hr shall submit a flare minimization plan (FPM) to the APCO for approval.

On June 30, 2010, under project 1103187, Woodbridge Winery submitted their flare minimization plan and received approval of that plan from the District. Therefore, the requirements of this section have been previously satisfied and are not applicable at this time.

Sections 6.6 through 6.10 all apply to petroleum refinery flares or flares with heat input ratings of 50.0 MMBtu/hr or greater. As discussed above, this facility is not a petroleum refinery and the flare has a maximum heat input rating of 11.25 MMBtu/hr. Therefore, the requirements of these sections are not applicable.

E. District Rule 4603 – Surface Coating of Metal Parts and Products, Plastic Parts and Products, and Pleasure Crafts

The purpose of this rule is to limit the emissions of volatile organic compounds (VOC) from the coating of metal parts and products, large appliances parts or products, metal furniture, plastic parts and products, automotive/transportation and business machine plastic parts and products, and pleasure crafts, and from the organic solvent cleaning and storage and disposal of solvents and waste solvent materials associated with such coating. This winery operates a metal parts and products coating operation under permit N-2321-8. Therefore, the requirements of this rule are applicable to that coating operation.

Sections 5.1 and 5.2 require that no person shall apply to any metal part or product any coating with a VOC content in excess of the following limits, expressed as grams of VOC per liter (or pounds per gallon) of coating applied, (less water and exempt compounds). These limits and the coatings proposed by the applicant are presented in the following table:

Coating Category	Allowable VOC content less water and exempt compounds, **baked** g/l (lb/gal)	Allowable VOC content less water and exempt compounds, **air-dried** g/l (lb/gal)
General Baked Coating	275 (2.3)	N/A
General Air-Dried Coating	N/A	340 (2.8)
Dip Coating of Steel Joists, air dried:		
a. coatings with a viscosity, as applied, of more than 45.6 centistokes at 78°F or an average dry-film thickness of greater than 2.0 mil	N/A	340 (2.8)
b. coatings with a viscosity, as applied, of less than or equal to 45.6 centistokes at 78°F and an average dry-film thickness of less than or equal to 2.0 mils	N/A	400 (3.32)

Specialty Coatings:		
	VOC Limit - Baked	VOC Limit – Air Dried
Camouflage	360 (3.0)	420 (3.5)
Extreme Performance	420 (3.5)	420 (3.5)
Heat Resistant	360 (3.0)	420 (3.5)
High Gloss	360 (3.0)	420 (3.5)
High Performance Architectual	420 (3.5)	420 (3.5)
High Temperature	420 (3.5)	420 (3.5)
Metallic Topcoat	360 (3.0)	420 (3.5)
Pretreatment Wash Primer	420 (3.5)	420 (3.5)
Silicone Release	420 (3.5)	420 (3.5)
Solar Absorbant	360 (3.0)	420 (3.5)
Solid Film Lubricant	880 (7.3)	880 (7.3)

Compliance is assured with the following conditions:

N-2321-8-6	*Conditions 3, 4 and 5*

Sections 5.4 through 5.7 apply to large appliance parts or products coating operations, metal furniture coating operations, plastic parts and products coating operations, automotive/transportation and business machine plastic parts and products coating operations and pleasure craft coating operations. The coating operation at this facility is strictly a metal parts and products coating operation. Therefore, the requirements of these sections are not applicable.

Section 5.8 specifies requirements for VOC emission control systems. This metal parts and products coating operation is not served by a VOC emission control system. Therefore, the requirements of this section are not applicable.

Section 5.9 specifies certain work practice standards that minimize opportunities for VOC emissions.

Compliance is assured with the following condition:

N-2321-8-6	*Condition 11*

Section 5.10.1 states that an operator shall not use organic solvents for cleaning operations that exceed the VOC content limits specified in the following table:

Cleaning Solvent Use	Allowable VOC content less water and exempt compounds g/l (lb/gal)
Product Cleaning During Manufacturing Process or Surface Preparation for Coating Application	25 (0.21)
Repair and Maintenance Cleaning	25 (0.21)
Cleaning of Coating Application Equipment	25 (0.21)

Compliance is assured with the following condition:

N-2321-8-6	*Condition 12*

Section 5.11 requires that an owner or operator shall store or dispose of fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty.

Compliance is assured with the following condition:

N-2321-8-6	*Condition 13*

Section 5.12 requires that a person shall not use or operate any coating application equipment on any metal parts and products subject to the provisions of this rule unless one of the following methods is used:

- Electrostatic application;
- Electrodeposition;
- High-Volume, Low-Pressure (HVLP) spray;
- Flow coating;
- Roll coating;
- Dip coating;
- Brush coating; or
- Continuous coating.

In addition Section 5.12.3.1 requires that High-Volume, Low-Pressure (HVLP) spray equipment shall be operated in accordance with the manufacturer's recommendations. Section 5.12.3.2 requires that for HVLP spray guns manufactured prior to January 1, 1996, the end user shall demonstrate that the gun meets HVLP spray equipment standards. Satisfactory proof will be either in the form of manufacturer's published technical material or by a demonstration using a certified air pressure tip gauge, measuring the air atomizing pressure dynamically at the center of the air cap and at the air horns.

Compliance is assured with the following conditions:

N-2321-8-6	*Conditions 9 and 10*

Section 6.1.1 requires that each container or accompanying data sheet of any coating shall display the maximum VOC content of the coating, as applied, and after any thinning recommended by the manufacturer. The VOC content shall be displayed as grams of VOC per liter of coating (less water and exempt compounds). Section 6.1.2 requires that each container or accompanying data sheet display a statement of the manufacturer's recommendation regarding thinning of the coating.

Compliance is assured with the following condition:

N-2321-8-6	*Condition 19*

Section 6.2.1 requires that any person subject to Section 5.0 shall comply with the following requirements: Maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information, as applicable:

- mix ratio of components used,
- VOC content and specific chemical constituents of coatings as applied, and
- VOC content and specific chemical constituents of solvents used for surface preparation and cleanup.

Section 6.2.2 requires that the permittee maintain records which include the following information:

- volume coating/solvent mix ratio,
- VOC content(lb/gal) and, for dip coating operations, viscosity (cSt) of coating,
- volume of each coating used (gallons), and
- quantity of cleanup solvent used (gallons).

Compliance is assured with the following conditions:

N-2321-8-6	*Conditions 20 and 21*

Section 6.2.4 requires that consistent records may be kept in grams/liter and liters instead of pounds/gallon and gallons. An owner or operator of a stationary source subject to this rule shall maintain such records on a daily basis. An owner or operator that is subject to the exemption of Section 4.2 may maintain usage records of non-compliant coatings on the days that such non-compliant coatings are used.

Section 6.2.5 requires that the operator retain the records specified in Sections 6.2.1 through 6.2.4, as applicable, on site for a period of five years, make the records available on site during normal business hours to the APCO, ARB, or EPA and submit records to the APCO, ARB, or EPA upon request.

Compliance is assured with the following condition:

N-2321-8-6	*Condition 23*

Section 6.3 specifies the test methods for determining compliance with various rule requirements. However, the permit for this metal parts and products coating operation does not specifically require the applicant to perform testing to demonstrate ongoing compliance. Therefore, the test methods specified in this section will not be included on the permit.

F. District Rule 4606 – Wood Products and Wood Into Stationary Storage Containers, Delivery Vessels, and Bulk Plants

The purpose of this rule is to limit the emissions of volatile organic compounds (VOCs) from wood products coating operations, and from the organic solvent cleaning, and the storage and disposal of solvents and waste solvent materials associated with such coating operations. The rule also provides the administrative requirements for recording and measuring emissions. This winery operates two wood products coating operations under permit N-2321-8 and '-10. Therefore, the requirements of this rule are applicable to these coating operations.

Section 5.1 requires that no person shall apply to any wood product any coating with a VOC content in excess of the following limits, expressed as grams of VOC per liter (or pounds per gallon) of coating applied, (less water and exempt compounds).

Coating Category	VOC Limit – grams/liter	VOC Limit – lb/gallon
Table 1:		
Clear Topcoat	275	2.3
Filler	275	2.3
High Solids Stain	240	2.0
Ink	500	4.2
Mold-Seal Coating	750	6.3
Multi-Colored Coating	275	2.3
Pigmented Coating	275	2.3
Sanding Sealer	275	2.3
Table 2:		
Low-Solids Stain	120	1.0
Stripper	350	2.9

Compliance is assured with the following conditions:

N-2321-8-6	*Conditions 6 and 7*
N-2321-10-6	*Conditions 2 and 3*

Section 5.2 specifies that the VOC emission limit requirements of Section 5.1 above are not applicable to facilities using an APCO approved emissions control system. The wood products coating operations at this facility are not served by any VOC emission control systems. Therefore, the requirements of this section are not applicable.

Section 5.3 applies to flat wood paneling products coating operations. The coating operations at this facility are wood products coating operations, however, they do not coat any flat wood paneling. Therefore, the requirements of this section are not applicable.

Section 5.4 specifies the requirements for VOC emission control systems. As stated above, this facility does not use an APCO approved VOC emission control system for either of their coating operations. Therefore, the requirements of this section are not applicable.

Section 5.5 requires that an operator shall not apply coatings to wood products subject to the provisions of this rule unless the coating is applied with properly operating equipment, according to proper operating procedures, and by the use of one of the following methods:

- Electrostatic application;
- High-Volume, Low-Pressure (HVLP) spray;
- Hand Roller;
- Flow Coat;
- Roll Coater;
- Dip Coating;
- Paint Brush;
- Detailing or Touch-Up Guns; or
- Such other coating application methods which are demonstrated to the APCO to be capable of achieving at least 65 percent transfer efficiency as determined in accordance with Section 6.6. Prior written approval from the APCO shall be obtained for each alternative method used.

In addition Section 5.5.2.1 requires that High-Volume, Low-Pressure (HVLP) spray equipment shall be operated in accordance with the manufacturer's recommendations. Section 5.5.2.2 requires that for HVLP spray guns manufactured prior to January 1, 1996, the end user shall demonstrate that the gun meets HVLP spray equipment standards. Satisfactory proof will be either in the form of manufacturer's published technical material or by a demonstration using a certified air pressure tip gauge, measuring the air atomizing pressure dynamically at the center of the air cap and at the air horns.

Compliance is assured with the following conditions:

N-2321-8-6	*Conditions 9 and 10*
N-2321-10-6	*Condition 1*

Section 5.6 specifies certain work practice standards for flat wood paneling products coating operations. As discussed above, this facility does not coat flat wood paneling. Therefore, the requirements of this section are not applicable.

Section 5.7 states that an operator shall not use organic solvents for cleaning operations that exceed the VOC content limits specified in the following table:

Cleaning Solvent Use	Allowable VOC content less water and exempt compounds g/l (lb/gal)
Product Cleaning During Manufacturing Process or Surface Preparation for Coating Application	25 (0.21)
Repair and Maintenance Cleaning	25 (0.21)
Cleaning of Coating Application Equipment	25 (0.21)

In addition, section 5.7.2 states that an operator shall not use a strippable booth coating with a VOC content in excess of 450 g/l (3.8 lb/gal) as applied, less water and exempt compounds. The coating operation under PTO N-2321-10 takes place outside of a paint spray booth. Therefore, the requirements of this section are only applicable to PTO N-2321-8.

Compliance is assured with the following conditions:

N-2321-8-6	*Conditions 8 and 11*
N-2321-10-6	*Conditions 4 and 5*

Section 5.8 requires that an operator shall store or dispose of fresh or spent solvents, waste solvent cleaning materials such as cloth, paper, etc., coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers. The containers shall remain closed at all times except when depositing or removing the contents of the containers or when the container is empty.

Compliance is assured with the following condition:

N-2321-8-6	*Condition 13*
N-2321-10-6	*Condition 6*

Section 6.1 requires that the operator retain the records specified in Sections 6.1 through 6.4, as applicable, on site for a period of five years, make the records available on site during normal business hours to the APCO, ARB, or EPA and submit records to the APCO, ARB, or EPA upon request.

Section 6.2.1 requires that any person subject to Section 5.1 shall comply with the following requirements: Maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information, as applicable:

- Identify coatings, catalysts, reducers, inks, adhesives and solvents,
- manufacturer's recommended mix ratio of components
- VOC content of coatings, as applied
- VOC content of solvents
- VOC content of inks, as applied, and
- VOC content of adhesives, as applied.

Section 6.2.2 requires that the permittee maintain records on a daily basis which include the following information:

- Coating and mix ratio of components used in coating,
- Quantity of each coating used,
- Identification of coating category,
- Identification and quantity of each ink used,
- Identification and quantity of each adhesive used, and
- Type and amount of solvent used for cleanup and surface preparation (gallons).

Section 6.3 specifies recordkeeping requirements for facilities claiming exemption under section 4.3, Custom Replica Furniture Operations. This facility is not claiming exemption under section 4.3, therefore, the requirements of this section are not applicable.

Section 6.4 requires that an operator who uses solvents subject to Section 5.7 of this rule shall maintain the following records, and have available at all times, a current list of solvents in use which provides all of the data necessary to evaluate compliance, including the following information as applicable:

- Keep a copy of the manufacturer's product data sheet or material safety data sheet of the solvents used for organic solvent cleaning activities,
- Maintain a current list of solvents that are being used for organic solvent cleaning activities. The list shall include the following information VOC content of coatings, as applied:

- The name of the solvent and its manufacturer's name,
- The VOC content of the solvent expressed in grams/liter or lb/gallon,
- When the solvent is a mixture of different materials that are blended by the operator, the mix ratio of the batch shall be recorded and the VOC content of the batch shall be calculated and recorded in order to determine compliance with the specified limits of VOC content, as applied
- The type of cleaning activity for each solvent that is being used in accordance with the applicable cleaning category specified in Table 4 of this rule.

Section 6.5 requires records for VOC control systems. As discussed above, this facility does not operate a VOC control system. Therefore, the requirements of this section are not applicable.

Compliance with these sections is assured with the following conditions:

N-2321-8-6	*Conditions 20 thru 23*
N-2321-10-6	*Conditions 12 thru 15*

Section 6.6 specifies the following labeling requirements for VOC content and thinning recommendations:

- Each container or accompanying data sheet of any coating subject to this rule shall display the maximum VOC content of the coating, as applied after any thinning as recommended by the manufacturer. VOC content shall be displayed as grams of VOC per liter (or pounds of VOC per gallon) of coating, less water and exempt compounds.
- Each container or accompanying data sheet of any coating subject to this rule shall display the manufacturer's recommendation regarding thinning of the coating. This requirement shall not apply to the thinning of coatings with water.

Compliance is assured with the following condition:

N-2321-8-6	*Condition 19*
N-2321-10-6	*Condition 11*

Section 6.7 specifies compliance statement requirements for coating manufacturer's. This facility does not manufacture any coatings; therefore, the requirements of this section are not applicable.

Section 6.8 specifies the test methods for determining compliance with various rule requirements. However, the two coating permits at this facility are for metal parts and products and wood products coating operations and do not specifically require the applicant to perform testing to demonstrate ongoing compliance with the coating and solvent VOC content limits. Therefore, the test methods specified in this section will not be included as conditions on these permits.

G. District Rule 4694 – Wine Fermentation and Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. The rule is applicable to any facility with VOC emissions in excess of 10 tons per year. For those facilities to which the rule applies, the requirements of the rule are applicable to any fermentation or storage tank with capacity in excess of 5,000 gallons.

This facility is a winery with VOC emissions greater than 10 tons per year. Each of the tanks operated at this facility are greater than 5,000 gallons in capacity. Therefore, the requirements of this rule are applicable to this facility.

As previously discussed in Section VII.A above, on August 18, 2011 the District approved an amended SIP submittal which excludes the fermentation provisions of District Rule 4694 while maintaining the storage provisions. Therefore, only the storage provisions are federally enforceable and will be discussed below.

Section 5.2 states that owners or operators of any wine storage tank having an internal volume equal to or greater than 5,000 gallons shall comply with the following requirements when storing wine:

5.2.1 The tank shall be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements:

- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,
- The pressure-vacuum relief valve shall operate in accordance with the manufacturer's instructions, and
- The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings.
- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21.

5.2.2 The temperature of the stored wine shall be maintained at or below 75° F.

- Temperature of the stored wine shall be determined and recorded at least once per week.
- For each batch of wine, operators shall achieve the storage temperature of 75° F or less within 60 days after completing fermentation.

The tanks under permits N-2321-121 thru '-126, '-140 thru '-150, '-241 thru '-250, '-637 thru '-641 and '-652 thru '-673 each have a maximum storage capacity of less than 5,000 gallons. Therefore, the requirements of section 5.2 do not apply to these tanks.

For the remaining tanks, compliance is assured with the following conditions:

N-2321-97 thru '-120	*Conditions 3, 4 and 5*
N-2321-127 thru '-139	*Conditions 3, 4 and 5*
N-2321-151 thru '-240	*Conditions 3, 4 and 5*
N-2321-251 thru '-636	*Conditions 3, 4 and 5*
N-2321-642 thru '-648	*Conditions 3, 4 and 5*
N-2321-677 thru '-792	*Conditions 3, 4 and 5*

Section 6.4 states that commencing January 1, 2007, the following records shall be maintained, retained on-site for a minimum of five years, and made available to the APCO upon request:

6.4.2 For each storage tank, operators shall record the following information on a weekly basis:

- Total gallons of wine contained in the tank, and
- Maximum temperature of the stored wine.

For all tanks, compliance is assured with the following conditions:

N-2321-97 thru '-649	*Conditions 9 and 16*
N-2321-652 thru '-792	*Conditions 9 and 16*

H. District Rule 4702 – Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NO_x), carbon monoxide (CO), and volatile organic compounds (VOC) from internal combustion engines. This rule applies to any internal combustion engine with a rated brake horsepower greater than 25 horsepower.

Current District Rule 4702 (amended 8/18/11) has not been SIP approved. Attachment D contains the streamlining of the SIP approved District Rule 4702 (1/18/07) to the current District Rule 4702 to show the current rule is as stringent, if not more stringent, than the SIP approved version.

Emergency IC Engines:

This facility operates one 128 bhp propane fired emergency standby IC engine (N-2321-6), one 133 bhp diesel fired emergency IC engine (N-2321-11), one 115 bhp diesel fired emergency IC engine (N-2321-12) and one 97 bhp diesel fired emergency standby IC engine (N-2321-13). Therefore, the requirements of this rule are applicable to these four emergency IC engines.

Section 4.2 states that except for the requirements of Sections 5.9 and 6.2.3, the requirements of this rule shall not apply to an emergency standby engine or a low-use engine, provided that the engine is operated with an operating nonresettable elapsed time meter. Woodbridge Winery operates two emergency standby engines under PTO's N-2321-6 and N-2321-13. These two engines will only be subject to the requirements of Section 5.9 and 6.2.3.

Section 4.3 states that except for the administrative requirements of Section 6.2.3, the requirements of this rule shall not apply to an internal combustion engine that meets the following conditions:

> The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood; and
> The engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed time meter, for periodic maintenance, periodic readiness testing; and readiness testing during and after repair work of the engine; and
> The engine is operated with an operational nonresettable elapsed time meter. In lieu of installing a nonresettable elapsed time meter, the operator of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA. The operator of the engine shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions.

Woodbridge Winery operates two emergency engines under PTO's N-2321-11 and N-2321-12 for fire protection services. These two engines will only be subject to the requirements of Section 6.2.3.

Section 5.9 specifies monitoring requirements for all other engines not included in Section 5.8 above. The monitoring shall consist of the following:

- Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.
- Monitor the operational characteristics or each engine as recommended by the engine manufacturer or emission control system supplier.
- Install and operate a nonresettable elapsed time meter.

Compliance is assured with the following conditions:

N-2321-6	*Conditions 2, 12 and 18*
N-2321-13	*Conditions 2, 10 and 14*

Section 6.2.3 requires that an operator claiming an exemption under Section 4.2 or Section 4.3, shall maintain annual operating records. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The records shall include, but are not limited to, the following:

- Total hours of operation,
- Type of fuel used,
- The purpose for operating the engine,
- For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and
- Other support documentation necessary to demonstrate claim to the exemption.

Compliance is assured with the following conditions:

N-2321-6	*Condition 19*
N-2321-11 and '-12	*Condition 14*
N-2321-13	*Condition 15*

Full Time IC Engines:

This facility operates two additional 122 bhp natural gas or digester gas fired full time IC engines (N-2321-649 and N-2321-650). Therefore, the requirements of this rule are applicable to these two full time IC engines.

Section 5.1 applies to stationary engines rated at 25 bhp up to and including 50 bhp. The engines operated at this facility are each rated with a maximum horsepower rating of 122 bhp. Therefore, the requirements of this section are not applicable.

Section 5.2 states that operators of spark-ignited internal combustion engines rated at greater than 50 bhp that is used exclusively in non-agricultural operations shall not operate it in such a manner that results in emissions exceeding the limits in Table 2 for the appropriate engine type.

Rule 4702 Emission Limits, Table 2			
Engine Type	NO_X Limit (ppmv @ 15% O_2)	CO Limit (ppmv @ 15% O_2)	VOC Limit (ppmv @ 15% O_2)
1. Rich Burn			
a. Waste Gas Fueled	50	2000	250
b. Cyclic Loaded, Field Gas Fueled	50	2000	250
c. Limited Use	25	2000	250
d. Rich-Burn Engine, not listed above	11	2000	250

The engines operating at this facility are operating with NO_X emissions of 11 ppmv @ 15% O_2, CO emissions of 70 ppmvd @ 15% O_2, and VOC emissions of 51 ppmvd @ 15% O_2. Therefore, the engine is operating in compliance with the requirements of this section.

Compliance is assured with the following condition:

N-2321-649 and '-650	*Condition 7*

Section 5.3 requires that all continuous emission monitoring systems (CEMS) emissions measurements shall be averaged over a period of 15 consecutive minutes. The engines operated at this facility are not equipped with a CEMS. Therefore the requirements of this section are not applicable.

Sections 5.4 and 5.5 are applicable to engines that use percent reduction to comply with the NO_X emission limits specified in Section 5.2. The engines at this facility are meeting the NO_X emission limit specified in Table 2 of Section 5.2 and are not using percent reduction to demonstrate compliance with the NO_X emission limits of Section 5.2. Therefore, the requirements of these sections are not applicable.

Section 5.6 specifies requirements for paying an annual emissions fee in lieu of complying with the NO_X emission limits specified in Section 5.2. Both engines comply with the NO_X emission limits specified in Section 5.2. Therefore, this facility does not need to pay the annual fee option and the requirements of this section are not applicable.

Section 5.7 specifies requirements for sulfur oxide emission control requirements. Section 5.7.1 states that an engine be operated on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases. Section 5.7.2 states that the operator shall limit the gaseous fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet.

As shown above, these engines are fired on PUC-quality natural gas or digester gas. When fired on PUC-quality natural gas, the engines meet the requirements of Section 5.7.1. The current permits also limit the H_2S content of the digester gas burned in these engines to 25 ppmvd. Converting this fuel H_2S ppmvd to a fuel sulfur content results in a maximum sulfur content of 1.57 grains/100 dscf. Therefore, the digester gas combusted in these engines meets the requirements of Section 5.7.2.

Compliance is assured with the following conditions:

N-2321-649 and '-650	*Conditions 4 and 5*

Section 5.8 states that each non-agricultural operation spark ignited engine that is equipped with a control device shall either install, operate, and maintain a continuous emission monitoring equipment for NO_X, CO, and oxygen, or install, operate, and maintain APCO-approved alternate monitoring. The monitoring system may be a continuous emissions monitoring system (CEMS), a parametric emissions monitoring system (PEMS), or an alternative monitoring system approved by the APCO. In order to satisfy the requirements of this section, the engines at this facility are currently required to monitor and record the stack concentration of NO_X, CO and O_2 at least once every month.

Compliance is assured with the following conditions:

N-2321-649 and '-650	*Conditions 8, 9, 10 and 11*

Section 5.9 specifies monitoring requirements for all other engines. As shown above, the engines operated at this facility are subject to the monitoring requirements of Section 5.8. Therefore, the requirements of this section are not applicable.

Section 5.10 specifies that an operator of an engine complying with the SO_X Emissions Monitoring requirements of Section 5.7.2 shall perform an annual sulfur fuel analysis in accordance with the test methods in Section 6.4. The engines operated at this facility will be required to perform an annual fuel sulfur analysis for digester gas only.

Compliance is assured with the following condition:

N-2321-649 and '-650	*Condition 15*

Section 5.11 specifies requirements for permit-exempt equipment registrations. The engines operated at this facility are subject to permit requirements and are not permit-exempt. Therefore, the requirements of this section are not applicable.

Section 6.1 requires that the owner of an engine to submit to the APCO an emission control plan of all actions to be taken to satisfy the emission requirements of Section 5.2 and the compliance schedules of Section 7.0. The engines operated at this facility are already in compliance with the most current requirements of Rule 4702. Therefore, the requirements of this section have been satisfied.

Section 6.2.1 requires that engines subject to Section 5.2, the owner of an engine subject to the requirements of this rule shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine operating log shall include, on a monthly basis, the following information:

- Total hours of operation,
- Type of fuel used,
- Maintenance or modifications performed,
- Monitoring data,
- Compliance source test results, and
- Any other information necessary to demonstrate compliance with this rule.

Compliance is assured with the following condition:

N-2321-649 and '-650	*Condition 21*

Section 6.3 specifies compliance testing requirements for the following engines:

- Engines retrofitted with an exhaust control device
- Engines subject to Section 8.0
- An AO spark-ignited engine that is subject to the requirements of Section 8.0
- An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0.

The engines operated at this facility are equipped with non-selective catalytic reduction systems on their exhaust stacks. Therefore, they are required to meet the compliance testing requirements.

Section 6.3.2 states that the operator shall demonstrate compliance with applicable emission limits at least once every 24 months.

Compliance is assured with the following condition:

N-2321-649 and '-650	*Condition 14*

Section 6.4 specifies the test methods which shall be used during compliance testing of Section 6.3.

- Oxides of nitrogen – EPA Method 7E, or ARB Method 100
- Carbon Monoxide – EPA Method 10, or ARB Method 100
- Stack gas oxygen – EPA Method 3 or 3A, or ARB Method 100
- Volatile Organic Compounds – EPA Method 25A or 25B, or ARB Method 100. Methane or ethane, which are exempt compounds, shall be excluded from the result of the test.
- Operating horsepower determination – any method approved by EPA and the APCO
- SO_X Test Methods
  - Oxides of Sulfur – EPA Method 6C, EPA Method 8, or ARB Method 100
  - Determination of total sulfur as hydrogen sulfide (H_2S) content – EPA Method 11 or EPA Method 15, as appropriate.
  - Sulfur content of liquid fuel – American Society of Testing and Materials (ASTM) D 6920-03 or ASTM D 5453-99.
  - SO_X emission control system efficiency shall be determined using the following: %control efficiency = $[(C_{SO2,\ inlet} - C_{SO2,\ outlet}) / C_{SO2,\ inlet}] \times 100$

Compliance is assured with the following condition:

N-2321-649 and '-650	*Condition 18*

Section 6.5 requires that the owner of an engine subject to the requirements of Section 5.2 or the requirements of Section 8.0, shall submit to the APCO for approval, an I&M plan that specifies all actions to be taken to satisfy the requirements of Section 6.5.2 through and 6.5.9. Section 6.5.1 states that sections 6.5.2 through 6.5.9 shall only apply to the following engines:

- Engines retrofitted with an exhaust control device
- Engines subject to Section 8.0
- An AO spark-ignited engine that is subject to the requirements of Section 8.0
- An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0.

The engines operated at this facility are equipped with non-selective catalytic reduction systems on their exhaust stacks. Therefore, they are required to meet the I&M requirements of this rule.

Compliance is assured with the following conditions:

N-2321-649 and '-650	*Conditions 2 and 22*

I. 40 CFR Part 60 Subpart IIII – Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

N-2321-11, '-12 and '-13:

Section 60.4200 states that the provisions of this subpart are applicable to manufacturers, owners, and operators of stationary compression ignition (CI) internal combustion engines (ICE) and other persons as specified in paragraphs (a)(1) through (4) of this section. Sections (a)(1) through (4) specify the following:

Section (a)(1) applies to manufacturers of engines. This facility does not manufacture engines. Therefore, the requirements of this section are not applicable.

Section (a)(2) specifies requirements for owners and operators of stationary CI ICE that commenced construction after July 11, 2005. Pursuant to information in the facility files, all three of the CI ICE's operated at this facility were installed in the 1980's. Therefore, the requirements of this section are not applicable.

Section (a)(3) states that owners and operators of stationary CI ICE that are modified or reconstructed after July 11, 2005, and any person that modifies or reconstructs any stationary CI ICE after July 11, 2005. As discussed above, the engines were installed at this facility in the 1980's and have not been modified or reconstructed since installation. Therefore, the requirements of this section are not applicable.

Section (a)(4) states that the provisions of Section 60.4208 of this subpart are applicable to all owners or operators of stationary CI ICE that commenced construction after July 11, 2005. As discussed above, the engines operated at this facility were installed in the 1980's. Therefore, the engines commenced construction before July 11, 2005 and the requirements of Section 60.4208 are not applicable.

Conclusion:

Since the three diesel fired emergency IC engines operated at this facility are existing engines in place and operating prior to July 11, 2005, the requirements of 40 CFR 60, Subpart IIII are not applicable.

J. 40 CFR Part 60 Subpart JJJJ – Standards of Performance for Stationary Spark Ignited Internal Combustion Engines

Section 60.4230 states that the provisions of this subpart are applicable to manufacturers, owners, and operators of stationary spark ignition (SI) internal combustion engines (ICE) as specified in paragraphs (a)(1) through (6) of this section.

Emergency IC Engine:

This facility operates one spark ignited propane fired emergency IC engine under permit N-2321-6. For this engine, sections (a)(1) through (6) specify the following:

Sections (a)(1) through (a)(3) apply to manufacturers of engines. This facility does not manufacture engines. Therefore, the requirements of these sections are not applicable.

Section (a)(4) states that owners and operators of stationary SI ICE that commence construction after June 12, 2006. This propane fired emergency engine was installed in 1996. Therefore, construction did not commence after June 12, 2006 and the requirements of this section are not applicable.

Section (a)(5) states that owners and operators of stationary SI ICE that are modified or reconstructed after June 12, 2006, and any person that modifies or reconstructs any stationary SI ICE after June 12, 2006. As discussed above, this engine was installed at this facility in 1996 and has not been modified or reconstructed since installation. Therefore, the requirements of this section are not applicable.

Section (a)(6) states that the provisions of Section 60.4236 of this subpart are applicable to all owners or operators of stationary SI ICE that commence construction after June 12, 2006. As discussed above, this emergency engine was installed in 1996. Therefore, the requirements of this section are not applicable.

Since the spark ignited propane fired emergency IC engine operating under PTO N-2321-6 was installed prior to June 12, 2006, the requirements of Subpart JJJJ are not applicable to this unit.

Full Time IC Engines:

This facility operates two spark ignited natural gas/digester gas fired IC engines under permits N-2321-649 and '-650.

Sections (a)(1) through (a)(3) apply to manufacturers of engines. This facility does not manufacture engines. Therefore, the requirements of these sections are not applicable.

Section (a)(4) states that owners and operators of stationary SI ICE that commence construction after June 12, 2006, where the stationary SI ICE are manufactured:

(i) On or after July 1, 2007, for engines with a maximum engine power greater than or equal to 500 HP (except lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1,350 HP); or
(ii) On or after January 1, 2008, for lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1350 HP; or
(iii) On or after July 1, 2008, for engines with a maximum engine power less than 500 HP; or
(iv) On or after January 1, 2009, for emergency engines with a maximum engine power greater than 19 KW (25 HP).

This facility operates two full IC time engines under permits N-2321-649 and '-650. These engines were installed on April 1, 2009 and are rated with a maximum power output of 122 HP. In addition, the facility provided information from each engines data plate that indicates the engines were manufactured in 2007. Therefore, the engines operated at this facility do not meet any of the applicability requirements specified above and the requirements of this section are not applicable.

Section (a)(5) states that owners and operators of stationary SI ICE that are modified or reconstructed after June 12, 2006, and any person that modifies or reconstructs any stationary SI ICE after June 12, 2006. As discussed above, the engines were installed at this facility in 2007 and have not been modified or reconstructed since installation. Therefore, the requirements of this section are not applicable.

Section (a)(6) states that the provisions of Section 60.4236 of this subpart are applicable to all owners or operators of stationary SI ICE that commence construction after June 12, 2006. As discussed above, the engines operated at this facility were installed on April 1, 2009. Therefore, the engines commenced construction after June 12, 2006 and the requirements of Section 60.4236 are the only requirements of this subpart applicable to these engines.

Section 60.4236 specifies the following requirements for importing or installing stationary SI ICE produced in previous model years:

Section (a) states that after July 1, 2010, owners and operators may not install stationary SI ICE with a maximum engine power of less than 500 HP that do not meet the applicable requirements in Section 60.4233. As discussed above, the engines at this facility are rated at 122 HP and were installed in 2007. Therefore, the requirements of this section are not applicable.

Section (b) states that after July 1, 2009, owners and operators may not install stationary SI ICE with a maximum engine power of greater than or equal to 500 HP that do not meet the applicable requirements in Section 60.4233, except lean burn engines with a maximum engine power greater than or equal to 500 HP and less than 1350 HP that do not meet the applicable requirements in Section 60.4233 may not be installed after January 1, 2010. As discussed above, the engines at this facility are rated at 122 HP. Therefore, the requirements of this section are not applicable.

Section (c) states that for emergency SI ICE with a maximum engine power output of greater than 19 KW (25 HP), owners and operators may not install engines that do not meet the applicable requirements in Section 60.4233 after January 1, 2011. The engines at this facility are not emergency SI ICE. Therefore, the requirements of this section are not applicable.

Section (d) states that in addition to the requirements specified in Sections 60.4231 and 60.4233, is it prohibited to import stationary SI ICE less than or equal to 19 KW (25 HP), stationary rich burn LPG SI ICE, and stationary gasoline SI ICE that do not meet the applicable requirements specified in paragraphs (a), (b), and (c) of this section, after the date specified in paragraph (a), (b), and (c) of this section. This facility does not operate any engines that combust LPG fuel or gasoline and they do not have engines with a maximum rating of less than or equal to 25 HP. Therefore, the requirements of this section are not applicable.

Section (e) states that the requirements of this section do not apply to owners and operators of stationary SI ICE that have been modified or reconstructed, and they do not apply to engines that were removed from one existing location and reinstalled at a new location. These engines were installed as new engines at this facility in 2009. The engines have not been modified or reconstructed and were not removed from one existing location and reinstalled at a new location. Therefore, the requirements of this section are not applicable.

K. 40 CFR Part 63 Subpart ZZZZ – National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Section 63.6585 states that you are subject to this subpart if you own or operate a stationary reciprocating internal combustion engines (RICE) at a major or area source of HAP emissions, except if the stationary RICE is being tested at a stationary RICE test cell/stand.

A major source of HAP emissions is a plant site that emits or has the potential to emit any single HAP at a rate of 10 tons or more per year or any combination of HAP at a rate of 25 tons or more per year, except for oil and gas production facilities, a major source of HAP emissions is determined for each surface site. An area source of HAP emissions is a source that is not a major source.

This facility operates one propane fired emergency RICE, three diesel fired emergency RICE's and two natural gas/digester gas fired full time RICE's. The facility does not emit any single HAP at a rate of 10 tons per year and does not emit a combination of HAP's at a rate of 25 tons per year. Therefore, this facility can be classified as an area source of HAP emissions and the requirements of this subpart are applicable to these engines.

Emergency IC Engines:

§ 63.6590 What parts of my plant does this subpart cover?

This subpart applies to each affected source.

(a) *Affected source*. An affected source is any existing, new, or reconstructed stationary RICE located at a major or area source of HAP emissions, excluding stationary RICE being tested at a stationary RICE test cell/stand.

This facility is an area source of HAP emissions; therefore, this subpart applies.

(1) Existing stationary RICE

(iii) For stationary RICE located at an area source of HAP emissions, stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.

The four emergency engines (PTO's N-2321-6, '-11, '-12 and '-13) operating at this facility are defined as "existing" since installation was prior to June 12, 2006.

(2) New stationary RICE

(iii) A stationary RICE located at an area source of HAP emissions is new if you commenced construction of the stationary RICE on or after June 12, 2006.

The emergency engines operating at this facility were all installed prior to June 12, 2006 and are not considered new per this subpart.

(3) The following stationary RICE do not have to meet the requirements of this subpart and of subpart A of this part, including initial notification requirements:

(i) Existing spark ignition 2 stroke lean burn (2SLB) stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;

(ii) Existing spark ignition 4 stroke lean burn (4SLB) stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;
(iii) Existing emergency stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;
(iv) Existing limited use stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions;
(v) Existing stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;
(vi) Existing residential emergency stationary RICE located at an area source of HAP emissions;
(vii) Existing commercial emergency stationary RICE located at an area source of HAP emissions; or
(viii) Existing institutional emergency stationary RICE located at an area source of HAP emissions.

The existing emergency engines at this facility do not qualify for any of the exemptions listed in (3)(i) thru (3)(viii) above.

(c) *Stationary RICE subject to Regulations under 40 CFR Part 60.* An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines. No further requirements apply for such engines under this part.

(1) A new or reconstructed stationary RICE located at an area source;
(2) A new or reconstructed 2SLB stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;
(3) A new or reconstructed 4SLB stationary RICE with a site rating of less than 250 brake HP located at a major source of HAP emissions;
(4) A new or reconstructed spark ignition 4 stroke rich burn (4SRB) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;
(5) A new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis;
(6) A new or reconstructed emergency or limited use stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions;
(7) A new or reconstructed compression ignition (CI) stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions.

All of the emergency engines operated at this facility are classified as existing engines per this subpart. Therefore, the requirements of section (c) above are not applicable.

§ 63.6595 When do I have to comply with this subpart?

(a) *Affected sources.* (1) If you have an existing stationary RICE, excluding existing non-emergency CI stationary RICE, with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than June 15, 2007. If you have an existing non-emergency CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, an existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary CI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than May 3, 2013. If you have an existing stationary SI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or an existing stationary SI RICE located at an area source of HAP emissions, you must comply with the applicable emission limitations and operating limitations no later than October 19, 2013.

Permit units '-11, '-12, and '-13 are existing stationary CI RICE located at an area source of HAP emissions; therefore, the full compliance date for this subpart is May 3, 2013.

Permit unit '-6 is an existing stationary SI RICE located at an area source of HAP emissions; therefore, the full compliance date for this subpart is October 19, 2013.

Compliance is assured with the following condition:

N-2321-6	*Condition 6*
N-2321-11, '-12 and '-13	*Condition 4*

§ 63.6603 What emission limitations and operating limitations must I meet if I own or operate an existing stationary RICE located at an area source of HAP emissions?

(a) If you own or operate an existing stationary RICE located at an area source of HAP emissions, you must comply with the requirements in Table 2d to this subpart and the operating limitations in Table 1b and Table 2b to this subpart that apply to you. Note, there are no Table 1b or Table 2b operating limitations for emergency engines.

Table 2d to Subpart ZZZZ of Part 63 - Requirements for Existing Stationary RICE Located at Area Sources of HAP Emissions.

As stated in §§63.6603 and 63.6640, the following table applies to existing stationary RICE located at area sources of HAP emissions:

For each . . .	You must meet the following requirements, except during periods of startup . . .	During periods of startup you must . . .
4. Emergency stationary CI RICE and black start stationary CI RICE.*	a. Change oil and filter every 500 hours of operation or annually, whichever comes first;	N/A
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; and	N/A
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	N/A
5. Emergency stationary SI RICE and black start stationary SI RICE.*	a. Change oil and filter every 500 hours of operation or annually, whichever comes first;	N/A
	b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first; and	N/A
	c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.	N/A

*If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the management practice requirements on the schedule required in Table 2d of this subpart, or if performing the management practice on the required schedule would otherwise pose an unacceptable risk under Federal, State, or local law, the management practice can be delayed until the emergency is over or the unacceptable risk under Federal, State, or local law has abated. The management practice should be performed as soon as practicable after the emergency has ended or the unacceptable risk under Federal, State, or local law has abated. Sources must report any failure to perform the management practice on the schedule required and the Federal, State or local law under which the risk was deemed unacceptable.

Compliance is assured with the following conditions:

N-2321-6	*Conditions 8, 9 and 10*
N-2321-11, '-12 and '-13	*Conditions 5, 6 and 7*

§ 63.6625 What are my monitoring, installation, collection, operation, and maintenance requirements?

(e) If you own or operate any of the following stationary RICE, you must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:

(1) An existing stationary RICE with a site rating of less than 100 HP located at a major source of HAP emissions;
(2) An existing emergency or black start stationary RICE with a site rating of less than or equal to 500 HP located at a major source of HAP emissions;
(3) An existing emergency or black start stationary RICE located at an area source of HAP emissions;

(h) If you operate a new, reconstructed, or existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply.

(i) If you own or operate a stationary CI engine that is subject to the work, operation or management practices in items 1 or 2 of Table 2c to this subpart or in items 1 or 4 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.

Compliance is assured with the following conditions:

N-2321-6	*Conditions 2, 7 and 11*
N-2321-11, '-12 and '-13	*Conditions 2, 6 and 9*

§ 63.6640 How do I demonstrate continuous compliance with the emission limitations and operating limitations?

(a) You must demonstrate continuous compliance with each emission limitation and operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you according to methods specified in Table 6 to this subpart.

(b) You must report each instance in which you did not meet each emission limitation or operating limitation in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you. These instances are deviations from the emission and operating limitations in this subpart. These deviations must be reported according to the requirements in §63.6650. If you change your catalyst, you must reestablish the values of the operating parameters measured during the initial performance test. When you reestablish the values of your operating parameters, you must also conduct a performance test to demonstrate that you are meeting the required emission limitation applicable to your stationary RICE.

(f) *Requirements for emergency stationary RICE.*

(1) If you own or operate an existing emergency stationary RICE located at an area source of HAP emissions, you must operate the emergency stationary RICE according to the requirements in paragraphs (f)(1)(i) through (iii) of this section. Any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1)(i) through (iii) of this section, is prohibited. If you do not operate the engine according to the requirements in paragraphs (f)(1)(i) through (iii) of this section, the engine will not be considered an emergency engine under this subpart and will need to meet all requirements for non-emergency engines.

(i) There is no time limit on the use of emergency stationary RICE in emergency situations.

(ii) You may operate your emergency stationary RICE for the purpose of maintenance checks and readiness testing, provided that the tests are recommended by Federal, State or local government, the manufacturer, the vendor, or the insurance company associated with the engine. Maintenance checks and readiness testing of such units is limited to 100 hours per year. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that Federal, State, or local standards require maintenance and testing of emergency RICE beyond 100 hours per year.

(iii) You may operate your emergency stationary RICE up to 50 hours per year in non-emergency situations, but those 50 hours are counted towards the 100 hours per year provided for maintenance and testing. The 50 hours per year for non-emergency situations cannot be used for peak shaving or to generate income for a facility to supply power to an electric grid or otherwise supply power as part of a financial arrangement with another entity; except that owners and operators may operate the emergency engine for a maximum of 15 hours per year as part of a demand response program if the regional transmission organization or equivalent balancing authority and transmission operator has determined there are emergency conditions that could lead to a potential electrical blackout, such as unusually low frequency, equipment overload, capacity or energy deficiency, or unacceptable voltage level. The engine may not be operated for more than 30 minutes prior to the time when the emergency condition is expected to occur, and the engine operation must be terminated immediately after the facility is notified that the emergency condition is no longer imminent. The 15 hours per year of demand response operation are counted as part of the 50 hours of operation per year provided for non-emergency situations. The supply of emergency power to another entity or entities pursuant to financial arrangement is not limited by this paragraph (f)(1)(iii), as long as the power provided by the financial arrangement is limited to emergency power.

Compliance is assured with the following condition:

N-2321-6	*Condition 15*
N-2321-11, '-12 and '-13	*Condition 11*

Table 6 to Subpart ZZZZ of Part 63 - Continuous Compliance With Emission Limitations, Operating Limitations, Work Practices, and Management Practices

As stated in §63.6640, you must continuously comply with the emissions and operating limitations and work or management practices as required by the following:

For each . . .	Complying with the requirement to . . .	You must demonstrate continuous compliance by . . .
9. Existing emergency and black start stationary RICE located at an area source of HAP	a. Work or Management practices	i. Operating and maintaining the stationary RICE according to the manufacturer's emission-related operation and maintenance instructions; or ii. Develop and follow your own maintenance plan which must provide to

		the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.

Compliance is assured with the following condition:

N-2321-6, '-11, '-12 and '-13	*Condition 2*

§ 63.6645 What notifications must I submit and when?

There are no notifications necessary for existing emergency engines.

§ 63.6650 What reports must I submit and when?

There are no report submittals necessary for existing emergency engines.

§ 63.6655 What records must I keep?

(a) If you must comply with the emission and operating limitations, you must keep the records as follows:

(4) Records of all required maintenance performed on the air pollution control and monitoring equipment.
(5) Records of actions taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation.

(d) You must keep the records required in Table 6 of this subpart to show continuous compliance with each emission or operating limitation that applies to you.

(e) You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following stationary RICE:

(2) An existing stationary emergency RICE.

(3) An existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.

(f) If you own or operate any of the stationary RICE in paragraph (f)(2) below, you must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engines are used for demand response operation, the owner or operator must keep records of the notification of the emergency situation, and the time the engine was operated as part of demand response.

(2) An existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines.

Compliance is assured with the following conditions:

N-2321-6	*Conditions 19 and 20*
N-2321-11, '-12 and '-13	*Conditions 14 and 15*

§ 63.6660 In what form and how long must I keep my records?

(a) Your records must be in a form suitable and readily available for expeditious review according to §63.10(b)(1).
(b) As specified in §63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.
(c) You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to §63.10(b)(1).

Compliance is assured with the following condition:

N-2321-6	*Condition 22*
N-2321-11, '-12 and '-13	*Condition 17*

Full Time Spark Ignited Engines:

Using EPA's navigation page for National Emission Standards for Hazardous Air Pollutants for Reciprocating Internal Combustion Engines, http://www.epa.gov/ttn/atw/rice/ricepg.html#IMP, and the step by step navigation tool, it has been determined that compliance with the requirements of 40 CFR 63, Subpart ZZZZ are satisfied with the engines being subject to the requirements of 40 CFR part 60, subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines). As discussed above, the full time spark ignited engines operated at this facility are subject to the requirements of 40 CFR 60, subpart JJJJ. Therefore, the requirements of 40 CFR 63, Subpart ZZZZ are satisfied.

L. 40 CFR Part 64 - CAM

§64.2 – Applicability

This section requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

1) the unit must have an emission limit for the pollutant;
2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
VOC	20,000
NO_X	20,000
CO	200,000
PM_{10}	140,000
SO_X	140,000

a. N-2321-2 and '-7 – 5,049 Gallon Ethyl Alcohol Storage Tanks

These ethyl alcohol tanks contain emission limits for VOC emissions. However, these tanks are not equipped with any add-on or external control devices. Since these tank permits are not equipped with add-on control devices, they are not subject to the CAM requirements of 40 CFR Subpart 64.

b. N-2321-6 – Emergency IC Engine, With Controls

The permit for this emergency engine contains emission limits for NO_X, CO, VOC, PM_{10} and SO_X. However, this engine is not equipped with any add on control devices for PM_{10} or SO_X emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable to these pollutants and no further discussion is required.

This engine is served by a catalytic converter. Pursuant to current District policy and practice, the catalytic converter will achieve 95% NO_X emission control, 90% CO emission control and 70% VOC emissions control. Therefore, the uncontrolled NO_X, CO and VOC emission rates from this operation can be determined using the horsepower rating of the engine, the emission factors listed on the current permits and a worst case operating scenario of 100 hours per year for non-emergency operation.

NO_X Emissions:

Controlled Annual Emissions = 128 bhp x 0.11 gr-bhp/hr x 100 hr/year / 453.6 gr/lb

Controlled Annual Emissions = 3 lb/year

NSCR Control Efficiency = 95%

Uncontrolled Annual PE = 3 lb/year / (1 – 0.95)

Annual Uncontrolled PE = 60 lb/year

CO Emissions:

Controlled Annual Emissions = 128 bhp x 1.59 gr-bhp/hr x 100 hr/year / 453.6 gr/lb

Controlled Annual Emissions = 45 lb/year

NSCR Control Efficiency = 90%

Uncontrolled Annual PE = 45 lb/year / (1 – 0.90)

Annual Uncontrolled PE = 450 lb/year

VOC Emissions:

Controlled Annual Emissions = 128 bhp x 0.39 gr-bhp/hr x 100 hr/year / 453.6 gr/lb

Controlled Annual Emissions = 11 lb/year

NSCR Control Efficiency = 70%

Uncontrolled Annual PE = 11 lb/year / (1 – 0.70)

Annual Uncontrolled PE = 37 lb/year

As shown above, the uncontrolled PE's for NO_X, CO and VOC emissions are less than the major source thresholds for each pollutant. Therefore, these engines are not subject to the requirements of 40 CFR 64 for this pollutant and no further discussion is required.

c. N-2321-8 – Metal Parts and Wood Products Coating Operation

This metal parts and wood products coating operation has a permitted VOC emission limit. However, the coating operation is not equipped with any add-on control devices for VOC emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for VOC emissions and no further evaluation is required.

d. N-2321-9 – Abrasive Blasting Operation

This abrasive blasting permit does not contain emission limitations for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable.

e. N-2321-10– Outdoor Wood Products Coating Operation

This wood products coating operation permit contains a VOC emission limit. However, all products are coated outdoors, without the use of any add-on control devices. Since this coating operation is not equipped with any add-on control devices, the CAM requirements of 40 CFR 64 are not applicable.

f. N-2321-11, '-12 and '-13 – Emergency IC Engines, No Controls

These engines are only used during emergency situations (e.g. power outages, fires, etc.). The engines are not equipped with any add on control devices. Therefore, the CAM requirements of 40 CFR 64 are not applicable.

g. N-2321-97 through '-648 and '-652 through '-792 – Wine Fermentation and/or Storage Tanks

These wine fermentation and/or storage tanks contain emission limits for VOC emissions. However, these tanks are only equipped with insulation and/or are installed inside of climate controlled buildings and are equipped with pressure vacuum relief valves. This equipment is standard in the wine industries and is not classified as add-on or external control equipment. Since these tank permits are not equipped with add-on control devices, they are not subject to the CAM requirements of 40 CFR Subpart 64.

h. N-2321-649 and '-650 – 122 HP Digester or Natural Gas Fired Full Time IC Engines

Each of the permits for these engines contain emission limits for NO_X, CO, VOC, PM_{10} and SO_X. However, these engines are not equipped with any add on control devices for PM_{10} or SO_X emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable to these pollutants and no further discussion is required.

These engines are each served by non-selective catalytic reduction (NSCR) system. Pursuant to current District policy and practice, the NSCR system will achieve 95% NO_X emission control, 90% CO emission control and 70% VOC emissions control. Therefore, the uncontrolled NO_X, CO and VOC emission rates from these operations can be determined using the horsepower rating of the engines, the emission factors listed on the current permits and a worst case operating scenario of 365 days per year.

NO_X Emissions:

Controlled Annual Emissions = 122 bhp x 0.15 gr-bhp/hr x 8,760 hr/year / 453.6 gr/lb

Controlled Annual Emissions = 353 lb/year

NSCR Control Efficiency = 95%

Uncontrolled Annual PE = 353 lb/year / (1 – 0.95)

Annual Uncontrolled PE = 7,060 lb/year

CO Emissions:

Controlled Annual Emissions = 122 bhp x 0.60 gr-bhp/hr x 8,760 hr/year / 453.6 gr/lb

Controlled Annual Emissions = 1,413 lb/year

NSCR Control Efficiency = 90%

Uncontrolled Annual PE = 1,413 lb/year / (1 – 0.90)

Annual Uncontrolled PE = 14,130 lb/year

VOC Emissions:

Controlled Annual Emissions = 122 bhp x 0.25 gr-bhp/hr x 8,760 hr/year / 453.6 gr/lb

Controlled Annual Emissions = 589 lb/year

NSCR Control Efficiency = 70%

Uncontrolled Annual PE = 589 lb/year / (1 – 0.70)

Annual Uncontrolled PE = 1,963 lb/year

As shown above, the uncontrolled PE's for NO_X, CO and VOC emissions are less than the major source thresholds for each pollutant. Therefore, these engines are not subject to the requirements of 40 CFR 64 for this pollutant and no further discussion is required.

i. N-2321-651 – 11.25 MMBtu/hr Digester Gas Fired Flare

This facility has an anaerobic digester that treats the facility's process wastewater. The anaerobic digester generates digester gas that is primarily made up of Methane (CH4) - 75.3% by volume; and Carbon Dioxide (CO2) - 22.8% by volume. Typically, all of the digester gas generated by the anaerobic digester is used as fuel in one of the two IC engines operating under permits N-2321-649 and '-650. However, in extremely rare cases when the facility generates too much digester gas for these two engines to handle or if the engines are down for maintenance or repair, the digester gas will be burned in this 11.25 MMBtu/hr flare.

This digester gas fired flare has the potential to generate NO_X, CO, VOC, PM_{10} and SO_X emissions. However, the flare is only used to destroy excess digester gas, which is highly flammable and can create explosive mixtures if released directly in to the atmosphere. The flare is not an add-on control device being used to control NO_X, CO, VOC, PM_{10} or SO_X emissions from the anaerobic digester. Therefore, the CAM requirements of 40 CFR Subpart 64 are not applicable and no further discussion is required.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

By using the model general permit template(s) listed in Section IV of this evaluation, the applicant has requested that a permit shield be issued for requirements addressed in the template(s). The basis for each permit shield is discussed in the Permit Shield section of each template.

Requirements not Addressed by Model General Permit Templates

The applicant is not proposing any new permit shields.

X. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit

XI. ATTACHMENTS

A. Draft Renewed Title V Operating Permit
B. Previous Title V Operating Permit
C. Detailed Facility List
D. SIP Stringency Analysis for Rule 4702

ATTACHMENT A

Draft Renewed Title V Operating Permit

FACILITY: N-2321-0-2 **EXPIRATION DATE:** 08/31/2011

DRAFT

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

42. The winery operator shall achieve required annual emissions reductions (RAER) equal to at least 35% of the winery's baseline fermentation emissions (BFE). [District Rule 4694]

43. By December 1, 2006, and every three years thereafter, the winery operator subject to the requirements of Section 5.1 shall submit to the District a three-year compliance plan that demonstrates compliance with the applicable requirements of District Rule 4694 for each year of the applicable compliance period. The three-year compliance plan shall include all the information specified in sections 6.1.1 through 6.1.8 of the rule. [District Rule 4694, 6.1]

44. By July 1, 2007, and every three years thereafter, the winery operator shall submit to the District a three-year compliance plan verification that demonstrates that the three-year compliance plan elements are in effect. The compliance plan verification shall include all the information specified in sections 6.2.1 through 6.2.5 of District Rule 4694. [District Rule 4694, 6.2]

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

45. By February 1, 2008, and every year thereafter, the winery operator shall submit to the District an annual compliance plan demonstration that shows compliance with the applicable requirements of District Rule 4694. The compliance plan demonstration shall include all the information specified in sections 6.3.1 through 6.3.7 of the rule. All additional Required Annual Emissions Reductions (RAER) shall be obtained by April 1 of the year of the Annual Compliance Demonstration, per section 6.3.7.2 of the rule. [District Rule 4694, 6.3]

46. Operators using certified emission reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved three-year compliance plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

47. Payment of District Obtained Emissions Reductions (DOER) and administrative fees shall be made to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694, 6.1.5.3.5]

48. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin April 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-2-7 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,049 GALLON ETHYL ALCOHOL STORAGE TANK (TANK 301)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The maximum amount of material throughput shall not exceed 5,049 gallons in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Emissions from the ethanol storage tank shall not exceed 0.30 lb-VOC/1000 gallons of throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Records of the rolling 12 month total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201] Federally Enforceable Through Title V Permit
5. Records shall be maintained on the premises indicating the daily amount of material loaded into the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All records required by this permit shall be maintained on-site for a period of at least five years, and shall be made available for inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-6-7 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
128 BHP GENERAL MOTORS, MODEL SG 085, EMERGENCY STANDBY PROPANE-FIRED IC ENGINE SERVED BY A HOUSTON INDUSTRIAL SILENCER CATALYTIC CONVERTER, MODEL DN/S-1604C, POWERING AN 80 KW GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This engine shall be fired only on propane (LPG) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-selective catalyst installed on the exhaust stack. [District Rule 2201] Federally Enforceable Through Title V Permit
6. On and after October 19, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. On and after October 19, 2013, the permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. On and after October 19, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. On and after October 19, 2013, the engine's spark plugs shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

10. On and after October 19, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

11. On and after October 19, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

12. This engine shall be equipped with an operational non-resettable elapsed operating time meter or other APCO approved alternative. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit

13. Emissions from this engine shall not exceed any of the following limits: 0.11 g NOx/bhp-hr, 1.59 g CO/bhp-hr, 0.39 g VOC/bhp-hr, 0.175 g PM10/bhp-hr, or 0.012 g SOx/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

15. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

16. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

17. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

18. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

19. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

20. On and after October 19, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

21. Records of the rolling 12 month total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-7-6 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,049 GALLON ETHYL ALCOHOL STORAGE TANK (TANK 302)

DRAFT

PERMIT UNIT REQUIREMENTS

1. The maximum amount of material throughput shall not exceed 5,049 gallons in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Emissions from the ethanol storage tank shall not exceed 0.30 lb-VOC/1000 gallons of throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Records of the rolling 12 month total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records shall be maintained on the premises indicating the daily amount of material loaded into the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All records required by this permit shall be maintained on-site for a period of at least five years, and shall be made available for inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-8-6 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
METAL PARTS AND PRODUCTS AND WOOD PRODUCTS COATING OPERATIONS SERVED BY A SPRAY BOOTH WITH EXHAUST FILTERS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All painting shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2080] Federally Enforceable Through Title V Permit
3. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
4. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
5. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
6. VOC content of coatings as applied, excluding water and exempt compounds, used for wood products, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), or sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC content of coatings as applied, excluding water and exempt compounds, used for wood products, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), or stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. VOC content of strippable booth coating, as applied, excluding water and exempt compounds, used for wood products, shall not exceed 450 g/l (3.8 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit

9. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

10. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

11. An operator of a metal parts products coating operation shall minimize VOC emissions by complying with the following work practice standards: store all VOC-containing coatings, thinners, cleaning materials, and waste materials in closed non-absorbent and non-leaking containers, keeping the containers closed except when specifically in use; close mixing vessels that contain VOC coatings and other materials, except when specifically in use; minimize spill of any VOC-containing materials and clean up spills immediately; and convey VOC-containing materials in closed containers or pipes. [District Rule 4603] Federally Enforceable Through Title V Permit

12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

13. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

14. VOC emissions shall not exceed 50 lb in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The total VOC emissions from this permit unit shall not exceed 14,290 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

16. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

17. Records of the rolling 12 month total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained (lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201] Federally Enforceable Through Title V Permit

18. Records of the cumulative annual quantity of VOC emissions from this permit unit shall be maintained and updated daily. [District Rules 2201] Federally Enforceable Through Title V Permit

19. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

20. Permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information, as applicable: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content and quantity of each solvent used. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

22. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4606] Federally Enforceable Through Title V Permit

23. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-9-2

EXPIRATION DATE: 08/31/2011

EQUIPMENT DESCRIPTION:
UNCONFINED ABRASIVE BLASTING OPERATION

DRAFT

PERMIT UNIT REQUIREMENTS

1. {1481} Abrasive blasting operations which do not use steel or iron shot/grit exclusively shall use wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
2. {1482} Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
3. {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
4. {1484} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
5. Permittee shall maintain daily operation records, including type and quantity of abrasive used, and total hours of operation. Such records such be retained on-site for a periods of at least 5 years. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-10-6 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
OUTDOOR WOOD PRODUCTS COATING OPERATION

DRAFT

PERMIT UNIT REQUIREMENTS

1. Only non-spray (i.e. hand roller, roll coater, dip coat, paint brush, etc.) coating application methods shall be used. [District Rules 2201 and 4606] Federally Enforceable Through Title V Permit
2. VOC content of coatings as applied, excluding water and exempt compounds, used for wood products, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
3. VOC content of coatings as applied, excluding water and exempt compounds, used for wood products, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), or stripper 350 g/l (2.9 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
4. VOC content of strippable booth coating, as applied, excluding water and exempt compounds, used for wood products, shall not exceed 450 g/l (3.8 lb/gallon). [District Rule 4606] Federally Enforceable Through Title V Permit
5. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4606] Federally Enforceable Through Title V Permit
6. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4606] Federally Enforceable Through Title V Permit
7. VOC emissions shall not exceed 30.0 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Records of the rolling 12 month total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the cumulative annual quantity of VOC emissions from the entire stationary source shall be maintained and updated daily. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4606] Federally Enforceable Through Title V Permit
12. Permittee shall maintain a current list of coatings and solvents in use which provides all of the data necessary to evaluate compliance, including the following information, as applicable: identity of coatings, catalysts, reducers, and solvents; manufacturer's recommended mix ratio of components; VOC content of coatings, as applied; and VOC content of solvents. [District Rule 4606] Federally Enforceable Through Title V Permit
13. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, coating and mix ratio of components added to each coating, quantity of each coating applied, identity of coating category and type and amount of solvent used for cleanup and surface preparation. [District Rules 4606] Federally Enforceable Through Title V Permit
14. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4606] Federally Enforceable Through Title V Permit
15. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4606] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-11-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
133 HP CUMMINS MODEL V-378-F2 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. On and after May 3, 2013, the permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

10. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702,17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

11. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule and 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

12. An emergency situation is an unscheduled fire caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

13. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

14. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, emergency fire fighting, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

15. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

16. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702,17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-12-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
115 HP CLARKE GM MODEL MD-6T-1334 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. On and after May 3, 2013, the permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

10. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702,17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

11. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule and 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

12. An emergency situation is an unscheduled fire caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

13. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

14. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, emergency fire fighting, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

15. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

16. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

17. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702,17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-13-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
97 HP DETROIT DIESEL MODEL 1033-5000 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
6. On and after May 3, 2013, the permittee has the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d of Subpart ZZZZ. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

10. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

11. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

12. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

13. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

14. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit

15. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

16. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

17. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-97-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-98-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-99-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-100-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-101-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-102-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-103-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-104-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-105-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-106-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-107-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-108-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-109-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-110-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-111-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-112-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-113-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-114-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-115-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 129 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-116-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 130 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-117-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-118-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-119-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-120-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE AND INSTALLED IN A CLIMATE CONTROLLED BUILDING

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-121-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-123-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 137 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-124-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 138 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-125-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 139 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-126-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 140 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-127-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 201 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-128-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 202 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-129-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 203 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-130-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
166,340 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 204 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-131-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
166,340 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 205 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-132-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 300 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-133-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-134-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-135-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-136-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-137-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-138-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-139-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-140-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,030 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-141-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,240 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 320 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-142-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,240 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-143-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-144-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-145-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-146-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-147-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-148-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 328 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-149-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 329 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-150-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 330 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-151-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-152-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-153-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-154-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-155-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-156-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-157-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-158-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-159-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-161-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-162-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-164-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-165-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-166-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-167-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-168-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-169-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-170-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-171-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 507 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-172-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 508 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-173-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-174-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-175-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-176-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-177-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-178-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-179-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-180-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-181-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 517 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-182-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 518 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-183-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-184-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-185-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-186-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-187-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-188-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-189-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-190-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-191-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-192-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-193-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-194-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-195-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-196-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-197-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 549 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-198-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 550 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-199-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 551 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-200-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 552 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-201-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 553 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-202-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 554 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-203-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 555 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-204-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 556 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-205-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 557 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-206-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 558 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-207-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 559 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-208-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 560 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-209-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 561 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-210-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 562 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-211-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 563 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-212-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 564 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-213-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 565 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-214-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 566 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-215-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 567 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-216-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 568 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-217-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 569 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-218-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 570 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-219-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 571 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-220-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 572 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-221-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 573 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-222-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 574 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-223-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 575 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-224-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 576 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-225-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-226-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-227-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-228-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-229-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-230-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-231-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-232-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-233-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-234-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-235-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 701 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-236-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 702 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-237-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 703 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-238-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 704 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-239-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 705 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-240-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 706 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-241-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 707 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-242-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 708 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-243-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 709 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-244-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-245-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-246-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-247-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-248-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-249-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-250-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-251-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-252-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-253-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-254-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-255-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-256-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-257-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-258-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 732 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-259-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-260-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 734 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-261-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 735 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-262-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 736 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-263-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 737 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-264-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 738 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-265-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 739 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-266-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 740 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-267-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 741 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-268-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 742 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-269-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 751 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-270-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 752 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-271-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 753 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-272-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 754 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-273-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 755 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-274-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 756 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-275-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 757 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-276-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 758 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-277-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 759 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-278-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 760 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-279-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 761 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-280-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 762 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-281-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 763 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-282-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 764 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-283-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-284-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-285-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-286-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-287-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-288-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-289-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-290-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-291-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 WITH PRESSURE/VACUUM VALVE AND INSULATION EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-292-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-293-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-294-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-295-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-296-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-297-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 815 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-298-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 816 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-299-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 817 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-300-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 818 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-301-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 819 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-302-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 820 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-303-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 901 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-304-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 902 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-305-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 903 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-306-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 904 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-307-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 905 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-308-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 906 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-309-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 907 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-310-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 908 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-311-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 909 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-312-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 910 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-313-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 911 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-314-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 912 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-315-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 921 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-316-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 922 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-317-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 923 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-318-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 924 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-319-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 925 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-320-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 926 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-321-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 927 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-322-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 928 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-323-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 929 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-324-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 930 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-325-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-326-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-327-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-328-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-329-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-330-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-331-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-332-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-333-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-334-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-335-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-336-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1112 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-337-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1113 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-338-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1114 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-339-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1115 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-340-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1116 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-341-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1117 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-342-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1118 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-343-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1119 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-344-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1120 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-345-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-346-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-347-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-348-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-349-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-350-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-351-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-352-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-353-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-354-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-355-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-356-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1132 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-357-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1133 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-358-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1134 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-359-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1135 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-360-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1136 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-361-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1137 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-362-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1138 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-363-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1139 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-364-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1140 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-365-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-366-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-367-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-368-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-369-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-370-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-371-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-372-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-373-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-374-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-375-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1153 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-376-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1154 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-377-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1155 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-378-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1156 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-379-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1157 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-380-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1158 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-381-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1159 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-382-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1160 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-383-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1161 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-384-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1162 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-385-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1163 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-386-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1164 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-387-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1165 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-388-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1166 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-389-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1167 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-390-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1168 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-391-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1169 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-392-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1170 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-393-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1171 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-394-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1172 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-395-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1173 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-396-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1174 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-397-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1175 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-398-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1176 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-399-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1177 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-400-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1178 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-401-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1179 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-402-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1180 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-403-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1181 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-404-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1182 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-405-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1183 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-406-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1184 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-407-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1185 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-408-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1186 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-409-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1187 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-410-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1188 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-411-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1189 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-412-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1190 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-413-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1191 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-414-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1192 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-415-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1193 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-416-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1194 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-417-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1195 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-418-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1196 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-419-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1197 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-420-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1198 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-421-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-422-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-423-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-424-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-425-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-426-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-427-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-428-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-429-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1209 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-430-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1210 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-431-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-432-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-433-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-435-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-447-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-448-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-449-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-450-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-451-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-452-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-453-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-454-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-455-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-456-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-457-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-458-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-459-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-460-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-461-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-462-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-463-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-464-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-465-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-466-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-467-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-468-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-469-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-470-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-471-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-472-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-473-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-474-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-475-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-476-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-477-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-478-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-479-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-480-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-481-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-482-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-483-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-484-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-485-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-486-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-487-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-488-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-489-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-490-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-491-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-492-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-493-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-494-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-495-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1275 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-496-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1276 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-497-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1277 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-498-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1278 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-499-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1279 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-500-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1280 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-501-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1281 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-502-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1282 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-503-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1283 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-504-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1284 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-505-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1285 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-506-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1286 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-507-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1301 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-508-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1302 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-509-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1303 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-510-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1304 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-511-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1305 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-512-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1306 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-513-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1307 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-514-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1308 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-515-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1309 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-516-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1310 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-517-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1311 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-518-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-519-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-520-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-521-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-522-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1316 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-523-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-524-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-525-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-526-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-527-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-528-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-529-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-530-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-531-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-532-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-533-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-534-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-535-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-536-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-537-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-538-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-539-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-540-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-541-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-542-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-543-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-544-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-545-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-546-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-547-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-548-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-549-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-550-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-551-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-552-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-553-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-554-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-555-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-556-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-557-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-558-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-559-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-560-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-561-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-562-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-563-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-564-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-565-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-566-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-567-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-568-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-569-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1511 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-570-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1512 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-571-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1513 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-572-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1514 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-573-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1515 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-574-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1516 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-575-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-576-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-577-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-578-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-579-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1521 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-580-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1522 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-581-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1523 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-582-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1524 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-583-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1525 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-584-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1526 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-585-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-586-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-587-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-588-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-589-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1531 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-590-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1532 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-591-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1601 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-592-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1602 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-593-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1603 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-594-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1604 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-595-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1605 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-596-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1606 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-597-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1607 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-598-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1608 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-599-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1609 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-600-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1610 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-601-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1611 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-602-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1612 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-603-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1625 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-604-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1626 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-605-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1627 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-606-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1628 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-607-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1629 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-608-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1630 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-609-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1631 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-610-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1632 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-611-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1633 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-612-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1634 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-613-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1635 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-614-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1636 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-615-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1649 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-616-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1650 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-617-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1651 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-618-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1652 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-619-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1653 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-620-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1654 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-621-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1655 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-622-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1656 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-623-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1657 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-624-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1658 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-625-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1659 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-626-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1660 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-629-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1661 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-630-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1662 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-631-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1663 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-632-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1664 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-633-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1665 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-634-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1666 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-635-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1667 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-636-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1668 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-637-3 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-1 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-638-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-2 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-639-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-3 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-640-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-4 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-641-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-5 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-642-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
18,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK GANI WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-643-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK ROTO WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-644-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,287 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 941 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-645-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 942 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-646-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 943 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-647-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 944 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-648-3 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 945 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-649-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
122 HP ENERGY NOW MODEL ENI65 DIGESTER GAS OR NATURAL GAS-FIRED RICH-BURN IC ENGINE SERVED BY JOHNSON MATTHEY BANDITO CATALYTIC CONVERTER POWERING AN ELECTRICAL GENERATOR WITH DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-650 AND '-651

PERMIT UNIT REQUIREMENTS

1. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. This engine shall only be fired on PUC-quality natural gas and/or digester gas. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Digester gas fuel to the IC engine shall be treated by a dry absorption system for removal of H2S. Maximum H2S concentration in the treated digester gas shall be 25 ppmvd. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
6. The dry absorption system for H2S removal shall utilize a minimum of two absorbent beds to allow leaving at least one absorbent bed operational during periodical change out of absorbent. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 11 ppmvd NOx @ 15% O2 (equivalent to 0.15 g-NOx/hp-hr), 0.0233 g-SOx/hp-hr, 0.158 g-PM10/hp-hr, 70 ppmvd CO @ 15% O2 (equivalent to 0.60 g-CO/hp-hr), or 51 ppmvd VOC @ 15% O2 (equivalent to 0.25 g-VOC/hp-hr). [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
8. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. If either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4702] Federally Enforceable Through Title V Permit

10. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702] Federally Enforceable Through Title V Permit

11. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702] Federally Enforceable Through Title V Permit

12. Testing to demonstrate compliance with the digester gas fuel sulfur content shall be conducted weekly using draeger tubes. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Records of all monitoring and source testing results shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Source testing to measure digester gas-combustion NOx, CO, and VOC emissions shall be conducted at least once every 24 months and shall be performed during the annual grape crush operational period at this facility. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

15. The permittee shall perform an annual digester gas fuel sulfur analysis in accordance with the test methods specified within this permit. [District Rule 4702] Federally Enforceable Through Title V Permit

16. Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rule 4702] Federally Enforceable Through Title V Permit

17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702] Federally Enforceable Through Title V Permit

18. The following test methods shall be used, or any other method approved by the EPA and the APCO: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100; stack gas oxygen - EPA Method 3 or 3A or ARB Method 100; VOC (ppmv) - EPA Method 18, 25A or 25B, or ARB Method 100; SOx - EPA Method 6C, 8 or ARB Method 100; and total sulfur, as hydrogen sulfide (H2S) - EPA Method 11 or 15, as appropriate [District Rules 1081 and 4702] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

21. The permittee shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rule 4702] Federally Enforceable Through Title V Permit

22. The permittee shall update the I&M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I&M plan and must submit an updated I&M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I&M plan shall be recorded in the engine's operating log. For modifications, the revised I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I&M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-650-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
122 HP ENERGY NOW MODEL ENI65 DIGESTER GAS OR NATURAL GAS-FIRED RICH-BURN IC ENGINE SERVED BY JOHNSON MATTHEY BANDITO CATALYTIC CONVERTER POWERING AN ELECTRICAL GENERATOR WITH DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-651

PERMIT UNIT REQUIREMENTS

1. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Digester gas fuel to the IC engine shall be treated by a dry absorption system for removal of H2S. Maximum H2S concentration in the treated digester gas shall be 25 ppmvd. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The dry absorption system for H2S removal shall utilize a minimum of two absorbent beds to allow leaving at least one absorbent bed operational during periodical change out of absorbent. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 11 ppmvd NOx @ 15% O2 (equivalent to 0.15 g-NOx/hp-hr), 0.0233 g-SOx/hp-hr, 0.158 g-PM10/hp-hr, 70 ppmvd CO @ 15% O2 (equivalent to 0.60 g-CO/hp-hr), or 51 ppmvd VOC @ 15% O2 (equivalent to 0.25 g-VOC/hp-hr). [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
7. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702] Federally Enforceable Through Title V Permit
8. If either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702] Federally Enforceable Through Title V Permit

10. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702] Federally Enforceable Through Title V Permit

11. Testing to demonstrate compliance with the digester gas fuel sulfur content shall be conducted weekly using draeger tubes. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Records of all monitoring and source testing results shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Source testing to measure digester gas-combustion NOx, CO, and VOC emissions shall be conducted at least once every 24 months and shall be performed during the annual grape crush operational period at this facility. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

14. Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rule 4702] Federally Enforceable Through Title V Permit

15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702] Federally Enforceable Through Title V Permit

16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, and VOC (ppmv) - EPA Method 18, 25A or 25B, or ARB Method 100. [District Rules 1081 and 4702] Federally Enforceable Through Title V Permit

17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

19. The permittee shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rule 4702] Federally Enforceable Through Title V Permit

20. The permittee shall update the I&M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I&M plan and must submit an updated I&M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I&M plan shall be recorded in the engine's operating log. For modifications, the revised I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I&M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-651-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11.25 MMBTU/HR SHAW LFG SPECIALTIES MODEL EF52514 DIGESTER GAS-FIRED ENCLOSED GROUND FLARE WITH FLOW-SENSING AUTOMATIC PILOT AND DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-650

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All flaring shall be conducted in accordance with the facility's approved flare minimization plan (FMP). [District Rule 4311] Federally Enforceable Through Title V Permit
3. A flame shall be present at all times in the flare whenever combustible gases are vented through the flare. [District Rule 4311] Federally Enforceable Through Title V Permit
4. The flare outlet shall be equipped with an automatic ignition system, or, shall be operated with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
5. Digester gas fuel to the flare shall be treated by a dry absorption system for removal of H2S. Maximum H2S concentration in the treated digester gas shall be 25 ppmvd. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The dry absorption system for H2S removal shall utilize a minimum of two absorbent beds to allow leaving at least one absorbent bed operational during periodical change out of absorbent. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The flare pilot shall be fired with natural gas only. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The flare shall be equipped with a flow-sensing automatic ignition system. The flow sensing automatic ignition system shall use natural gas for purging. [District Rule 4311] Federally Enforceable Through Title V Permit
9. The flare shall be equipped and operated with a non-resettable cumulative fuel consumption meter or other APCO approved alternative. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
10. There shall be no visible emissions from the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions from the digester gas-fired unit shall not exceed any of the following limits: 0.06 lb-NOx/MMBtu, 0.0085 lb-SOx/MMBtu, 0.008 lb-PM10/MMBtu, 0.20 lb-CO/MMBtu, or 0.0027 lb-VOC/MMBtu. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
12. Annual digester gas fired in the unit shall not exceed 18.42 MMscf per year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Digester gas fuel consumption in standard cubic feet shall be recorded monthly. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Testing to demonstrate compliance with the digester gas fuel sulfur content shall be conducted weekly using draeger tubes. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

15. Source testing to measure NOx and VOC emissions from this unit while fired on digester gas shall be conducted at least once every twelve (12) months and shall be performed during the annual grape crush operational period at this facility. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

16. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified and a source test plan must be submitted for approval at least 30 days prior to testing. [District Rules 1081 and 4311] Federally Enforceable Through Title V Permit

17. The following test methods shall be used: VOC - EPA Method 25, except when the outlet concentration must be below 50 ppm to meet the standard, in which case EPA Method 25a may be used; analysis of halogenated exempt compounds - EPA Method 18 or ARB Method 422 "Determination of Volatile organic Compounds in Emission from Stationary Sources"; NOx (lb/MMBtu) - EPA Method 19; and NOx and O2 (concentrations) - EPA Method 3A, EPA Method 7E, or ARB 100. The VOC concentration in ppmv shall be converted to pounds per million Btu (lb/MMBtu) as specified in District Rule 4311. [District Rule 4311] Federally Enforceable Through Title V Permit

18. The results of each source test shall be submitted to the District within 45 days thereafter. [District Rules 1081 and 4311] Federally Enforceable Through Title V Permit

19. The operator shall notify the APCO of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, which ever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time. [District Rule 4311] Federally Enforceable Through Title V Permit

20. The operator shall submit an annual report to the APCO that summarizes the following: all Reportable Flaring Events, as defined in Rule 4311; the total volumetric flow of vent gas in standard cubic feet for each day; and any flare monitoring system downtime periods, including dates and times. The report shall be submitted within 30 days following the end of each twelve month period of the previous year. [District Rule 4311] Federally Enforceable Through Title V Permit

21. The permittee shall maintain the following records: the amount of vent gas burned in the flare, in scf; copies of annual source testing results; a copy of the approved flare minimization plan; and copies of annual reportable flaring events reports. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4311] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-652-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-653-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-654-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-655-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-656-1 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-657-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-658-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-659-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-660-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-661-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-662-1 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-663-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-664-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-665-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
790 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-666-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-667-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-668-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-669-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 648 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-670-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 649 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-671-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-672-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1673 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-673-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1674 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-677-1 **EXPIRATION DATE:** 08/31/2011

DRAFT

EQUIPMENT DESCRIPTION:
6,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-678-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1576 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-679-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1578 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-680-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1580 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-681-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1582 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-682-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1584 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-683-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1586 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-684-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1588 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-685-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-1 WITH PRESSURE/VACUUM VALVE AND REFRIGERATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-686-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-687-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-688-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1556 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-689-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-690-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-691-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1562 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-692-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1577 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-693-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1579 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-694-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1581 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-695-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1583 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-696-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-697-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-698-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-699-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-4 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-700-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-5 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-701-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-6 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-702-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1564 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-703-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1566 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-704-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1585 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-705-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1587 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-706-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-7 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-707-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-8 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-708-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-9 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-709-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-10 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-710-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1533 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-711-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1534 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-712-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1535 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-713-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1536 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-714-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-715-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-716-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-717-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-718-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1541 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-719-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1542 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-720-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1543 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-721-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1544 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-722-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1545 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-723-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1546 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-724-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-725-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-726-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-727-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-728-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1551 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-729-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1552 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-730-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1553 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-731-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1554 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-732-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1555 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-733-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-734-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-735-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1561 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-736-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1563 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-737-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1565 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-738-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1567 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-739-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1569 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-740-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1571 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-741-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1573 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-742-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1575 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-743-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-744-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-745-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-746-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-4 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-747-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-5 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-748-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-6 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-749-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-7 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-750-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-8 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-751-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-9 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-752-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 650 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-753-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-754-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-755-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-756-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-757-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-758-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-759-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-760-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 658 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-761-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 659 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-762-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 660 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-763-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-764-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-765-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-766-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-767-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-768-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-769-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 667 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-770-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 668 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-771-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 669 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-772-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 670 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-773-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-774-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-775-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-776-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-777-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-778-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-779-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 677 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-780-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 678 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-781-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 679 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-782-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 680 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-783-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-784-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-785-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-786-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-787-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-788-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-789-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 687 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-790-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 688 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-791-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 689 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: N-2321-792-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-25K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
6. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
7. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
8. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

11. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb/year, calculated on a twelve (12) month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. {4659} The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and the ethanol concentration of each wine movement; and the calculated 12 month rolling VOC emission rate (lb-VOC per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

16. {4660} If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

17. {4661} Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

ATTACHMENT B

Previous Title V Operating Permit

Permit to Operate

FACILITY: N-2321 **EXPIRATION DATE:** 08/31/2011

LEGAL OWNER OR OPERATOR: CBUS OPS INC (DBA WOODBRIDGE WINERY)
MAILING ADDRESS: P O BOX 1260
WOODBRIDGE, CA 95258-1260

FACILITY LOCATION: 5950 E WOODBRIDGE ROAD
ACAMPO, CA 95220

FACILITY DESCRIPTION: WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

David Warner
Director of Permit Services

Dec 7 2012 10:33AM -- BROWND

San Joaquin Valley
Air Pollution Control District

FACILITY: N-2321-0-1 **EXPIRATION DATE:** 08/31/2011

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (3/21/02). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.12.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (11/15/01). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (10/31/01) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. All VOC-containing materials for architectural coatings subject to Rule 4601 (10/31/01) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (10/31/01). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR 82, Subpart B. [40 CFR 82, Subpart B] Federally Enforceable Through Title V Permit

29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit

30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit

31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit

32. Whenever open areas are disturbed or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit

33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit

34. Any unpaved vehicle/equipment area that anticipates more than 75 vehicle trips per day shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 100 vehicle trips per day shall comply with the requirements of Section 5.1.2 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (11/15/01) or Rule 8011 (11/15/01). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit

35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), and Rule 111 (Kern, Tulare, Kings). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (11/15/01); 4601, sections 5.1, 5.2, 5.3, 5.8 and 8.0 (10/31/01); 8021 (11/15/01); 8031 (11/15/01); 8041 (11/15/01); 8051 (11/15/01); 8061 (11/15/01); and 8071 (11/15/01). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. On March 31, 2007, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

43. The winery operator shall achieve required annual emissions reductions (RAER) equal to at least 35% of the winery's baseline fermentation emissions (BFE) [District Rule 4694]

44. By December 1, 2006, and every three years thereafter, the winery operator subject to the requirements of Section 5.1 shall submit to the District a three-year compliance plan that demonstrates compliance with the applicable requirements of District Rule 4694 for each year of the applicable compliance period. The three-year compliance plan shall include all the information specified in sections 6.1.1 through 6.1.8 of the rule. [District Rule 4694, 6.1]

45. By July 1, 2007, and every three years thereafter, the winery operator shall submit to the District a three-year compliance plan verification that demonstrates that the three-year compliance plan elements are in effect. The compliance plan verification shall include all the information specified in sections 6.2.1 through 6.2.5 of District Rule 4694. [District Rule 4694, 6.2]

46. By March 1, 2008, and every year thereafter on or before March 1, the winery operator shall submit to the District an annual compliance plan demonstration that shows compliance with the applicable requirements of District Rule 4694. The compliance plan demonstration shall include all the information specified in sections 6.3.1 through 6.3.7 of the rule. All additional Required Annual Emissions Reductions (RAER) shall be obtained by April 1 of the year of the Annual Compliance Demonstration, per section 6.3.7.2 of the rule. [District Rule 4694, 6.3]

47. Operators using certified emission reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved three-year compliance plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

48. Payment of District Obtained Emissions Reductions (DOER) and administrative fees shall be made to the District no later than March 1, of the first year in the applicable compliance period. [District Rule 4694, 6.1.5.3.5]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-2-5 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,049 GALLON ETHYL ALCOHOL STORAGE TANK (TANK 301)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The maximum amount of material throughput shall not exceed 5,049 gallons in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Emissions from the ethanol storage tank shall not exceed 0.30 lb-VOC/1000 gallons of throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Records shall be maintained on the premises indicating the daily amount of material loaded into the tank. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. All records required by this permit shall be maintained on-site for a period of at least five years, and shall be made available for inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-6-5 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
128 BHP GENERAL MOTORS, MODEL SG 085, EMERGENCY PROPANE-FIRED IC ENGINE SERVED BY A HOUSTON INDUSTRIAL SILENCER CATALYTIC CONVERTER, MODEL DN/S-1604C, POWERING AN 80 KW GENERATOR

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with either a positive crankcase ventilation (PCV) system that recirculates crankcase emissions into the air intake system for combustion, or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
5. This engine shall be fired only on propane (LPG) gas. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This engine shall be equipped with an operational non-selective catalyst installed on the exhaust stack. [District Rule 2201] Federally Enforceable Through Title V Permit
7. This engine shall be equipped with an operational non-resettable elapsed operating time meter or other APCO approved alternative. [District Rules 2201, 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Emissions from this engine shall not exceed any of the following limits: 0.11 g NOx/bhp-hr, 1.59 g CO/bhp-hr, 0.39 g VOC/bhp-hr, 0.175 g PM10/bhp-hr, or 0.012 g SOx/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Records of the total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702] Federally Enforceable Through Title V Permit
12. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
14. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
15. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-7-4 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,049 GALLON ETHYL ALCOHOL STORAGE TANK (TANK 302)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The maximum amount of material throughput shall not exceed 5,049 gallons in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Emissions from the ethanol storage tank shall not exceed 0.30 lb-VOC/1000 gallons of throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Records shall be maintained on the premises indicating the daily amount of material loaded into the tank. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. All records required by this permit shall be maintained on-site for a period of at least five years, and shall be made available for inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-8-4 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
METAL PARTS AND PRODUCTS AND WOOD PRODUCTS COATING OPERATIONS SERVED BY A SPRAY BOOTH WITH EXHAUST FILTERS

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. All painting shall be conducted in the booth with filters in place, fan(s) operating, and doors closed. [District Rule 2080] Federally Enforceable Through Title V Permit
4. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 øF or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 øF or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603]
5. Until December 31, 2010, VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603]
6. After January 1, 2011, VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603]
7. Until December 31, 2010, VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. After January 1, 2011, VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603]

9. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit

10. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit

11. VOC content of strippable booth coating shall not exceed 450 g/l (3.8 lb/gallon) as applied, excluding water and exempt compounds. [District Rule 4606, 5.6.9] Federally Enforceable Through Title V Permit

12. Only HVLP, electrostatic, brush, dip, flow, or roll coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations. [District Rules 4603, 5.6 and 4606, 5.4] Federally Enforceable Through Title V Permit

13. Permittee shall demonstrate that HVLP guns manufactured prior to 1/1/96 operate between 0.1 and 10 psig air atomizing pressure, by manufacturer's published technical material or by use of a certified air pressure tip gauge. [District Rules 4603, 5.6.3.2 and 4606, 5.4.2.2] Federally Enforceable Through Title V Permit

14. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit

15. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rules 4603 and 4606]

16. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603]

17. VOC content of coatings and solvents shall be analyzed by EPA Method 24 and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603]

18. Emissions of VOC shall be measured by EPA Method 25, 25A or 25B, as applicable, and analysis of halogenated exempt compounds shall be analyzed by ARB Method 422. [District Rule 4603]

19. The viscosity of coatings used for dip coating of steel joists shall be determined by using ASTM D5478-98 or ASTM D5125-97 [District Rule 4603]

20. The quantification of coating as a metallic/iridescent topcoat shall be determined by SCAQMD Method 318 (Determination of Weight Percent of Elemental Metal in Coatings by X-ray Diffraction Method), July 1996. [District Rule 4603]

21. Measurement of acid content of pre-treatment wash primers shall be conducted and reported in accordance with ASTM D1613-96, Standard Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish Lacquer and Related products. [District Rule 4603]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. Determination of emissions of VOC from spray gun cleaning systems shall be made using SCAQMD 'General Method for Determining Solvent Losses from Spray Gun Cleaning Systems," dated October 3, 1989. [District Rule 4603]

23. VOC emissions shall not exceed 50 lb in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit

24. The total VOC emissions from this permit unit shall not exceed 14,290 lb/yr. [District Rule 2201] Federally Enforceable Through Title V Permit

25. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year. [District Rule 2201] Federally Enforceable Through Title V Permit

26. Records of the total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

27. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content and quantity of each solvent used. [District Rules 4603, 6.2.3, 4606, 6.1.1.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

28. Permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information, as applicable: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rules 4603, 6.2.2 and 4606, 6.1.1.1] Federally Enforceable Through Title V Permit

29. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4606, 6.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

30. Records of the cumulative annual quantity of VOC emissions from this permit unit shall be maintained and updated daily. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

31. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 4603, 6.2.10, 4606, 6.0 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-9-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
UNCONFINED ABRASIVE BLASTING OPERATION

PERMIT UNIT REQUIREMENTS

1. Abrasive blasting operations which do not use steel or iron shot/grit exclusively shall use wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
2. Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
3. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
4. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
5. Permittee shall maintain daily operation records, including type and quantity of abrasive used, and total hours of operation. Such records such be retained on-site for a periods of at least 5 years. [District Rule 2520, 9.3.2 & 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-10-4 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
OUTDOOR WOOD PRODUCTS COATING OPERATION

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Only non-spray (i.e. hand roller, roll coater, dip coat, paint brush, etc.) coating application methods shall be used. [District Rules 2201 and 4606, 5.4] Federally Enforceable Through Title V Permit
3. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: clear topcoat 275 g/l (2.3 lb/gallon), filler 275 g/l (2.3 lb/gallon), high-solids stains 240 g/l (2.0 lb/gallon), ink 500 g/l (4.2 lb/gallon), mold-seal coating 750 g/l (6.3 lb/gallon), multi-colored coating 275 g/l (2.3 lb/gallon), pigmented coating 275 g/l (2.3 lb/gallon), sanding sealer 275 g/l (2.3 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
4. VOC content of coatings as applied, excluding water and exempt compounds, used for wood product, shall not exceed any of the following limits: low-solids stain 120 g/l (1.0 lb/gallon), stripper 350 g/l (2.9 lb/gallon). [District Rule 4606, 5.1] Federally Enforceable Through Title V Permit
5. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4606, 5.6.10] Federally Enforceable Through Title V Permit
6. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning: 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rules 4603 and 4606] Federally Enforceable Through Title V Permit
7. Permittee shall maintain daily records of the following: quantity and type of coatings used, mix ratios of volume of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent or stripper. [District Rules 4606, 6.1.1.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rules 4606, 6.2 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. VOC emissions shall not exceed 30.0 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Combined VOC emissions from permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall not exceed 15,844 lb-VOC/year. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Records of the total annual VOC emissions for permit units N-2321-2, N-2321-6, N-2321-7, N-2321-8, and N-2321-10 shall be maintained. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Records of the cumulative annual quantity of VOC emissions from the entire stationary source shall be maintained and updated daily. [District Rules 2201 and 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

13. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rules 1070, 4606, 6.0 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

14. Permittee shall maintain a current list of coatings and solvents in use which provides all of the data necessary to evaluate compliance, including the following information, as applicable: identity of coatings, catalysts, reducers, and solvents; manufacturer's recommended mix ratio of components; VOC content of coatings, as applied; and VOC content of solvents. [District Rule 4606, 6.1.1.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-11-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
133 HP CUMMINS MODEL V-378-F2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115 and District Rule 4801] Federally Enforceable Through Title V Permit
2. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the initial start-up hours, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [17 CCR 93115 and District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed operating time meter or other APCO approved alternative. [17 CCR 93115 and District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [17 CCR 93115 and District Rules 4702 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. This engine shall be used exclusively for fire fighting purposes. [District Rule 4702, 4.3.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-12-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
115 HP CLARKE GM MODEL MD-6T-1334 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP

PERMIT UNIT REQUIREMENTS

1. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115 and District Rule 4801] Federally Enforceable Through Title V Permit
2. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule and 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the initial start-up hours, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [17 CCR 93115 and District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed operating time meter or other APCO approved alternative. [17 CCR 93115 and District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [17 CCR 93115 and District Rules 4702 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. This engine shall be used exclusively for fire fighting purposes. [District Rule 4702, 4.3.1] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-13-1 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
97 HP DETROIT DIESEL MODEL 1033-5000 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE

PERMIT UNIT REQUIREMENTS

1. This engine shall be operated using only CARB certified diesel fuel. [17 CCR 93115 and District Rule 4801] Federally Enforceable Through Title V Permit
2. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [17 CCR 93115 and District Rule 4702] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the initial start-up hours, the number of hours of operation, the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.), and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [17 CCR 93115 and District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This engine shall be equipped with an operational non-resettable elapsed operating time meter or other APCO approved alternative. [17 CCR 93115 and District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
7. During periods of maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (e.g. oil pressure, exhaust gas temperature, etc.). [District Rules 4702 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [17 CCR 93115]
9. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [17 CCR 93115 and District Rules 4702 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-97-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-98-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-99-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-100-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-101-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-102-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-103-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-104-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-105-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-106-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-107-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-108-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-109-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-110-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-111-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-112-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-113-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-114-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-115-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 129 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-116-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 130 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-117-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-118-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-119-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-120-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-121-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-123-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 137 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-124-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 138 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-125-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 139 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-126-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 140 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-127-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 201 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-128-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 202 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-129-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 203 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-130-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
166,340 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 204 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-131-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
166,340 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 205 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-132-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 300 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-133-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-134-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-135-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-136-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-137-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-138-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-139-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-140-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,030 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-141-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,240 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 320 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-142-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,240 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-143-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-144-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-145-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-146-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-147-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-148-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 328 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-149-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 329 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-150-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 330 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-151-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-152-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-153-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-154-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-155-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-156-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-157-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-158-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-159-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-161-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-162-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-164-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-165-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-166-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-167-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-168-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-169-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-170-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-171-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 507 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-172-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 508 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-173-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-174-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-175-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-176-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-177-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-178-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-179-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-180-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-181-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 517 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-182-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 518 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-183-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-184-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-185-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-186-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-187-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-188-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-189-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-190-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-191-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-192-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-193-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-194-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-195-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-196-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-197-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 549 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-198-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 550 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-199-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 551 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-200-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 552 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-201-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 553 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-202-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 554 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-203-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 555 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-204-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 556 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-205-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 557 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-206-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 558 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-207-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 559 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-208-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 560 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-209-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 561 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-210-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 562 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-211-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 563 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-212-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 564 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-213-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 565 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-214-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 566 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-215-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 567 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-216-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 568 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-217-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 569 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-218-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 570 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-219-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 571 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-220-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 572 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-221-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 573 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-222-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 574 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-223-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 575 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-224-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 576 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-225-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-226-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-227-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-228-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-229-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-230-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-231-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-232-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-233-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-234-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-235-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 701 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-236-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 702 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-237-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 703 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-238-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 704 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-239-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 705 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-240-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 706 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-241-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 707 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-242-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 708 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-243-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 709 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-244-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-245-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-246-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-247-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-248-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-249-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-250-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-251-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-252-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-253-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-254-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-255-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-256-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-257-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-258-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 732 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-259-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-260-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 734 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-261-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 735 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-262-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 736 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-263-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 737 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-264-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 738 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-265-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 739 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-266-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 740 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-267-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 741 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-268-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 742 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-269-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 751 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-270-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 752 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-271-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 753 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-272-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 754 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-273-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 755 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-274-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 756 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-275-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 757 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-276-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 758 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-277-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 759 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-278-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 760 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-279-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 761 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-280-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 762 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-281-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 763 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-282-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 764 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-283-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-284-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-285-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-286-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-287-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-288-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-289-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-290-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-291-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-292-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-293-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-294-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-295-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-296-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-297-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 815 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-298-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 816 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-299-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 817 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-300-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 818 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-301-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 819 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-302-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 820 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-303-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 901 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-304-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 902 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-305-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 903 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-306-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 904 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-307-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 905 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-308-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 906 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-309-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 907 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-310-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 908 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-311-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 909 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-312-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 910 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-313-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 911 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-314-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 912 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-315-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 921 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-316-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 922 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-317-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 923 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-318-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 924 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-319-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 925 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-320-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 926 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-321-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 927 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-322-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 928 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-323-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 929 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-324-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 930 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-325-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-326-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-327-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-328-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-329-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-330-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-331-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-332-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-333-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-334-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-335-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-336-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1112 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-337-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1113 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-338-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1114 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-339-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1115 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-340-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1116 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-341-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1117 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-342-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1118 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-343-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1119 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-344-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1120 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-345-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-346-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-347-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-348-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-349-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-350-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-351-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-352-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-353-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-354-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-355-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-356-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1132 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-357-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1133 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-358-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1134 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-359-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1135 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-360-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1136 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-361-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1137 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-362-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1138 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-363-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1139 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-364-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1140 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-365-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-366-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-367-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-368-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-369-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-370-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-371-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-372-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-373-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-374-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-375-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1153 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-376-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1154 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-377-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1155 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-378-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1156 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-379-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1157 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-380-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1158 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-381-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1159 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-382-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1160 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-383-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1161 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-384-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1162 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-385-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1163 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-386-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1164 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-387-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1165 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-388-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1166 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-389-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1167 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-390-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1168 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-391-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1169 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-392-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1170 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-393-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1171 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-394-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1172 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-395-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1173 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-396-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1174 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-397-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1175 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-398-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1176 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-399-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1177 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-400-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1178 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-401-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1179 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-402-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1180 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-403-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1181 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-404-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1182 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-405-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1183 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-406-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1184 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-407-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1185 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-408-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1186 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-409-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1187 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

PERMIT UNIT: N-2321-410-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1188 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-411-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1189 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-412-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1190 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-413-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1191 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-414-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1192 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-415-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1193 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-416-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1194 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-417-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1195 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-418-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1196 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-419-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1197 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-420-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1198 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-421-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-422-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-423-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-424-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-425-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-426-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-427-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-428-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-429-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1209 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-430-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1210 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-431-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-432-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-433-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-435-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-447-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-448-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-449-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-450-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-451-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-452-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-453-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-454-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-455-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-456-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-457-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-458-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-459-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-460-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-461-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-462-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-463-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-464-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-465-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-466-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-467-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-468-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-469-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-470-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-471-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-472-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-473-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-474-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-475-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-476-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-477-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-478-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-479-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-480-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-481-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-482-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-483-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-484-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-485-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-486-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-487-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-488-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-489-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-490-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-491-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-492-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-493-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-494-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-495-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1275 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-496-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1276 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-497-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1277 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-498-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1278 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-499-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1279 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-500-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1280 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-501-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1281 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-502-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1282 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-503-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1283 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-504-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1284 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-505-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1285 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-506-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1286 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-507-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1301 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-508-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1302 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-509-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1303 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-510-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1304 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-511-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1305 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-512-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1306 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-513-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1307 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-514-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1308 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-515-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1309 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-516-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1310 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-517-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1311 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-518-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-519-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-520-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-521-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-522-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1316 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-523-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-524-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-525-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-526-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-527-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-528-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-529-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-530-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-531-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-532-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-533-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-534-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-535-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-536-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-537-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-538-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-539-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-540-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-541-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-542-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-543-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-544-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-545-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-546-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-547-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-548-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-549-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-550-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-551-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-552-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-553-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-554-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-555-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-556-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-557-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-558-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-559-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-560-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-561-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-562-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-563-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-564-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-565-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-566-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-567-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-568-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-569-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1511 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-570-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1512 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-571-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1513 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-572-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1514 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-573-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1515 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-574-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1516 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-575-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-576-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-577-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-578-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-579-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1521 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-580-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1522 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-581-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1523 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-582-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1524 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-583-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1525 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-584-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1526 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-585-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-586-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-587-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-588-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-589-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1531 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-590-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1532 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-591-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1601 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-592-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1602 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-593-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1603 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-594-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1604 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-595-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1605 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-596-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1606 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-597-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1607 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-598-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1608 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-599-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1609 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-600-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1610 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-601-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1611 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-602-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1612 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-603-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1625 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-604-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1626 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-605-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1627 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-606-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1628 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-607-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1629 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-608-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1630 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-609-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1631 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-610-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1632 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-611-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1633 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-612-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1634 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-613-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1635 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-614-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1636 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-615-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1649 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-616-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1650 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-617-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1651 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-618-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1652 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-619-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1653 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-620-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1654 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-621-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1655 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-622-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1656 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-623-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1657 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-624-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1658 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-625-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1659 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-626-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1660 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-629-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1661 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-630-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1662 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-631-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1663 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-632-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1664 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-633-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1665 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-634-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1666 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-635-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1667 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-636-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1668 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201]
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1]
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1]
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2]
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201]
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]
11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201]

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201]

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201]

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201]

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201]

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-637-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-638-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-639-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-640-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-4 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-641-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-5 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-642-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
18,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK GANI WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-643-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK ROTO WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-644-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,287 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 941 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-645-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 942 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-646-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 943 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-647-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 944 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-648-2 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 945 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-649-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
122 HP ENERGY NOW MODEL ENI65 DIGESTER GAS OR NATURAL GAS-FIRED RICH-BURN IC ENGINE SERVED BY JOHNSON MATTHEY BANDITO CATALYTIC CONVERTER POWERING AN ELECTRICAL GENERATOR WITH DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-651

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. Digester gas fuel to the IC engine shall be treated by a dry absorption system for removal of H2S. Maximum H2S concentration in the treated digester gas shall be 25 ppmvd. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The dry absorption system for H2S removal shall utilize a minimum of two absorbent beds to allow leaving at least one absorbent bed operational during periodical change out of absorbent. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 11 ppmvd NOx @ 15% O2 (equivalent to 0.15 g-NOx/hp-hr), 0.0233 g-SOx/hp-hr, 0.158 g-PM10/hp-hr, 70 ppmvd CO @ 15% O2 (equivalent to 0.60 g-CO/hp-hr), or 51 ppmvd VOC @ 15% O2 (equivalent to 0.25 g-VOC/hp-hr). [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
9. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4702] Federally Enforceable Through Title V Permit

11. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702] Federally Enforceable Through Title V Permit

12. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702] Federally Enforceable Through Title V Permit

13. Testing to demonstrate compliance with the digester gas fuel sulfur content shall be conducted weekly using draeger tubes. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of all monitoring and source testing results shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Source testing to measure digester gas-combustion NOx, CO, and VOC emissions shall be conducted at least once every 24 months and shall be performed during the annual grape crush operational period at this facility. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

16. Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rule 4702] Federally Enforceable Through Title V Permit

17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702] Federally Enforceable Through Title V Permit

18. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, and VOC (ppmv) - EPA Method 18, 25A or 25B, or ARB Method 100. [District Rules 1081 and 4702] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. The permittee shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall update the I&M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I&M plan and must submit an updated I&M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I&M plan shall be recorded in the engine's operating log. For modifications, the revised I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I&M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-650-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
122 HP ENERGY NOW MODEL ENI65 DIGESTER GAS OR NATURAL GAS-FIRED RICH-BURN IC ENGINE SERVED BY JOHNSON MATTHEY BANDITO CATALYTIC CONVERTER POWERING AN ELECTRICAL GENERATOR WITH DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-651

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. Digester gas fuel to the IC engine shall be treated by a dry absorption system for removal of H2S. Maximum H2S concentration in the treated digester gas shall be 25 ppmvd. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The dry absorption system for H2S removal shall utilize a minimum of two absorbent beds to allow leaving at least one absorbent bed operational during periodical change out of absorbent. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed any of the following limits: 11 ppmvd NOx @ 15% O2 (equivalent to 0.15 g-NOx/hp-hr), 0.0233 g-SOx/hp-hr, 0.158 g-PM10/hp-hr, 70 ppmvd CO @ 15% O2 (equivalent to 0.60 g-CO/hp-hr), or 51 ppmvd VOC @ 15% O2 (equivalent to 0.25 g-VOC/hp-hr). [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
9. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

10. If either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rule 4702] Federally Enforceable Through Title V Permit

11. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rule 4702] Federally Enforceable Through Title V Permit

12. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rule 4702] Federally Enforceable Through Title V Permit

13. Testing to demonstrate compliance with the digester gas fuel sulfur content shall be conducted weekly using draeger tubes. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Records of all monitoring and source testing results shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Source testing to measure digester gas-combustion NOx, CO, and VOC emissions shall be conducted at least once every 24 months and shall be performed during the annual grape crush operational period at this facility. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

16. Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rule 4702] Federally Enforceable Through Title V Permit

17. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702] Federally Enforceable Through Title V Permit

18. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, and VOC (ppmv) - EPA Method 18, 25A or 25B, or ARB Method 100. [District Rules 1081 and 4702] Federally Enforceable Through Title V Permit

19. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

21. The permittee shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

22. The permittee shall update the I&M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I&M plan and must submit an updated I&M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I&M plan shall be recorded in the engine's operating log. For modifications, the revised I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I&M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-651-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
11.25 MMBTU/HR SHAW LFG SPECIALTIES MODEL EF52514 DIGESTER GAS-FIRED ENCLOSED GROUND FLARE WITH FLOW-SENSING AUTOMATIC PILOT AND DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-650

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. A flame shall be present at all times in the flare whenever combustible gases are vented through the flare. [District Rule 4311] Federally Enforceable Through Title V Permit
4. The flare shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
5. Digester gas fuel to the flare shall be treated by a dry absorption system for removal of H2S. Maximum H2S concentration in the treated digester gas shall be 25 ppmvd. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The dry absorption system for H2S removal shall utilize a minimum of two absorbent beds to allow leaving at least one absorbent bed operational during periodical change out of absorbent. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The pilot shall be fired with natural gas only. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The flow sensing automatic ignition system shall use natural gas for purging. [District Rule 4311]
9. The flare shall be equipped and operated with a non-resettable cumulative fuel consumption meter or other APCO approved alternative. [District Rule 2201]
10. There shall be no visible emissions from the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions from the digester gas-fired unit shall not exceed any of the following limits: 0.06 lb-NOX/MMBtu, 0.0085 lb-SOx/MMBtu, 0.008 lb-PM10/MMBtu, 0.20 lb-CO/MMBtu, or 0.0027 lb-VOC/MMBtu. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
12. Annual digester gas fired in the unit shall not exceed 18.42 MMscf per year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Digester gas fuel consumption in standard cubic feet shall be recorded monthly. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Testing to demonstrate compliance with the digester gas fuel sulfur content shall be conducted weekly using draeger tubes. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified and a source test plan must be submitted for approval at least 30 days prior to testing. [District Rules 1081 and 4311] Federally Enforceable Through Title V Permit

16. Source testing to measure NOx and VOC emissions from this unit while fired on digester gas shall be conducted at least once every twelve (12) months and shall be performed during the annual grape crush operational period at this facility. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

17. NOX emissions determined as lb/MMBtu for source test purposes shall be determined using EPA Method 19. [District Rule 4311] Federally Enforceable Through Title V Permit

18. VOC, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case Method 25a may be used, and analysis of halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422 "Determination of Volatile organic Compounds in Emission from Stationary Sources". The VOC concentration in ppmv shall be converted to pounds per million Btu (lb/MMBtu) as specified in District Rule 4311. [District Rule 4311] Federally Enforceable Through Title V Permit

19. NOx and O2 concentrations shall be determined using EPA Method 3A, EPA Method 7E or ARB 100. [District Rule 4311] Federally Enforceable Through Title V Permit

20. The results of each source test shall be submitted to the District within 45 days thereafter. [District Rules 1081 and 4311] Federally Enforceable Through Title V Permit

21. Records of all monitoring and source testing results shall be maintained. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 4311] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-652-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-653-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-654-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-655-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-656-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-657-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-658-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-659-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-660-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-661-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-662-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-663-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-664-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-665-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
790 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-666-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-667-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-668-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-669-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 648 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-670-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
1,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 649 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily records of filling and emptying operations, including the date of the operation, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-671-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-672-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1673 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-673-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1674 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 2201] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, as defined in District Rule 4694, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-677-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-678-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1576 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-679-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1578 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-680-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1580 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-681-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1582 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-682-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1584 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-683-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1586 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-684-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1588 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-685-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-1 WITH PRESSURE/VACUUM VALVE AND REFRIGERATION.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-686-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-687-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-688-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1556 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-689-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-690-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-691-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1562 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-692-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1577 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-693-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1579 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-694-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1581 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-695-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1583 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-696-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-697-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-698-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-699-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-4 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-700-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-5 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-701-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-6 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-702-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1564 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-703-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1566 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-704-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1585 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-705-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1587 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-706-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-7 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-707-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-8 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-708-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-9 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-709-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-10 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-710-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1533 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-711-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1534 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-712-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1535 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-713-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1536 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-714-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-715-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-716-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-717-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-718-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1541 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-719-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1542 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-720-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1543 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-721-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1544 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-722-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1545 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-723-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1546 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-724-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-725-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-726-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-727-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-728-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1551 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-729-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1552 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-730-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1553 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-731-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1554 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-732-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1555 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-733-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-734-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-735-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1561 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-736-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1563 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-737-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1565 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-738-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1567 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-739-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1569 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-740-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1571 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-741-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1573 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-742-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1575 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-743-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-744-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-745-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-746-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-4 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-747-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-5 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-748-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-6 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-749-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-7 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-750-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-8 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-751-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-9 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-752-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 650 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-753-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-754-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-755-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated on the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-756-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-757-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-758-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-759-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-760-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 658 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-761-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 659 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-762-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 660 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-763-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-764-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-765-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-766-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-767-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-768-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-769-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 667 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-770-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 668 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-771-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 669 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-772-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 670 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-773-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-774-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-775-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-776-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-777-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-778-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-779-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 677 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-780-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 678 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-781-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 679 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-782-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 680 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-783-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-784-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-785-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-786-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-787-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-788-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-789-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 687 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-790-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 688 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-791-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 689 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: N-2321-792-0 **EXPIRATION DATE:** 08/31/2011

EQUIPMENT DESCRIPTION:
25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-25K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The daily VOC emissions rate for fermentation shall not exceed 3.46 lb/1000 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
8. When this tank is used for wine storage, the daily tank throughput, in gallons, shall not exceed four times the maximum nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
9. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694, 6.4.1]
10. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

12. Total annual VOC emissions from all wine fermentation and wine storage operations at this facility shall not exceed 1,167,178 lb. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Total annual VOC emissions from wine fermentation operations shall be determined by the following formula: Total annual VOC emissions = (Total Annual Red Wine Production - gallons) x (6.2 lb-VOC/1000 gallons) + (Total Annual White Wine Production - gallons) x (2.5 lb-VOC/1000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations may be determined using the total annual wine throughput and a single storage emissions factor based on the average ethanol content of the annual wine throughput; or using the throughputs for different batches of wine and batch-specific storage emissions factors based on the ethanol content of each batch. [District Rule 2201] Federally Enforceable Through Title V Permit

15. Records of total annual fermentation and total annual storage emissions, including calculation methods and parameters used, shall be maintained. [District Rule 1070 and 2201] Federally Enforceable Through Title V Permit

16. Separate annual records of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

17. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

ATTACHMENT C

Detailed Facility List

Detailed Facility Report

For Facility=2321 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

CBUS OPS INC (DBA WOODBRIDGE WINERY)	FAC #	**N 2321**	TYPE:	**TitleV**	EXPIRE ON: 08/31/2011
5950 E WOODBRIDGE ROAD	STATUS:	**A**	TOXIC ID:		AREA: 1 /
ACAMPO, CA 95220	TELEPHONE:				INSP. DATE: 08/13

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-2-5	5,049 Gallons	3020-05 B	1	93.00	93.00	A	5,049 GALLON ETHYL ALCOHOL STORAGE TANK (TANK 301)
N-2321-6-5	128 bhp	3020-10 B	1	117.00	117.00	A	128 BHP GENERAL MOTORS, MODEL SG 085, EMERGENCY PROPANE-FIRED IC ENGINE SERVED BY A HOUSTON INDUSTRIAL SILENCER CATALYTIC CONVERTER, MODEL DN/S-1604C, POWERING AN 80 KW GENERATOR
N-2321-7-4	5,048 gallons	3020-05 B	1	93.00	93.00	A	5,049 GALLON ETHYL ALCOHOL STORAGE TANK (TANK 302)
N-2321-8-4	0.75 hp	3020-01 A	1	87.00	87.00	A	METAL PARTS AND PRODUCTS AND WOOD PRODUCTS COATING OPERATIONS SERVED BY A SPRAY BOOTH WITH EXHAUST FILTERS
N-2321-9-1	Miscellaneous	3020-06	1	105.00	105.00	A	UNCONFINED ABRASIVE BLASTING OPERATION
N-2321-10-4	Miscellaneous	3020-06	1	105.00	105.00	A	OUTDOOR WOOD PRODUCTS COATING OPERATION
N-2321-11-1	133 hp IC engine	3020-10 B	1	117.00	117.00	A	133 HP CUMMINS MODEL V-378-F2 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP
N-2321-12-1	115 hp IC engine	3020-10 B	1	117.00	117.00	A	115 HP CLARKE GM MODEL MD-6T-1334 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIRE PUMP
N-2321-13-1	97 hp IC engine	3020-10 A	1	80.00	80.00	A	97 HP DETROIT DIESEL MODEL 1033-5000 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE
N-2321-97-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-98-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-99-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-100-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-101-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-102-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 116 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-103-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 117 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-104-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 118 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-105-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 119 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-106-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 120 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-107-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-108-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-109-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-110-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-111-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-112-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-113-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-114-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-115-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 129 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-116-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 130 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-117-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-118-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-119-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-120-2	6,969 GAL	3020-05 B	1	93.00	93.00	A	6,969 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-121-2	1,122 GAL	3020-05 A	1	75.00	75.00	A	1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-123-2	1,122 GAL	3020-05 A	1	75.00	75.00	A	1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 137 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-124-2	1,122 GAL	3020-05 A	1	75.00	75.00	A	1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 138 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-125-2	1,122 GAL	3020-05 A	1	75.00	75.00	A	1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 139 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-126-2	1,122 GAL	3020-05 A	1	75.00	75.00	A	1,122 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 140 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-127-2	165,616 GAL	3020-05 E	1	246.00	246.00	A	165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 201 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-128-2	165,616 GAL	3020-05 E	1	246.00	246.00	A	165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 202 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-129-2	165,616 GAL	3020-05 E	1	246.00	246.00	A	165,616 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 203 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-130-2	166,340 GAL	3020-05 E	1	246.00	246.00	A	166,340 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 204 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-131-2	166,340 GAL	3020-05 E	1	246.00	246.00	A	166,340 GALLON MILD STEEL LINED ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 205 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-132-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 300 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-133-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 301 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-134-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 302 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-135-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 303 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-136-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 304 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-137-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 305 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-138-2	5,063 GAL	3020-05 B	1	93.00	93.00	A	5,063 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 306 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-139-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 307 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-140-2	1,030 GAL	3020-05 A	1	75.00	75.00	A	1,030 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 321 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-141-2	3,240 GAL	3020-05 A	1	75.00	75.00	A	3,240 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 320 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-142-2	3,240 GAL	3020-05 A	1	75.00	75.00	A	3,240 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 322 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-143-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 323 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-144-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 324 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-145-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 325 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-146-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 326 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-147-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 327 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-148-2	3,358 GAL	3020-05 B	1	93.00	93.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 328 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-149-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 329 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-150-2	3,358 GAL	3020-05 A	1	75.00	75.00	A	3,358 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 330 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-151-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-152-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-153-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-154-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-155-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-156-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-157-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-158-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-159-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-161-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-162-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-164-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-165-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-166-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-167-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-168-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-169-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-170-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-171-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 507 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-172-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 508 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-173-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-174-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-175-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-176-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-177-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-178-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-179-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-180-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-181-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 517 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-182-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 518 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-183-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-184-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-185-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-186-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-187-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-188-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-189-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-190-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-191-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-192-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-193-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-194-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-195-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-196-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-197-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 549 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-198-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 550 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-199-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 551 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-200-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 552 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-201-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 553 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-202-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 554 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-203-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 555 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-204-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 556 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-205-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 557 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-206-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 558 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-207-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 559 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-208-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 560 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-209-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 561 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-210-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 562 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-211-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 563 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-212-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 564 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-213-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 565 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-214-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 566 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-215-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 567 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-216-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 568 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-217-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 569 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-218-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 570 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-219-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 571 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-220-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 572 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-221-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 573 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-222-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 574 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-223-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 575 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-224-2	39,798 GAL	3020-05 C	1	135.00	135.00	A	39,798 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 576 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-225-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-226-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-227-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-228-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-229-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-230-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-231-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-232-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-233-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-234-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-235-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 701 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-236-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 702 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-237-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 703 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-238-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 704 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-239-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 705 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-240-2	16,118 GAL	3020-05 B	1	93.00	93.00	A	16,118 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 706 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-241-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 707 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-242-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 708 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-243-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 709 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-244-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 710 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-245-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 711 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-246-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 712 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-247-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 713 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-248-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 714 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-249-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 715 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-250-2	2,977 GAL	3020-05 A	1	75.00	75.00	A	2,977 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 716 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-251-2	6,934 GAL	3020-05 B	1	93.00	93.00	A	6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 717 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-252-2	6,934 GAL	3020-05 B	1	93.00	93.00	A	6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 718 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-253-2	6,934 GAL	3020-05 B	1	93.00	93.00	A	6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 719 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-254-2	6,934 GAL	3020-05 B	1	93.00	93.00	A	6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 720 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-255-2	6,934 GAL	3020-05 B	1	93.00	93.00	A	6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 721 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-256-2	6,934 GAL	3020-05 B	1	93.00	93.00	A	6,934 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 722 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-257-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 731 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-258-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 732 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-259-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 733 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-260-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 734 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-261-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 735 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-262-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 736 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-263-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 737 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-264-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 738 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-265-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 739 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-266-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 740 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-267-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 741 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-268-2	53,546 GAL	3020-05 D	1	185.00	185.00	A	53,546 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 742 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-269-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 751 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-270-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 752 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-271-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 753 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-272-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 754 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-273-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 755 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-274-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 756 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-275-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 757 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-276-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 758 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-277-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 759 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-278-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 760 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-279-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 761 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-280-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 762 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-281-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 763 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-282-2	40,697 GAL	3020-05 C	1	135.00	135.00	A	40,697 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 764 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-283-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-284-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-285-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-286-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-287-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-288-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-289-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-290-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-291-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-292-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-293-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-294-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-295-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-296-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-297-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 815 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-298-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 816 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-299-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 817 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-300-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 818 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-301-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 819 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-302-2	11,150 GAL	3020-05 B	1	93.00	93.00	A	11,150 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 820 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-303-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 901 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-304-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 902 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-305-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 903 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-306-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 904 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-307-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 905 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-308-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 906 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-309-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 907 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-310-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 908 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-311-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 909 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-312-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 910 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-313-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 911 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-314-2	19,700 GAL	3020-05 B	1	93.00	93.00	A	19,700 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 912 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-315-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 921 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-316-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 922 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-317-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 923 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-318-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 924 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-319-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 925 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-320-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 926 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-321-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 927 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-322-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 928 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-323-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 929 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-324-2	25,968 GAL	3020-05 C	1	135.00	135.00	A	25,968 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 930 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-325-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1101 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-326-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1102 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-327-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1103 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-328-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1104 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-329-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1105 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-330-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1106 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-331-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1107 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-332-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1108 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-333-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1109 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-334-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1110 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-335-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1111 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-336-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1112 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-337-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1113 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-338-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1114 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-339-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1115 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-340-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1116 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-341-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1117 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-342-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1118 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-343-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1119 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-344-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1120 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-345-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1121 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-346-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1122 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-347-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1123 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-348-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1124 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-349-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1125 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-350-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1126 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-351-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1127 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-352-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1128 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-353-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1129 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-354-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1130 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-355-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1131 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-356-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1132 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-357-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1133 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-358-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1134 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-359-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1135 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-360-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1136 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-361-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1137 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-362-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1138 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-363-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1139 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-364-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1140 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-365-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1141 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-366-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1142 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-367-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1143 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-368-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1144 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-369-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1145 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-370-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1146 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-371-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1147 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-372-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1148 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-373-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1151 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-374-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1152 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-375-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1153 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-376-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1154 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-377-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1155 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-378-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1156 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-379-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1157 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-380-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1158 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-381-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1159 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-382-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1160 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-383-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1161 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-384-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1162 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-385-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1163 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-386-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1164 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-387-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1165 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-388-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1166 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-389-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1167 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-390-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1168 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-391-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1169 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-392-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1170 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-393-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1171 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-394-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1172 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-395-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1173 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-396-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1174 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-397-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1175 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-398-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1176 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-399-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1177 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-400-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1178 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-401-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1179 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-402-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1180 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-403-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1181 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-404-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1182 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-405-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1183 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-406-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1184 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-407-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1185 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-408-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1186 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-409-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1187 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-410-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1188 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-411-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1189 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-412-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1190 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-413-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1191 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-414-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1192 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-415-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1193 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-416-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1194 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-417-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1195 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-418-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1196 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-419-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1197 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-420-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1198 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-421-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1201 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-422-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1202 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-423-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1203 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-424-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1204 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-425-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1205 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-426-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1206 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-427-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1207 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-428-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1208 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-429-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1209 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-430-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1210 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-431-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1211 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-432-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1212 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-433-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1213 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-435-2	31,538 GAL	3020-05 C	1	135.00	135.00	A	31,538 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1215 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-447-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1223 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-448-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1224 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-449-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1225 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-450-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1226 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-451-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1227 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-452-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1228 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-453-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1229 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-454-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1230 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-455-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1231 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-456-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1232 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-457-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1233 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-458-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1234 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-459-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1235 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-460-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1236 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-461-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1237 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-462-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1238 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-463-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1239 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-464-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1240 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-465-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1241 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-466-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1242 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-467-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1243 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-468-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1244 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-469-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1245 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-470-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1246 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-471-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1251 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-472-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1252 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-473-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1253 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-474-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1254 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-475-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1255 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-476-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1256 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-477-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1257 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-478-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1258 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-479-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1259 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-480-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1260 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-481-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1261 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-482-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1262 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-483-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1263 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-484-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1264 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-485-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1265 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-486-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1266 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-487-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1267 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-488-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1268 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-489-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1269 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-490-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1270 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-491-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1271 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-492-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1272 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-493-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1273 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-494-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1274 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-495-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1275 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-496-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1276 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-497-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1277 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-498-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1278 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-499-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1279 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-500-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1280 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-501-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1281 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-502-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1282 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-503-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1283 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-504-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1284 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-505-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1285 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-506-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1286 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-507-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1301 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-508-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1302 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-509-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1303 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-510-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1304 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-511-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1305 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-512-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1306 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-513-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1307 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-514-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1308 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-515-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1309 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-516-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1310 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-517-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1311 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-518-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1312 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-519-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1313 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-520-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1314 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-521-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1315 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-522-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1316 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-523-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1317 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-524-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1318 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-525-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1319 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-526-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1320 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-527-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1321 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-528-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1322 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-529-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1323 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-530-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1324 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-531-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1325 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-532-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1326 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-533-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1327 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-534-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1328 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-535-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1329 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-536-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1330 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-537-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1331 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-538-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1332 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-539-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1401 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-540-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1402 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-541-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1403 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-542-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1404 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-543-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1405 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-544-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1406 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-545-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1407 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-546-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1408 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-547-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1409 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-548-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1410 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-549-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1411 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-550-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1412 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-551-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1413 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-552-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1414 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-553-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1415 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-554-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1416 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-555-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1417 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-556-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1418 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-557-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1419 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-558-2	108,774 GAL	3020-05 E	1	246.00	246.00	A	108,774 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1420 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-559-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-560-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-561-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-562-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-563-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-564-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-565-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-566-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-567-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-568-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-569-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1511 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-570-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1512 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-571-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1513 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-572-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1514 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-573-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1515 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-574-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1516 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-575-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1517 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-576-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1518 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-577-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1519 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-578-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1520 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-579-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1521 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-580-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1522 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-581-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1523 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-582-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1524 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-583-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1525 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-584-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1526 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-585-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1527 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-586-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1528 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-587-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1529 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-588-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1530 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-589-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1531 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-590-2	216,830 GAL	3020-05 E	1	246.00	246.00	A	216,830 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1532 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-591-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1601 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-592-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1602 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-593-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1603 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-594-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1604 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-595-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1605 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-596-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1606 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-597-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1607 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-598-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1608 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-599-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1609 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-600-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1610 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-601-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1611 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-602-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1612 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-603-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1625 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-604-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1626 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-605-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1627 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-606-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1628 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-607-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1629 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-608-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1630 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-609-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1631 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-610-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1632 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-611-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1633 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-612-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1634 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-613-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1635 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-614-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1636 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-615-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1649 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-616-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1650 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-617-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1651 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-618-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1652 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-619-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1653 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-620-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1654 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-621-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1655 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-622-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1656 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-623-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1657 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-624-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1658 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-625-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1659 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-626-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1660 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-629-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1661 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-630-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1662 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-631-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1663 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-632-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1664 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-633-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1665 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-634-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1666 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-635-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1667 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-636-2	62,554 GAL	3020-05 D	1	185.00	185.00	A	62,554 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1668 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-637-2	3,070 GAL	3020-05 A	1	75.00	75.00	A	3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-638-2	3,070 GAL	3020-05 A	1	75.00	75.00	A	3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-639-2	3,070 GAL	3020-05 A	1	75.00	75.00	A	3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-640-2	3,070 GAL	3020-05 A	1	75.00	75.00	A	3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-4 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-641-2	3,070 GAL	3020-05 A	1	75.00	75.00	A	3,070 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK LT-5 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-642-2	18,000 GAL	3020-05 B	1	93.00	93.00	A	18,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK GANI WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-643-2	9,247 GAL	3020-05 B	1	93.00	93.00	A	9,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK ROTO WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-644-2	6,287 GAL	3020-05 B	1	93.00	93.00	A	6,287 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 941 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-645-2	12,067 GAL	3020-05 B	1	93.00	93.00	A	12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 942 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-646-2	12,067 GAL	3020-05 B	1	93.00	93.00	A	12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 943 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-647-2	12,067 GAL	3020-05 B	1	93.00	93.00	A	12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 944 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-648-2	12,067 GAL	3020-05 B	1	93.00	93.00	A	12,067 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 945 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-649-0	122 bhp	3020-10 B	1	117.00	117.00	A	122 HP ENERGY NOW MODEL ENI65 DIGESTER GAS OR NATURAL GAS-FIRED RICH-BURN IC ENGINE SERVED BY JOHNSON MATTHEY BANDITO CATALYTIC CONVERTER POWERING AN ELECTRICAL GENERATOR WITH DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-651
N-2321-650-0	122 bhp	3020-10 B	1	117.00	117.00	A	122 HP ENERGY NOW MODEL ENI65 DIGESTER GAS OR NATURAL GAS-FIRED RICH-BURN IC ENGINE SERVED BY JOHNSON MATTHEY BANDITO CATALYTIC CONVERTER POWERING AN ELECTRICAL GENERATOR WITH DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-651
N-2321-651-0	11.25 MMBtu/hour	3020-02 G	1	815.00	815.00	A	11.25 MMBTU/HR SHAW LFG SPECIALTIES MODEL EF52514 DIGESTER GAS-FIRED ENCLOSED GROUND FLARE WITH FLOW-SENSING AUTOMATIC PILOT AND DRY ABSORPTION H2S REMOVAL SYSTEM SHARED WITH PERMIT UNITS N-2321-649 AND '-650

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-652-0	500 GALLON	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 631 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-653-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 632 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-654-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 633 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-655-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 634 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-656-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 635 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-657-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 636 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-658-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 637 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-659-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 638 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-660-0	500 GAL	3020-05 A	1	75.00	75.00	A	500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 639 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-661-0	543 GAL	3020-05 A	1	75.00	75.00	A	543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 641 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-662-0	543 GAL	3020-05 A	1	75.00	75.00	A	543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 642 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-663-0	543 GAL	3020-05 A	1	75.00	75.00	A	543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 643 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-664-0	543 GAL	3020-05 A	1	75.00	75.00	A	543 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 644 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-665-0	790 GAL	3020-05 A	1	75.00	75.00	A	790 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 640 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-666-0	1,000 GAL	3020-05 A	1	75.00	75.00	A	1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 645 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-667-0	1,000 GAL	3020-05 A	1	75.00	75.00	A	1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 646 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-668-0	1,000 GAL	3020-05 A	1	75.00	75.00	A	1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 647 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-669-0	1,000 GAL	3020-05 A	1	75.00	75.00	A	1,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 648 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-670-0	1,100 GAL	3020-05 A	1	75.00	75.00	A	1,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 649 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-671-0	3,980 GAL	3020-05 A	1	75.00	75.00	A	3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1214 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-672-0	3,980 GAL	3020-05 A	1	75.00	75.00	A	3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1673 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-673-0	3,980 GAL	3020-05 A	1	75.00	75.00	A	3,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1674 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-677-0	6,050 GAL	3020-05 B	1	93.00	93.00	A	6,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1216 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-678-0	6,050 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1576 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-679-0	6,284 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1578 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-680-0	6,284 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1580 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-681-0	6,284 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1582 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-682-0	6,284 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1584 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-683-0	6,284 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1586 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-684-0	6,284 GAL	3020-05 B	1	93.00	93.00	A	6,284 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1588 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-685-0	8,050 GAL	3020-05 B	1	93.00	93.00	A	8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-1 WITH PRESSURE/VACUUM VALVE AND REFRIGERATION.
N-2321-686-0	8,050 GAL	3020-05 B	1	93.00	93.00	A	8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-687-0	8,050 GAL	3020-05 B	1	93.00	93.00	A	8,050 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-8K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-688-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1556 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-689-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1558 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-690-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1560 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-691-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1562 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-692-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1577 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-693-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1579 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-694-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1581 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-695-0	9,372 GAL	3020-05 B	1	93.00	93.00	A	9,372 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1583 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-696-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-697-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-698-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-699-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-4 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-700-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-5 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-701-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-6 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-702-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1564 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-703-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1566 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-704-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1585 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-705-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1587 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-706-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-7 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-707-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-8 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-708-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-9 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-709-0	12,049 GAL	3020-05 B	1	93.00	93.00	A	12,049 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-12K-10 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-710-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1533 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-711-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1534 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-712-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1535 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-713-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1536 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-714-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1537 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-715-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1538 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-716-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1539 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-717-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1540 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-718-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1541 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-719-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1542 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-720-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1543 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-721-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1544 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-722-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1545 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-723-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1546 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-724-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1547 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-725-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1548 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-726-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1549 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-727-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1550 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-728-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1551 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-729-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1552 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-730-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1553 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-731-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1554 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-732-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1555 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-733-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1557 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-734-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1559 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-735-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1561 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-736-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1563 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-737-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1565 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-738-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1567 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-739-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1569 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-740-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1571 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-741-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1573 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-742-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1575 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-743-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-744-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-2 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-745-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-3 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-746-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-4 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-747-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-5 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-748-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-6 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-749-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-7 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-750-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-8 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-751-0	17,893 GAL	3020-05 B	1	93.00	93.00	A	17,893 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-18K-9 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-752-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 650 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-753-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 651 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-754-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 652 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-755-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 653 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-756-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 654 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-757-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 655 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-758-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 656 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-759-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 657 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-760-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 658 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-761-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 659 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-762-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 660 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-763-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 661 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-764-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 662 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-765-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 663 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-766-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 664 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-767-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 665 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-768-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 666 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-769-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 667 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-770-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 668 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-771-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 669 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-772-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 670 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-773-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 671 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-774-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 672 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-775-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 673 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-776-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 674 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-777-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 675 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-778-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 676 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-779-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 677 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-780-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 678 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-781-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 679 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-782-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 680 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-783-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 681 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-784-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 682 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

Detailed Facility Report

For Facility=2321 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-2321-785-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 683 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-786-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 684 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-787-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 685 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-788-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 686 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-789-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 687 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-790-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 688 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-791-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 689 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.
N-2321-792-0	25,395 GAL	3020-05 C	1	135.00	135.00	A	25,395 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK RHP-25K-1 WITH PRESSURE/VACUUM VALVE AND INSULATION OR EQUIVALENT.

Number of Facilities Reported: 1

ATTACHMENT D

SIP Stringency Analysis for Rule 4702

Comparison of the Non-SIP amended version (amended August 18, 2011) of District Rule 4702 (Internal Combustion Engines) with the SIP approved version (amended January 18, 2007) of District Rule 4702 (Internal Combustion Engines – Phase 2)			
Section	**SIP Version of Rule 4702 (Amended January 18, 2007)**	**Non-SIP Version of Rule 4702 (Amended August 18, 2011)**	**Conclusion**
1.0 Purpose	1.0 The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), and volatile organic compounds (VOC) from internal combustion engines.	1.0 The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compounds (VOC), and sulfur oxides (SOx) from internal combustion engines.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
2.0 Applicability	2.0 This rule applies to any internal combustion engine with a rated brake horsepower greater than 50 horsepower.	2.0 This rule applies to any internal combustion engine rated at 25 brake horsepower or greater.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
4.0 Exemptions	4.1 The requirements of this rule shall not apply to the following engines: 4.1.1 An engine used to propel implements of husbandry, as that term is defined in Section 36000 of the California Vehicle Code, as that section existed on January 1, 2003. 4.1.2 An engine used exclusively to power a wind machine. 4.1.3 A de-rated spark-ignited engine not used in agricultural operations, provided the de-rating occurred before June 1, 2004. 4.1.4 A de-rated spark-ignited engine used in agricultural operations or a de-rated compression-ignited engine, provided the de-rating occurred before June 1, 2005. 4.1.5 An engine used exclusively to power Mobile Agricultural Equipment. 4.2 Except for the requirements of Section 5.7 and Section 6.2.3, the requirements of this rule shall not apply to: 4.2.1 An emergency standby engine as defined in Section 3.0 of this rule, and provided that it is operated with a nonresettable elapsed operating time meter. In lieu of a nonresettable time meter, the owner of an emergency engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions. 4.2.2 An internal combustion engine that is	4.1 The requirements of this rule shall not apply to the following engines: 4.1.1 An engine used to propel implements of husbandry, as that term is defined in Section 36000 of the California Vehicle Code, as that section existed on January 1, 2003. 4.1.2 An engine used exclusively to power a wind machine. 4.1.3 A de-rated spark-ignited engine not used in agricultural operations, provided the de-rating occurred before June 1, 2004. 4.1.4 A de-rated spark-ignited engine used in agricultural operations or a de-rated compression-ignited engine, provided the de-rating occurred before June 1, 2005. 4.1.5 An engine used exclusively to power Mobile Agricultural Equipment. 4.1.6 An internal combustion engine registered as a portable emissions unit under the Statewide Portable Equipment Registration Program pursuant to California Code of Regulations Title 13, Division 3, Chapter 9, Article 5, Sections 2450-2465. 4.1.7 An internal combustion engine registered as a portable emissions unit under Rule 2280 (Portable Equipment Registration). 4.2 Except for the requirements of Sections 5.9 and 6.2.3, the requirements of this rule shall not apply to an emergency standby engine or a low-use engine, provided that the engine is operated with an operating nonresettable elapsed time meter. 4.2.1 In lieu of operating a nonresettable	**The non-SIP version of this rule includes several operations that are not required to meet the requirements of this rule. These operations were added to clarify what operations are subject to this rule. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	operated no more than 200 hours per calendar year as determined by an operational nonresettable elapsed operating time meter and provided the engine is not used to perform any of the functions specified in Section 4.2.2.1 through Section 4.2.2.3 below. In lieu of a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions. 4.2.2.1 To generate electrical power that is either fed into the electrical utility power grid or used to reduce electrical power purchased by a stationary source, 4.2.2.2 To generate mechanical power that is used to reduce electrical power purchased by a stationary source, or 4.2.2.3 In a distributed generation application. 4.3 Except for the administrative requirements of Section 6.2.3, the requirements of this rule shall not apply to: 4.3.1 An internal combustion engine that meets the following conditions: 4.3.1.1 The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood, and 4.3.1.2 Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed operating time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine, and 4.3.1.3 The engine is operated with a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions. 4.3.2 An internal combustion engine registered as a portable emissions unit	elapsed time meter, the operator may use an alternative device, method, or technique, in determining operating time, provided that the alternative is approved by the APCO and EPA and is allowed by the Permit-to-Operate or Permit-Exempt Equipment Registration. The operator must demonstrate that the alternative device, method, or technique is equivalent to using a nonresettable elapsed time meter. 4.2.2 The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions. 4.3 Except for the administrative requirements of Section 6.2.3, the requirements of this rule shall not apply to the following: 4.3.1 An internal combustion engine that meets the following conditions: 4.3.1.1 The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood; and 4.3.1.2 Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine; and 4.3.1.3 The engine is operated with an operational nonresettable elapsed time meter. In lieu of installing a nonresettable elapsed time meter, the operator of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA. The operator of the engine shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions. 4.3.2 Military Tactical Equipment and engines used to retract military aircraft arresting gear cables. 4.4 For existing facilities, a replacement unit installed for the sole purpose of complying with the requirements of this rule shall be considered to be an emission control technique and shall be exempt from the Best Available Control Technology (BACT) and offsets requirements of District Rule 2201 (New and Modified Stationary Source Review Rule) provided that all other requirements of Rule 2201 are met.	

	under Rule 2280 (Portable Equipment Registration) or the Statewide Portable Equipment Registration Program pursuant to Sections 2450-2465, Article 5, Title 13, California Code of Regulations. 4.3.3 Military Tactical Equipment and engines used to retract military aircraft arresting gear cables. 4.4. A replacement engine installed for the sole purpose of complying with the requirements of this rule shall be exempt from the Best Available Control Technology (BACT) and Offsets requirements of District Rule 2201 (New and Modified Stationary Source Review Rule) provided that all of the following conditions are met: 4.4.1 The replacement engine is of equal or lesser horsepower rating of the engine being replaced, 4.4.2 The replacement engine is subject to the same operational parameters (e.g. hours of operation, fuel use limitations, etc.) as the engine being replaced, 4.4.3 The replacement engine performs the same function as the engine being replaced, and 4.4.4 The emissions of the replacement engine are no greater than the emissions of the engine being replaced.	4.5 Except for the requirements of Section 5.1, the requirements of this rule shall not apply to stationary engines rated at least 25 Brake Horsepower, up to, and including 50 Brake Horsepower.	
5.0 Requirements	**Note:** Secton 5.0 requirements refer to Tables 1 through 4, which list the emission limits/standards for various categories of IC engines subject to this rule. These Tables are included at the end of this Stringency Comparison for each version of the rule.		
	N/A	5.1 Stationary Engines Rated at Least 25 Brake Horsepower, Up To, and Including 50 Brake Horsepower and Used in Non-Agricultural Operations (Non-AO) 5.1.1 On and after July 1, 2012, no person shall sell or offer for sale any non-AO spark-ignited engine or any non-AO compression-ignited engine unless the engine meets the applicable requirements and emission limits specified in 40 Code of Federal Regulation (CFR) 60 Subpart IIII (Standards of Performance for Stationary Compression Ignition Internal Combustion Engines) and 40 CFR 60 Subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines) for the year in which the ownership of the engine changes. 5.1.2 By January 1, 2013, the operator shall submit a one-time report that includes the number of engines at the stationary source, and the following information for each engine: 5.1.2.1 Location of each engine, 5.1.2.2 Engine manufacturer,	**The SIP version does not apply to engines rated between 25 and 50 bhp. Therefore, the Non-SIP Version of the rule is more stringent.**

		5.1.2.3 Model designation and engine serial number, 5.1.2.4 Rated brake horsepower, 5.1.2.5 Type of fuel and type of ignition, 5.1.2.6 Combustion type: rich-burn, lean-burn, or compression ignition, 5.1.2.7 Purpose, and intended use, of the engine, 5.1.2.8 Typical daily operating schedule, and 5.1.2.9 Fuel consumption (cubic feet for gas or gallons for liquid fuel) for the previous one-year period.	
	5.1 Engine Emission Limits/Standards 5.1.1 Spark-Ignited Internal Combustion Engine Emission Limits/Standards - The owner of a spark-ignited internal combustion engine shall not operate it in such a manner that results in emissions exceeding the limits in Table 1 below for the appropriate engine type according to the compliance schedules listed in Section 7.0 or according to the compliance dates specified in Table 1 below. A spark-ignited engine shall comply with the applicable emission limits pursuant to Section 5.1 or Section 8.0.	5.2 Stationary Engines Rated at Greater than 50 Brake Horsepower (>50 bhp) 5.2.1 Spark Ignited Engines Used in non-AO - Table 1 Emission Limits/Standards The operator of a spark-ignited internal combustion engine rated at >50 bhp that is used exclusively in non-AO shall not operate it in such a manner that results in emissions exceeding the limits in Table 1 for the appropriate engine type until such time that the engine has demonstrated compliance with Table 2 emission limits pursuant to the compliance deadlines in Section 7.5. In lieu of complying with Table 1 emission limits, the operator of a spark-ignited engine shall comply with the applicable emission limits pursuant to Section 8.0. 5.2.2 Spark-Ignited Engines Used in non-AO – Table 2 Emission Limits/Standards On and after the compliance schedule specified in Section 7.5, the operator of a spark-ignited engine > 50 bhp that is used in non-AO shall comply with all the applicable requirements of the rule and one of the following, on an engine-by-engine basis: 5.2.2.1 On and after the compliance schedule specified in Section 7.5, the operator of a spark-ignited engine that is used exclusively in non-AO shall comply with Sections 5.2.2.1.1 through 5.2.2.1.3 on an engine-by-engine basis: 5.2.2.1.1 NOx, CO, and VOC emission limits pursuant to Table 2; 5.2.2.1.2 SOx control requirements of Section 5.7, pursuant to the deadlines specified in Section 7.5; and 5.2.2.1.3 Monitoring requirements of Section 5.10, pursuant to the deadlines specified in Section 7.5. 5.2.2.2 In lieu of complying with the NOx emission limit requirement of Section 5.2.2.1.1, an operator may pay an annual fee to the District, as specified in Section 5.6, pursuant to Section 7.6.	**The requirements of Table 1 of both versions of the rule are identical. Table 2 from the non-SIP version found at the end of this document has emissions requirements that are more stringent than the requirements of Table 1 in both versions of the Rule. The standards of the non-SIP version are at least as stringent as the SIP version. Therefore, the non-SIP version of the rule is more stringent than the SIP version of the rule.**

		5.2.2.2.1 Engines in the fee payment program shall have actual emissions not greater than the applicable limits in Table 1 during the entire time the engine is part of the fee payment program. 5.2.2.2.2 Compliance with Section 5.7 and 5.10, pursuant to the deadlines specified in Section 7.5, is also required as part of the fee payment option. 5.2.2.3 In lieu of complying with the NOx, CO, and VOC limits of Table 2 on an engine-by-engine basis, an operator may elect to implement an alternative emission control plan pursuant to Section 8.0. An operator electing this option shall not be eligible to participate in the fee payment option outlined in Section 5.2.2.2 and Section 5.6. 5.2.3 Spark-Ignited Engines Used Exclusively in Agricultural Operations (AO) 5.2.3.1 The operator of a spark-ignited internal combustion engine rated at >50 bhp that is used exclusively in AO shall not operate it in such a manner that results in emissions exceeding the limits in Table 3 for the appropriate engine type on an engine-by-engine basis. 5.2.3.2 In lieu of complying with the NOx, CO, and VOC limits of Table 3 on an engine-by-engine basis, an operator may elect to implement an alternative emission control plan pursuant to Section 8.0. 5.2.3.3 An operator of an AO spark-ignited engine that is subject to the applicable requirements of Table 3 shall not replace such engine with an engine that emits more emissions of NOx, VOC, and CO, on a ppmv basis, (corrected to 15% oxygen on a dry basis) than the engine being replaced.	

	5.1.2 Compression-Ignited Internal Combustion Engine Emission Limits/Standards and Compliance Schedules – The owner of a compression-ignited internal combustion engine shall repower, replace or control the engine to comply with the applicable limits/standards and compliance dates in Table 2 below. The annual hours of operation shall be determined on a calendar year basis. A compression-ignited engine shall comply with the applicable emission limits/standards pursuant to Section 5.1.2 or Section 8.0. 5.1.3 On and after June 1, 2006, the owner of an AO rich-burn spark-ignited engine, AO lean-burn spark-ignited engine, or AO compression-ignited engine that is subject to the requirements of Section 5.1 shall not replace such engine with a rich-burn spark-ignited, lean-burn spark-ignited, or compression-ignited engine, respectively, that emits more emissions of NOx, VOC, and CO, on a ppmv basis, (corrected to 15% oxygen on a dry basis) than the engine being replaced. 5.1.4 The owner of a non-certified compression-ignited engine, in place on June 1, 2006, shall comply with the Emission Limit/Standard and Compliance Date in Table 2 based on the non-certified compression-ignited engine that was in place on June 1, 2006, unless the owner meets one of the following conditions: 5.1.4.1Replaces the non-certified compression-ignited engine with a non-modified Tier 3 or a non-modified Tier 4 engine after June 1, 2006, 5.1.4.2 Controls the non-certified compression-ignited engine after June 1, 2006, to emit emissions less than, or equal to, 80 ppm NOx, 2,000 ppm CO, and 750 ppm VOC, (corrected to 15% oxygen on a dry basis), or 5.1.4.3 Replaces the non-certified compression-ignited engine after June 1, 2006, with an engine or other source with emissions less than, or equal to, 80 ppm NOx, 2,000 ppm CO, and 750 ppm VOC (corrected to 15% oxygen on a dry basis).	5.2.4 Certified Compression-Ignited Engines (AO and non-AO) The operator of a certified compression-ignited engine rated >50 bhp shall comply with the following requirements: 5.2.4.1 Repower, replace, or control the engine's emissions to comply with the applicable limits/standards in Table 4 on an engine-by-engine basis by the compliance dates as specified in Table 4. 5.2.4.2 The annual hours of operation shall be determined on a calendar year basis. 5.2.4.3 In lieu of complying with the NOx, CO, and VOC limits of Table 4 on an engine-by-engine basis, an operator may elect to implement an alternative emission control plan pursuant to Section 8.0. 5.2.4.4 An operator of an AO compression-ignited engine that is subject to the applicable requirements of Table 4 shall not replace such engine with an engine that emits more emissions of NOx, VOC, and CO, on a ppmv basis, (corrected to 15% oxygen on a dry basis) than the engine being replaced. 5.2.5 Non-Certified Compression-Ignited Engines (AO and Non-AO) The operator of a non-certified compression-ignited engine, in place on or before June 1, 2006, shall comply with the Emission Limit/Standard and Compliance Date in Table 4 based on the non-certified compression ignited engine that was in place on June 1, 2006, unless the operator meets one of the following conditions: 5.2.5.1 Replace the non-certified compression-ignited engine with a nonmodified Tier 3 or a non-modified Tier 4 engine after June 1, 2006; 5.2.5.2 Control the non-certified compression-ignited engine after June 1, 2006, to emit emissions less than, or equal to, 80 ppmv NOx, 2,000 ppmv CO, and 750 ppmv VOC (corrected to 15% oxygen on a dry basis); or 5.2.5.3 Replace the non-certified compression-ignited engine after June 1, 2006, with an engine or other source with emissions less than, or equal to, 80 ppmv NOx, 2,000 ppmv CO, and 750 ppmv VOC (corrected to 15% oxygen on a dry basis).	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	5.2 All continuous emission monitoring systems (CEMS) emissions measurements shall be averaged over a period of 15 consecutive minutes. Any 15-consecutive-minute block average CEMS measurement exceeding the applicable emission limits of this rule shall constitute a violation of this rule. 5.3 Percent emission reductions, if used to comply with the NOx emission limits of Section 5.1, shall be calculated as follows: 5.3.1 For engines with external control devices that are not operated in combination with a second emission control device or technique, percent reduction shall be calculated using emission samples taken at the inlet and outlet of the control device. 5.3.2 For engines without external control devices and for engines with an external control device in combination with a second emission control device or technique, percent reduction shall be based on source test results for the uncontrolled engine and the engine after the control device or technique has been employed. In this situation, the engine's typical operating parameters, loading, and duty cycle shall be documented and repeated at each successive post-control source test to ensure that the engine is meeting the percent reduction limit. When representative source sampling prior to the application of an emissions control technology or technique is not available, the APCO may approve the use of a manufacturer's uncontrolled emissions information or source sampling from a similar, uncontrolled engine. 5.4 The owner of an internal combustion engine that uses percent emission reduction to comply with the NOx emission limits of Section 5.1 shall provide an accessible inlet and outlet on the external control device or the engine as appropriate for taking emission samples and as approved by the APCO.	5.3 All continuous emission monitoring systems (CEMS) emissions measurements shall be averaged over a period of 15 consecutive minutes. Any 15-consecutiveminute block average CEMS measurement exceeding the applicable emission limits of this rule shall constitute a violation of this rule. 5.4 Percent emission reductions, if used to comply with the NOx emission limits of Section 5.2, shall be calculated as follows: 5.4.1 For engines with external control devices that are not operated in combination with a second emission control device or technique, percent reduction shall be calculated using emission samples taken at the inlet and outlet of the control device. 5.4.2 For engines without external control devices and for engines with an external control device in combination with a second emission control device or technique, percent reduction shall be based on source test results for the uncontrolled engine and the engine after the control device or technique has been employed. In this situation, the engine's typical operating parameters, loading, and duty cycle shall be documented and repeated at each successive post-control source test to ensure that the engine is meeting the percent reduction limit. When representative source sampling prior to the application of an emissions control technology or technique is not available, the APCO may approve the use of a manufacturer's uncontrolled emissions information or source sampling from a similar, uncontrolled engine. 5.5 The operator of an internal combustion engine that uses percent emission reduction to comply with the NOx emission limits of Section 5.2 shall provide an accessible inlet and outlet on the external control device or the engine as appropriate for taking emission samples and as approved by the APCO.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	N/A	5.6 Payment of an Annual Fee In Lieu of Complying with a NOx Emission Limit The operator of a non-AO spark-ignited engine who elects to comply under Section 5.2.2.2 shall comply with the requirements of Sections 5.6 by the schedule specified in Section 7.6 and all other applicable provisions of this rule. 5.6.1 An operator shall pay a total annual fee to the District based on the total NO_X emissions from those engines that will be subject to Section 5.2.2.2. The annual fee shall be calculated in the following manner: 5.6.1.1 The operator shall calculate the total emissions for all engines operating at a stationary source that will comply with Section 5.2.2.2. The total NOx emissions	**The annual fee option applies to units subject to Table 2.**

		shall be calculated in accordance with Section 5.6.1.3. 5.6.1.2 The total annual fee shall be calculated in accordance with Section 5.6.1.4. These calculations include only the units that have been identified to comply with Section 5.2.2.2. 5.6.1.3 Total Emissions (TE) Calculation E (engine) = A x B x C x D x 2.147 x 10-16 Where: E (engine) = Annual NOx emissions for each unit, in tons/year. A = NOx emission limit for the Permit-to-Operate, in ppmvd corrected to 15% oxygen. B = Annual fuel use (ft3/year) C = Fuel higher heating value (Btu/ft3) – for natural gas use 1,000 Btu/ft3 D = Fuel F-Factor at 60oF (Dscf/MMBtu) – for natural gas use 8,579 Dscf/MMBtu TE = ΣE(engine) Where: ΣE(engine) = Sum of all NOx emissions from all units in the annual fee program, in tons per year. 5.6.1.4 Total Annual Fee Calculation Total Annual Fee = (TE x FR) + Administrative Fee Where: TE = Total Emissions, in tons per year, as calculated in Section 5.6.1.3. FR (Fee Rate) = the cost of NOx reductions, in dollars per ton, as established by District Rule 9510. Under no circumstances shall the cost per ton of NO_X reductions exceed the cost effectiveness threshold for the Carl Moyer Cost Effectiveness, as established by the applicable state law. Administrative Fee = 4% x (TE x FR)	

	5.5 California Reformulated Gasoline shall be used as the fuel for all gasoline-fired, spark-ignited internal combustion engines.	5.7 Sulfur Oxides (SOx) Emission Control Requirements On and after the compliance schedule specified in Section 7.5, operators of non-AO spark-ignited engines and non-AO compression-ignited engines shall comply with one of the following requirements: 5.7.1 Operate the engine exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases; or 5.7.2 Limit gaseous fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or 5.7.3 Use California Reformulated Gasoline for gasoline-fired spark-ignited engines; or 5.7.4 Use California Reformulated Diesel for compression-ignited engines; or 5.7.5 Operate the engine on liquid fuel that contains no more than 15 ppm sulfur, as determined by the test method specified in Section 6.4.6; or 5.7.6 Install and properly operate an emission control system that reduces SO2 emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6.	**The non-SIP version of this rule contains SOx emissions control requirements not found in the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	5.6 Monitoring Requirements A The owner of a non-AO spark-ignited engine subject to the requirements of Section 5.1 or any engine subject to the requirements of Section 8.0 shall comply with the following requirements: 5.6.1 For each engine with a rated brake horsepower of 1,000 hp or greater and which is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition to operate more than 2,000 hours per calendar year, or with an external emission control device, either install, operate, and maintain continuous monitoring equipment for NOx, CO, and oxygen, as identified in Rule 1080 (Stack Monitoring), or install, operate, and maintain APCO-approved alternate monitoring. The monitoring system may be a continuous emissions monitoring system (CEMS), a parametric emissions monitoring system (PEMS), or an alternative monitoring system approved by the APCO. APCO-approved alternate monitoring shall consist of one or more of the following: 5.6.1.1 Periodic NOx and CO emission concentrations, 5.6.1.2 Engine exhaust oxygen concentration, 5.6.1.3 Air-to-fuel ratio, 5.6.1.4 Flow rate of reducing agents added to engine exhaust, 5.6.1.5 Catalyst inlet and exhaust temperature,	5.8 Monitoring Requirements: Non-AO Spark-Ignited Engines and Engines in an AECP (Section 8.0) The operator of a non-AO spark-ignited engine subject to the requirements of Section 5.2 or any engine subject to the requirements of Section 8.0 shall comply with the following requirements: 5.8.1 For each engine with a rated brake horsepower of 1,000 bhp or greater and which is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition to operate more than 2,000 hours per calendar year, or with an external emission control device, either install, operate, and maintain continuous monitoring equipment for NOx, CO, and oxygen, as identified in Rule 1080 (Stack Monitoring), or install, operate, and maintain APCO approved alternate monitoring. The monitoring system may be a continuous emissions monitoring system (CEMS), a parametric emissions monitoring system (PEMS), or an alternative monitoring system approved by the APCO. APCO-approved alternate monitoring shall consist of one or more of the following: 5.8.1.1 Periodic NOx and CO emission concentrations, 5.8.1.2 Engine exhaust oxygen concentration, 5.8.1.3 Air-to-fuel ratio, 5.8.1.4 Flow rate of reducing agents added to engine exhaust,	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	5.6.1.6 Catalyst inlet and exhaust oxygen concentration, 5.6.1.7 Other operational characteristics. 5.6.2 For each engine not subject to Section 5.6.1, monitor operational characteristics recommended by the engine manufacturer or emission control system supplier, and approved by the APCO. 5.6.3 For each engine with an alternative monitoring system, submit to, and receive approval from the APCO, adequate verification of the alternative monitoring system's acceptability. This would include data demonstrating the system's accuracy under typical operating conditions for the specific application and any other information or data deemed necessary in assessing the acceptability of the alternative monitoring system. 5.6.4 For each engine with an APCO approved CEMS, operate the CEMS in compliance with the requirements of 40 Code of Federal Regulations (CFR) Part 51, 40 CFR Parts 60.7 and 60.13 (except subsection h), 40 CFR Appendix B (Performance Specifications), 40 CFR Appendix F (Quality Assurance Procedures), and applicable provisions of Rule 1080 (Stack Monitoring). 5.6.5 For each engine, have the data gathering and retrieval capabilities of an installed monitoring system described in Section 5.6 approved by the APCO. 5.6.6 For each engine, install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions. 5.6.7 For each engine, implement the Inspection and Monitoring (I&M) plan, if any, submitted to and approved by the APCO pursuant to Section 6.5. 5.6.8 For each engine, collect data through the I&M plan in a form approved by the APCO. 5.6.9 For each engine use a portable NOx analyzer to take NOx emission readings to verify compliance with the emission requirements of Section 5.1 or Section 8.0 during each calendar quarter in which a source test is not performed and the engine is operated. All emission readings shall be taken with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt	5.8.1.5 Catalyst inlet and exhaust temperature, 5.8.1.6 Catalyst inlet and exhaust oxygen concentration, or 5.8.1.7 Other operational characteristics. 5.8.2 For each engine not subject to Section 5.8.1, monitor operational characteristics recommended by the engine manufacturer or emission control system supplier, and approved by the APCO. 5.8.3 For each engine with an alternative monitoring system, submit to, and receive approval from the APCO, adequate verification of the alternative monitoring system's acceptability. This would include data demonstrating the system's accuracy under typical operating conditions for the specific application and any other information or data deemed necessary in assessing the acceptability of the alternative monitoring system. 5.8.4 For each engine with an APCO approved CEMS, operate the CEMS in compliance with the requirements of 40 Code of Federal Regulations (CFR) Part 51, 40 CFR Parts 60.7 and 60.13 (except subsection h), 40 CFR Appendix B (Performance Specifications), 40 CFR Appendix F (Quality Assurance Procedures), and applicable provisions of Rule 1080 (Stack Monitoring). 5.8.5 For each engine, have the data gathering and retrieval capabilities of an installed monitoring system described in Section 5.8 approved by the APCO. 5.8.6 For each engine, install and operate a nonresettable elapsed time meter. 5.8.6.1 In lieu of installing a nonresettable elapsed time meter, the operator may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA and is allowed by a Permit-to- Operate or Permit-Exempt Equipment Registration condition. 5.8.6.2 The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions. 5.8.7 For each engine, implement the Inspection and Monitoring (I&M) plan, if any, submitted to and approved by the APCO pursuant to Section 6.5. 5.8.8 For each engine, collect data through the I&M plan in a form approved by the APCO. 5.8.9 For each engine, use a portable NOx analyzer to take NOx emission readings to verify compliance with the emission requirements of Section 5.2 or Section 8.0 during each calendar quarter in which a	

	Equipment Registration. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO. NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive-minute period. 5.6.10 The APCO shall not approve an alternative monitoring system unless it is documented that continued operation within ranges of specified emissions-related performance indicators or operational characteristics provides a reasonable assurance of compliance with applicable emission limits. The operator shall source test over the proposed range of surrogate operating parameters to demonstrate compliance with the applicable emission standards. 5.6.11 For each engine subject to Section 8.0, install and operate a nonresettable fuel meter. In lieu of installing a nonresettable fuel meter, the owner may use an alternative device, method, or technique in determining daily fuel consumption provided that the alternative is approved by the APCO. The owner shall properly maintain, operate, and calibrate the required fuel meter in accordance with the manufacturer's instructions.	source test is not performed and the engine is operated. 5.8.9.1 If an engine is operated less than 120 calendar days per calendar year, take one NOx emission reading during the calendar year in which a source test is not performed and the engine is operated. 5.8.9.2 All emission readings shall be taken with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration. 5.8.9.3 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. 5.8.9.4 All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO. 5.8.9.5 NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutiveminute period. 5.8.10 The APCO shall not approve an alternative monitoring system unless it is documented that continued operation within ranges of specified emissions related performance indicators or operational characteristics provides a reasonable assurance of compliance with applicable emission limits. The operator shall source test over the proposed range of surrogate operating parameters to demonstrate compliance with the applicable emission standards. 5.8.11 For each engine subject to Section 8.0, install and operate a nonresettable fuel meter. 5.8.11.1 In lieu of installing a nonresettable fuel meter, the operator may use an alternative device, method, or technique in determining daily fuel consumption provided that the alternative is approved by the APCO and EPA. 5.8.11.2 The operator shall properly maintain, operate, and calibrate the required fuel meter in accordance with the manufacturer's instructions.	
	5.7 Monitoring Requirements B 5.7.1 The owner of any of the following engines shall comply with the requirements specified	5.9 Monitoring Requirements: All Other Engines 5.9.1 The operator of any of the following engines shall comply with the requirements	**There is no change in the requirements of this section. Therefore, the non-SIP version of the**

	in Section 5.7.2 through Section 5.7.5 below: 5.7.1.1 An AO spark-ignited engine subject to the requirements of Section 5.1, 5.7.1.2 A compression-ignited engine subject to the requirements of Section 5.1, or 5.7.1.3 An engine subject to Section 4.2. 5.7.2 Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier. 5.7.3 Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier. 5.7.4 Install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions. 5.7.5 The owner of an AO spark-ignited engine that has been retro-fitted with a NOx exhaust control that has not been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements, or a compression-ignited engine that has been retro-fitted with a NOx exhaust control shall comply with the following: 5.7.5.1 Use a portable NOx analyzer to take NOx emission readings to demonstrate compliance with the emission requirements of Section 5.1. 5.7.5.2 The owner of a compression-ignited engine that is subject to the limits/standards of Section 5.1.2 Table 2 Category 1.d shall use a portable NOx analyzer to take NOx emission readings at least once every six months that the engine is operated. 5.7.5.3 The owner of any other engine that has been retro-fitted with a NOx exhaust control shall use a portable NOx analyzer to take NOx emission readings at least once every 24 months that the engine is operated. 5.7.5.4 All emission readings shall be taken with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration.	specified in Section 5.9.2 through Section 5.9.5 below: 5.9.1.1 An AO spark-ignited engine subject to the requirements of Section 5.2; 5.9.1.2 A compression-ignited engine subject to the requirements of Section 5.2; or 5.9.1.3 An engine subject to Section 4.2. 5.9.2 Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier. 5.9.3 Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier. 5.9.4 Install and operate a nonresettable elapsed time meter. 5.9.4.1 In lieu of installing a nonresettable elapsed time meter, the operator may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and EPA and is allowed by a Permit-to- Operate or Permit-Exempt Equipment Registration condition. 5.9.4.2 The operator shall properly maintain and operate the nonresettable elapsed time meter or alternative device in accordance with the manufacturer's instructions. 5.9.5 The operator of an AO spark-ignited engine that has been retro-fitted with a NOx exhaust control that has not been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements, or a compression ignited engine that has been retro-fitted with a NOx exhaust control shall comply with the following: 5.9.5.1 Use a portable NOx analyzer to take NOx emission readings to demonstrate compliance with the emission requirements of Section 5.2. 5.9.5.2 The operator of a compression-ignited engine that is subject to the limits/standards of Section 5.2 Table 4 Category 1.d shall use a portable NOx analyzer to take NOx emission readings at least once every six (6) months that the engine is operated. 5.9.5.3 The operator of any other engine that has been retro-fitted with a NOx exhaust control shall use a portable NOx analyzer to take NOx emission readings at least once every 24 months that the engine is operated. 5.9.5.4 All emission readings shall be taken with the engine operating either at	**rule is as stringent as the SIP version of the rule.**

	5.7.5.5 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. 5.7.5.6 All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO. 5.7.5.7 NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive-minute period.	conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration. 5.9.5.5 The portable NOx analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. 5.9.5.6 All NOx emissions readings shall be reported to the APCO in a manner approved by the APCO. 5.9.5.7 NOx emission readings taken pursuant to this section shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings evenly spaced out over the 15 consecutive minute period.	
		5.10 SOx Emissions Monitoring Requirements On and after the compliance schedule specified in Section 7.5, an operator of a non-AO engine shall comply with the following requirements: 5.10.1 An operator of an engine complying with Sections 5.7.2 or 5.7.5 shall perform an annual sulfur fuel analysis in accordance with the test methods in Section 6.4. The operator shall keep the records of the fuel analysis and shall provide it to the District upon request, 5.10.2 An operator of an engine complying with Section 5.7.6 by installing and operating a control device with at least 95% by weight SOx reduction efficiency shall submit for approval by the APCO the proposed the key system operating parameters and frequency of the monitoring and recording not later than July 1, 2013, and 5.10.3 An operator of an engine complying with Section 5.7.6 shall perform an annual source test unless a more frequent sampling and reporting period is included in the Permit-to-Operate. Source tests shall be performed in accordance with the test methods in Section 6.4.	**The non-SIP approved version contains SO_X emissions monitoring requirements not required in the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	5.8 Permit-Exempt Equipment Registration Requirements The owner of an engine used exclusively in agricultural operations shall register such engine pursuant to Rule 2250 (Permit-Exempt Equipment Registration), except for an engine that meets any one of the following conditions: 5.8.1 The engine is required to have a Permit-to-Operate pursuant to California Health and Safety Code Section 42301.16, or 5.8.2 The engine is not required to comply with Section 5.1 of this rule.	5.11 Permit-Exempt Equipment Registration Requirements The operator of an engine used exclusively in agricultural operations shall register such engine pursuant to Rule 2250 (Permit-Exempt Equipment Registration), except for an engine that meets any one of the following conditions: 5.11.1 The engine is required to have a Permit-to-Operate pursuant to California Health and Safety Code Section 42301.16; or 5.11.2 The engine is not required to comply with Section 5.2 of this rule.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
6.0 Administrative Requirements	6.1 Emission Control Plan The owner of an engine subject to the requirements of Section 5.1 or Section 8.0, except for an engine specified in Section 6.1.1, of this rule shall submit to the APCO an APCO-approvable emission control plan of all actions to be taken to satisfy the emission requirements of Section 5.1 and the compliance schedules of Section 7.0. 6.1.1 The requirement to submit an emission control plan shall not apply to an engine specified below: 6.1.1.1 A certified compression-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0, 6.1.1.2 A certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0, 6.1.1.3 An AO spark-ignited engine that has not been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0, 6.1.1.4 An engine subject to Section 4.2, or 6.1.1.5 An engine subject to Section 4.3. 6.1.1.6 An engine with an operating exhaust control system that has been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements. 6.1.2 Such emission control plan shall contain the following information, as applicable for each engine: 6.1.2.1 Permit-to-Operate number, Authority-to-Construct number, or Permit-Exempt Equipment Registration number 6.1.2.2 Engine manufacturer 6.1.2.3 Model designation and engine serial	6.1 Emission Control Plan The operator of an engine subject to the requirements of Section 5.2 of this rule shall submit to the APCO an APCO-approvable emission control plan of all actions to be taken to satisfy the emission requirements of Section 5.2 and the compliance schedules of Section 7.0. If there is no change to the previously-approved emission control plan, the operator shall submit a letter to the District indicating that the previously approved plan is still valid. 6.1.1 The requirement to submit an emission control plan shall apply to the following engines: 6.1.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0; 6.1.1.2 Engines subject to Section 8.0; 6.1.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0; 6.1.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0. 6.1.2 Such emission control plan shall contain the following information, as applicable for each engine: 6.1.2.1 Permit-to-Operate number, Authority-to-Construct number, or Permit-Exempt Equipment Registration number, 6.1.2.2 Engine manufacturer, 6.1.2.3 Model designation and engine serial number, 6.1.2.4 Rated brake horsepower, 6.1.2.5 Type of fuel and type of ignition, 6.1.2.6 Combustion type: rich-burn or lean-	**The non-SIP approved version of this rule includes what engine categories are subject to this section. The SIP approved version has a list of what engines are exempt from this section. However, there is no change in the actual engine categories that are required to meet these section requirements. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	number 6.1.2.4 Rated brake horsepower 6.1.2.5 Type of fuel and type of ignition 6.1.2.6 Combustion type: rich-burn or lean-burn 6.1.2.7 Total hours of operation in the previous one-year period, including typical daily operating schedule 6.1.2.8 Fuel consumption (cubic feet for gas or gallons for liquid) for the previous one-year period 6.1.2.9 Stack modifications to facilitate continuous in-stack monitoring and to facilitate source testing 6.1.2.10 Type of control to be applied, including in-stack monitoring specifications 6.1.2.11 Applicable emission limits 6.1.2.12 Documentation showing existing emissions of NOx, VOC, and CO, and 6.1.2.13 Date that the engine will be in full compliance with Rule 4702. 6.1.3 The emission control plan shall identify the type of emission control device or technique to be applied to each engine and a construction/removal schedule, or shall provide support documentation sufficient to demonstrate that the engine is in compliance with the emission requirements of this rule. 6.1.4 For an engine being permanently removed from service, the emission control plan shall include a letter of intent pursuant to Section 7.2.	burn, 6.1.2.7 Total hours of operation in the previous one-year period, including typical daily operating schedule, 6.1.2.8 Fuel consumption (cubic feet for gas or gallons for liquid) for the previous one-year period, 6.1.2.9 Stack modifications to facilitate continuous in-stack monitoring and to facilitate source testing, 6.1.2.10 Type of control to be applied, including in-stack monitoring specifications, 6.1.2.11 Applicable emission limits, 6.1.2.12 Documentation showing existing emissions of NOx, VOC, and CO, and 6.1.2.13 Date that the engine will be in full compliance with this rule. 6.1.3 The emission control plan shall identify the type of emission control device or technique to be applied to each engine and a construction/removal schedule, or shall provide support documentation sufficient to demonstrate that the engine is in compliance with the emission requirements of this rule. 6.1.4 For an engine being permanently removed from service, the emission control plan shall include a letter of intent pursuant to Section 7.2.	
	6.2 Recordkeeping 6.2.1 Except for engines subject to Section 4.0, the owner of an engine subject to the requirements of Section 5.1 of this rule shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine operating log shall include, on a monthly basis, the following information: 6.2.1.1 Total hours of operation, 6.2.1.2 Type of fuel used, 6.2.1.3 Maintenance or modifications performed, 6.2.1.4 Monitoring data, 6.2.1.5 Compliance source test results, and	6.2 Recordkeeping 6.2.1 The operator of an engine subject to the requirements of Section 5.2 of this rule shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine operating log shall include, on a monthly basis, the following information: 6.2.1.1 Total hours of operation, 6.2.1.2 Type of fuel used, 6.2.1.3 Maintenance or modifications performed, 6.2.1.4 Monitoring data, 6.2.1.5 Compliance source test results, and	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	6.2.1.6 Any other information necessary to demonstrate compliance with this rule. 6.2.1.7 For an engine subject to Section 8.0, the quantity (cubic feet of gas or gallons of liquid) of fuel used on a daily basis. 6.2.2 The data collected pursuant to the requirements of Section 5.6 and Section 5.7 shall be maintained for at least five years, shall be readily available, and made available to the APCO upon request. 6.2.3 An owner claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and provided to the APCO upon request. The records shall include, but are not limited to, the following: 6.2.3.1 Total hours of operation, 6.2.3.2 The type of fuel used, 6.2.3.3 The purpose for operating the engine, 6.2.3.4 For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and 6.2.3.5 Other support documentation necessary to demonstrate claim to the exemption.	6.2.1.6 Any other information necessary to demonstrate compliance with this rule. 6.2.1.7 For an engine subject to Section 8.0, the quantity (cubic feet of gas or gallons of liquid) of fuel used on a daily basis. 6.2.2 The data collected pursuant to the requirements of Section 5.8 and Section 5.9 shall be maintained for at least five years, shall be readily available, and made available to the APCO upon request. 6.2.3 An operator claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and provided to the APCO upon request. The records shall include, but are not limited to, the following: 6.2.3.1 Total hours of operation, 6.2.3.2 The type of fuel used, 6.2.3.3 The purpose for operating the engine, 6.2.3.4 For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and 6.2.3.5 Other support documentation necessary to demonstrate claim to the exemption.	
	6.3 Compliance Testing The owner of an engine subject to the requirements of Section 5.1 or the requirements of Section 8.0, shall comply with the following requirements, except for an engine specified in Section 6.3.1: 6.3.1 The requirements of Section 6.3.2 through Section 6.3.4 shall not apply to any of the following engines: 6.3.1.1 A certified compression-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0. 6.3.1.2 A certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0. 6.3.1.3 An AO spark-ignited engine that has not been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0. 6.3.1.4 An engine subject to Section 4.2. 6.3.1.5 An engine subject to Section 4.3. 6.3.1.6 An engine with an operating exhaust	6.3 Compliance Testing The operator of an engine subject to the requirements of Section 5.2 or the requirements of Section 8.0 shall comply with the following requirements: 6.3.1 The requirements of Section 6.3.2 through Section 6.3.4 shall apply to the following engines: 6.3.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0; 6.3.1.2 Engines subject to Section 8.0; 6.3.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0; 6.3.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0. 6.3.2 Demonstrate compliance with applicable limits, ppmv or percent reduction, in accordance with the test methods in Section 6.4, as specified below: 6.3.2.1 By the applicable date specified in	**The non-SIP approved version of this rule includes what engine categories are subject to this section. The SIP approved version has a list of what engines are exempt from this section. However, there is no change in the actual engine categories that are required to meet this section requirements. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	control system that has been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements. 6.3.2 Demonstrate compliance with applicable limits, ppmv or percent reduction, in accordance with the test methods in Section 6.4, as specified below: 6.3.2.1 By the applicable date specified in Section 5.1.1, Section 5.1.2, Section 7.3, Section 7.4, Section 7.5, or Section 7.6 and at least once every 24 months thereafter, except for an engine subject to Section 6.3.2.2. 6.3.2.2 By the applicable date specified in Section 5.1.1, Section 5.1.2,Section 7.3, Section 7.4, Section 7.5, or Section 7.6 and at least once every 60 months thereafter, for an AO spark-ignited engine that has been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0. 6.3.2.3 A portable NOx analyzer may be used to show initial compliance with the applicable limits/standards in Section 5.1 for AO spark-ignited engines, provided the criteria specified in Sections 6.3.2.3.1 to 6.3.2.3.5 are met, and a source test is conducted in accordance with Section 6.3.2 within 12 months from the required compliance date. 6.3.2.3.1 A minimum of 15 minutes of runtime must be measured with data recorded at a minimum of 15, evenly spaced time intervals. Compliance is to be determined with the arithmetic average of the oxygen-corrected data. 6.3.2.3.2 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer calibration records shall be made available at the District's request. 6.3.2.3.3 The analyzer shall be checked with EPA protocol span gas at the beginning and end of each test day. The results of these checks shall be recorded and copies submitted to the District with each engine test. If the analyzer exhibits more than a 10% deviation from the span check, the instrument must be re-calibrated. Any analysis performed prior to an end-of-day span check failure shall be void. 6.3.2.3.4. The test results of each engine, including span check results, shall be submitted to the District within 30 days of the test date. Test results shall clearly identify the engine tested including owner, location, permit or	Section 5.2, and at least once every 24 months thereafter, except for an engine subject to Section 6.3.2.2 By the applicable date specified in Section 5.2 and at least once every 60 months thereafter, for an AO spark-ignited engine that has been retro-fitted with a catalytic emission control device. 6.3.2.3 A portable NOx analyzer may be used to show initial compliance with the applicable limits/standards in Section 5.2 for AO spark ignited engines, provided the criteria specified in Sections 6.3.2.3.1 to 6.3.2.3.5 are met, and a source test is conducted in accordance with Section 6.3.2 within 12 months from the required compliance date. 6.3.2.3.1 A minimum of 15 minutes of runtime must be measured with data recorded at a minimum of 15, evenly spaced time intervals. Compliance is to be determined with the arithmetic average of the oxygen corrected data; 6.3.2.3.2 The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Analyzer calibration records shall be made available at the District's request; 6.3.2.3.3 The analyzer shall be checked with EPA protocol span gas at the beginning and end of each test day. The results of these checks shall be recorded and copies submitted to the District with each engine test. If the analyzer exhibits more than a 10% deviation from the span check, the instrument must be recalibrated. Any analysis performed prior to an end-of-day span check failure shall be void; 6.3.2.3.4 The test results of each engine, including span check results, shall be submitted to the District within 30 days of the test date. Test results shall clearly identify the engine tested including operator, location, permit or registration number, manufacturer, model, and serial number; and 6.3.2.3.5 The analyzer utilized for each check shall be clearly identified in the material submitted with the test results. Identification shall include manufacturer and serial number of the analyzer used, and the last calibration date. 6.3.3 Conduct emissions source testing with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration. For emissions source testing performed pursuant to Section 6.3.2 for the	

	registration number, manufacturer, model, and serial number. 6.3.2.3.5. The analyzer utilized for each check shall be clearly identified in the material submitted with the test results. Identification shall include manufacturer and serial number of the analyzer used, and the last calibration date. 6.3.3 Conduct emissions source testing with the engine operating either at conditions representative of normal operations or conditions specified in the Permit-to-Operate or Permit-Exempt Equipment Registration. For emissions source testing performed pursuant to Section 6.3.2 for the purpose of determining compliance with an applicable standard or numerical limitation, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15 percent oxygen. For engines that comply with a percent reduction limit in Table 1, the percent reduction of NOx emissions shall also be reported. 6.3.4 In addition to other information, the source test protocol shall describe which critical parameters will be measured and how the appropriate range for these parameters shall be established. The range for these parameters shall be incorporated into the I&M plan. 6.3.5 Engines that are limited by Permit-to-Operate or Permit-Exempt Equipment Registration condition to be fueled exclusively with PUC quality natural gas shall not be subject to the reoccurring source test requirements of Section 6.3.2 for VOC emissions.	purpose of determining compliance with an applicable standard or numerical limitation, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15 percent oxygen. For engines that comply with a percent reduction limit, the percent reduction of NO_X emissions shall also be reported. 6.3.4 In addition to other information, the source test protocol shall describe which critical parameters will be measured and how the appropriate range for these parameters shall be established. The range for these parameters shall be incorporated into the I&M plan. 6.3.5 Engines that are limited by Permit-to-Operate or Permit-Exempt Equipment Registration condition to be fueled exclusively with PUC quality natural gas shall not be subject to the reoccurring source test requirements of Section 6.3.2 for VOC emissions.	
	6.3.6 Representative Testing For spark-ignited engines, in lieu of compliance with the applicable requirements of Section 6.3.2, compliance with the applicable emission limits in Section 5.1 shall be demonstrated by submittal of annual emission test results, within 30 days of the test date, to the District, from a unit or units that represents a specified group of units, provided all of the following are requirements are satisfied: 6.3.6.1 The units are located at the same stationary source; 6.3.6.2 The units were produced by the same manufacturer, have the same model number or other manufacturer's designation in common, and have the same rated capacity and operating specifications;	6.3.6 Representative Testing For spark-ignited engines, in lieu of compliance with the applicable requirements of Section 6.3.2, compliance with the applicable emission limits in Section 5.2 shall be demonstrated by submittal of annual emission test results, within 30 days of the test date, to the District, from a unit or units that represents a specified group of units, provided all of the following requirements are satisfied: 6.3.6.1 The units are located at the same stationary source; 6.3.6.2 The units were produced by the same manufacturer, have the same model number or other manufacturer's designation in common, and have the same rated	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	6.3.6.3 The units are operated and maintained in a similar manner; and 6.3.6.4 At least 20% of the total number of units are tested during each annual test cycle. 6.3.6.5 The District, based on documentation submitted by the stationary source: 6.3.6.5.1 Determines that the margin of compliance for the identical units tested is significant and can be maintained on an on-going basis; or 6.3.6.5.2 Determines based on a review of sufficient emissions data that, though the margin of compliance is not substantial, other factors allow for the determination that the variability of emissions for identical tested units is low enough for confidence that the untested unit will be in compliance. These factors may include, but are not limited to, the following: 6.3.6.5.2.1 Historical records at the tested unit 6.3.6.5.2.2 Fuel characteristics yielding low variability and therefore assurance that emissions will be constant and below allowable levels; 6.3.6.5.2.3 Statistical analysis of a robust emissions data set demonstrate sufficiently low variability to convey assurance that the margin of compliance, though small, is reliable. 6.3.6.6 Should any of the representative units exceed the required emission limits, or if the District notifies the operator that the criteria in Sections 6.3.6.1 through 6.3.6.5 have not been fulfilled, each of the units in the group shall individually demonstrate compliance by emissions testing. Failure to complete emissions testing within 90 days of the failed test shall result in the untested units being in violation of this rule. After compliance with the requirements of Section 6.3.6.6 has been demonstrated, subsequent source testing shall be performed pursuant to Sections 6.3.2 or 6.3.6.	capacity and operating specifications; 6.3.6.3 The units are operated and maintained in a similar manner; and 6.3.6.4 At least 20% of the total number of units are tested during each annual test cycle. 6.3.6.5 The District, based on documentation submitted by the stationary source: 6.3.6.5.1 Determines that the margin of compliance for the identical units tested is significant and can be maintained on an on-going basis; or 6.3.6.5.2 Determines based on a review of sufficient emissions data that, though the margin of compliance is not substantial, other factors allow for the determination that the variability of emissions for identical tested units is low enough for confidence that the untested unit will be in compliance. These factors may include, but are not limited to, the following: 6.3.6.5.2.1 Historical records at the tested unit showing consistent invariant load; 6.3.6.5.2.2 Fuel characteristics yielding low variability and therefore assurance that emissions will be constant and below allowable levels; 6.3.6.5.2.3 Statistical analysis of a robust emissions data set demonstrating sufficiently low variability to convey assurance that the margin of compliance, though small, is reliable. 6.3.6.6 Should any of the representative units exceed the required emission limits, or if the District notifies the operator that the criteria in Sections 6.3.6.1 through 6.3.6.5 have not been fulfilled, each of the units in the group shall individually demonstrate compliance by emissions testing. Failure to complete emissions testing within 90 days of the failed test shall result in the untested units being in violation of this rule. After compliance with the requirements of this section has been demonstrated, subsequent source testing shall be performed pursuant to Sections 6.3.2 or 6.3.6.	
	6.4 Test Methods Compliance with the requirements of Section 5.0 shall be determined, as required, in accordance with the following test procedures or any other method approved by EPA and the APCO: 6.4.1 Oxides of nitrogen - EPA Method 7E, or ARB Method 100. 6.4.2 Carbon monoxide - EPA Method 10, or ARB Method 100.	6.4 Test Methods Compliance with the requirements of Section 5.2 shall be determined, as required, in accordance with the following test procedures or any other method approved by EPA and the APCO: 6.4.1 Oxides of nitrogen - EPA Method 7E, or ARB Method 100. 6.4.2 Carbon monoxide - EPA Method 10, or ARB Method 100.	**The Non-SIP approved version of this rule added SO_X test methods to the SIP approved version of this rule. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	6.4.3 Stack gas oxygen - EPA Method 3 or 3A, or ARB Method 100. 6.4.4 Volatile organic compounds - EPA Method 25A or 25B, or ARB Method 100. 6.4.5 Operating horsepower determination - any method approved by EPA and the APCO.	6.4.3 Stack gas oxygen - EPA Method 3 or 3A, or ARB Method 100. 6.4.4 Volatile organic compounds - EPA Method 25A or 25B, or ARB Method 100. Methane and ethane, which are exempt compounds, shall be excluded from the result of the test. 6.4.5 Operating horsepower determination - any method approved by EPA and the APCO. 6.4.6 SOx Test Methods 6.4.6.1 Oxides of sulfur – EPA Method 6C, EPA Method 8, or ARB Method 100. 6.4.6.2 Determination of total sulfur as hydrogen sulfide (H2S) content – EPA Method 11 or EPA Method 15, as appropriate. 6.4.6.3 Sulfur content of liquid fuel – American Society for Testing and Materials (ASTM) D 6920-03 or ASTM D 5453-99. 6.4.6.4 The SOx emission control system efficiency shall be determined using the following: % Control Efficiency = [(CSO2, inlet – CSO2, outlet) / CSO2, inlet] X 100 Where: CSO2, inlet = concentration of SOx (expressed as SO2) at the inlet side of the SOx emission control system, in lb/Dscf CSO2, outlet = concentration of SOx (expressed as SO2) at the outlet side of the SOx emission control system, in lb/Dscf 6.4.7 The Higher Heating Value (hhv) of the fuel shall be determined by one of the following test methods: 6.4.7.1 ASTM D 240-02 or ASTM D 3282-88 for liquid hydrocarbon fuels. 6.4.7.2 ASTM D 1826-94 or ASTM 1945-96 in conjunction with ASTM D 3588-89 for gaseous fuel.	

	6.5 Inspection and Monitoring (I&M) Plan The owner of an engine that is subject to the requirements of Section 5.1 or the requirements of Section 8.0, except for an engine specified in Section 6.5.1, shall submit to the APCO for approval, an I&M plan that specifies all actions to be taken to satisfy the following requirements and the requirements of Section 5.6. The actions to be identified in the I&M plan shall include, but are not limited to, the information specified below: 6.5.1 The requirements of Section 6.5.2 through Section 6.5.9 shall not apply to any of the following engines: 6.5.1.1 A certified compression-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0. 6.5.1.2 A certified spark-ignited engine that has not been retro-fitted with an exhaust control and is not subject to the requirements of Section 8.0. 6.5.1.3 An AO spark-ignited engine that has not been retro-fitted with a catalytic emission control device and is not subject to the requirements of Section 8.0. 6.5.1.4 An engine subject to Section 4.2. 6.5.1.5 An engine subject to Section 4.3. 6.5.1.6 An engine with an operating exhaust control system that has been certified in accordance with Section 9.0 Exhaust Control System Certification Requirements. 6.5.2 Procedures requiring the owner or operator to establish ranges for control equipment parameters, engine operating parameters, and engine exhaust oxygen concentrations that source testing has shown result in pollutant concentrations within the rule limits. 6.5.3 Procedures for monthly inspections as approved by the APCO. The applicable control equipment parameters and engine operating parameters will be inspected and monitored monthly in conformance with a regular inspection schedule listed in the I&M plan. 6.5.4 Procedures for the corrective actions on the noncompliant parameter(s) that the owner or operator will take when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust NOx, CO, VOC, or oxygen concentrations. 6.5.5 Procedures for the owner or operator to notify the APCO when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust	6.5 Inspection and Monitoring (I&M) Plan The operator of an engine that is subject to the requirements of Section 5.2 or the requirements of Section 8.0 shall submit to the APCO for approval, an I&M plan that specifies all actions to be taken to satisfy the following requirements and the requirements of Section 5.8. The actions to be identified in the I&M plan shall include, but are not limited to, the information specified below. If there is no change to the previously approved I&M plan, the operator shall submit a letter to the District indicating that previously approved plan is still valid. 6.5.1 The requirements of Section 6.5.2 through Section 6.5.9 shall apply to the following engines: 6.5.1.1 Engines that have been retrofitted with an exhaust control device, except those certified per Section 9.0; 6.5.1.2 Engines subject to Section 8.0; 6.5.1.3 An AO spark-ignited engine that is subject to the requirements of Section 8.0. 6.5.1.4 An AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0. 6.5.2 Procedures requiring the operator to establish ranges for control equipment parameters, engine operating parameters, and engine exhaust oxygen concentrations that source testing has shown result in pollutant concentrations within the rule limits. 6.5.3 Procedures for monthly inspections as approved by the APCO. The applicable control equipment parameters and engine operating parameters will be inspected and monitored monthly in conformance with a regular inspection schedule listed in the I&M plan. 6.5.4 Procedures for the corrective actions on the noncompliant parameter(s) that the operator will take when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust NOx, CO, VOC, or oxygen concentrations. 6.5.5 Procedures for the operator to notify the APCO when an engine is found to be operating outside the acceptable range for control equipment parameters, engine operating parameters, and engine exhaust NOx, CO, VOC, or oxygen concentrations. 6.5.6 Procedures for preventive and corrective maintenance performed for the purpose of maintaining an engine in proper operating	**The non-SIP approved version of this rule includes what engine categories are subject to this section. The SIP approved version has a list of what engines are exempt from this section. However, there is no change in the actual engine categories that are required to meet these section requirements. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	NOx, CO, VOC, or oxygen concentrations. 6.5.6 Procedures for preventive and corrective maintenance performed for the purpose of maintaining an engine in proper operating condition. 6.5.7 Procedures and a schedule for using a portable NOx analyzer to take NOx emission readings pursuant to Section 5.6.9. 6.5.8 Procedures for collecting and recording required data and other information in a form approved by the APCO including, but not limited to, data collected through the I&M plan and the monitoring systems described in Sections 5.6.1 and 5.6.2. Data collected through the I&M plan shall have retrieval capabilities as approved by the APCO. 6.5.9 Procedures for revising the I&M plan. The I&M plan shall be updated to reflect any change in operation. The I&M plan shall be updated prior to any planned change in operation. An engine owner that changes significant I&M plan elements must notify the District no later than seven days after the change and must submit an updated I&M plan to the APCO no later than 14 days after the change for approval. The date and time of the change to the I&M plan shall be recorded in the engine operating log. For new engines and modifications to existing engines, the I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit-to-Operate or Permit-Exempt Equipment Registration. The owner of an engine may request a change to the I&M plan at any time.	condition. 6.5.7 Procedures and a schedule for using a portable NOx analyzer to take NO_X emission readings pursuant to Section 5.8.9. 6.5.8 Procedures for collecting and recording required data and other information in a form approved by the APCO including, but not limited to, data collected through the I&M plan and the monitoring systems described in Sections 5.8.1 and 5.8.2. Data collected through the I&M plan shall have retrieval capabilities as approved by the APCO. 6.5.9 Procedures for revising the I&M plan. The I&M plan shall be updated to reflect any change in operation. The I&M plan shall be updated prior to any planned change in operation. An engine operator that changes significant I&M plan elements must notify the District no later than seven days after the change and must submit an updated I&M plan to the APCO no later than 14 days after the change for approval. The date and time of the change to the I&M plan shall be recorded in the engine operating log. For new engines and modifications to existing engines, the I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit-to-Operate or Permit-Exempt Equipment Registration. The operator of an engine may request a change to the I&M plan at any time.	
7.0 Compliance Schedules	7.1 Loss of Exemption The owner of an engine which becomes subject to the emission limits/standards of this rule through loss of exemption shall not operate the subject engine, except as required for obtaining a new or modified Permit-to-Operate or Permit-Exempt Equipment Registration for the engine, until the owner demonstrates that the subject engine is in full compliance with the requirements of this rule.	7.1 Loss of Exemption The operator of an engine which becomes subject to the emission limits/standards of this rule through loss of exemption shall not operate the subject engine, except as required for obtaining a new or modified Permit-to-Operate or Permit-Exempt Equipment Registration for the engine, until the operator demonstrates that the subject engine is in full compliance with the requirements of this rule.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	7.2 Permanent Removal of an Engine The owner of an engine who elects to permanently remove the engine from service shall comply with all of the following conditions: 7.2.1 Comply with all applicable requirements of this rule until the engine is permanently removed from service; 7.2.2 Submit a letter to the APCO no later than 14 days before the engine is permanently removed from service, stating the intent to	7.2 Permanent Removal of an Engine The operator of an engine who elects to permanently remove the engine from service shall comply with all of the following conditions: 7.2.1 Comply with all applicable requirements of this rule until the engine is permanently removed from service; 7.2.2 Submit a letter to the APCO no later than 14 days before the engine is permanently	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	permanently remove the engine from service. The engine removal letter can be submitted with the emission control plan, if any; and 7.2.3 Permanently remove the engine from service and officially surrender the Permit-to-Operate or Permit-Exempt Equipment Registration, if any, to the APCO no later than 30 days after the engine is permanently removed from service.	removed from service, stating the intent to permanently remove the engine from service. The engine removal letter can be submitted with the emission control plan, if any; and 7.2.3 Permanently remove the engine from service and officially surrender the Permit-to-Operate or Permit-Exempt Equipment Registration, if any, to the APCO no later than 30 days after the engine is permanently removed from	
	7.3 Compliance Schedule for an AO Compression-Ignited Engine 7.3.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, Permit-Exempt Equipment Registration Application and Authority-to-Construct for an AO Compression-Ignited Engine 7.3.1.1 The owner of an engine that is subject to Section 4.2 or Section 4.3 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than January 1, 2006. 7.3.1.2 The owner of an engine that is subject to Section 5.1 and that is required to submit an Authority-to-Construct application in order to comply with the requirements of Rule 4702, shall submit the Authority-to-Construct application, and any required Emission Control Plan or I&M Plan, no later than six months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702. 7.3.1.3 The owner of an engine that is subject to Section 5.1 and that is required to submit a Permit-Exempt Equipment Registration application in order to comply with the requirements of Rule 4702, shall submit the Permit-Exempt Equipment Registration application, and any required Emission Control Plan or I&M Plan, no later than three months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702. 7.3.2 Compliance Schedule - Monitoring and Recordkeeping for an AO Compression-Ignited Engine Subject to Section 5.1 and Section 5.7 On and after June 1, 2006, the owner of an engine that is subject to Section 5.1 and Section 5.7 of Rule 4702 shall be in compliance with the requirements of Section 5.7, Section 6.2.1.1, and Section 6.2.1.2. 7.3.3 Compliance Schedule - General for an AO Compression-Ignited Engine	7.3 AO Compression-Ignited Engine 7.3.1 The operator of an AO compression-ignited engine that is subject to Section 5.2 and that is required to submit an Authority-to-Construct application in order to comply with the requirements of this rule, shall submit the Authority-to-Construct application, and any required Emission Control Plan or I&M Plan, no later than six months before the engine is required to be in compliance with the requirements of Section 5.2. 7.3.2 The operator of an AO compression-ignited engine that is subject to Section 5.2 and that is required to submit a Permit-Exempt Equipment Registration application in order to comply with the requirements of Rule 4702, shall submit the Permit-Exempt Equipment Registration application, and any required Emission Control Plan or I&M Plan, no later than three months before the engine is required to be in compliance with the requirements of Section 5.2. 7.3.3 Unless otherwise specified, the operator of an engine that is subject to the requirements of Section 5.2 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates in Table 4.	**The Non-SIP approved version of this rule only includes current requirements from the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	7.3.3.1 On and after January 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.2 or Section 4.3 of Rule 4702 shall be in full compliance with Rule 4702. 7.3.3.2 Unless otherwise specified, the owner of an engine that is subject to the requirements of Section 5.1 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates pursuant to Section 5.1.2.		
	7.4 Compliance Schedule for an AO Spark-Ignited Engine 7.4.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, Permit-Exempt Equipment Registration Application and Authority-to-Construct for an AO Spark-Ignited Engine 7.4.1.1 The owner of an engine that is subject to Section 4.2 or Section 4.3 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than January 1, 2006. 7.4.1.2 The owner of an engine that is subject to Section 5.1 and that is required to submit an Authority-to-Construct application in order to comply with the requirements of Rule 4702, shall submit the Authority-to-Construct application, and any required Emission Control Plan or I&M Plan, by June 1, 2006, or six months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702, whichever is later. 7.4.1.3 The owner of an engine that is subject to Section 5.1 and that is required to submit a Permit-Exempt Equipment Registration application in order to comply with the requirements of Rule 4702, shall submit the Permit-Exempt Equipment Registration application, and any required Emission Control Plan or I&M Plan by January 1, 2007, or three months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702, whichever is later. 7.4.2 Compliance Schedule - Monitoring and Recordkeeping for an AO Spark-Ignited Engine Subject to Section 5.1 and Section 5.7 On and after June 1, 2006, the owner of an engine that is subject to Section 5.1 and Section 5.7 of Rule 4702 shall be in compliance with the requirements of Section 5.7.3 through Section		**AO speak-ignited engines are were required to be in full compliance with this rule by 1/1/10. The requirements from this section of the rule are obsolete and not required on the Non-SIP approved version of the rule. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	5.7.5, Section 6.2.1.1, and Section 6.2.1.2. 7.4.3 Compliance Schedule - General for an AO Spark-Ignited Engine 7.4.3.1 On and after June 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.2 or Section 4.3 of Rule 4702 shall be in full compliance with Rule 4702. 7.4.3.2 Unless otherwise specified, the owner of an engine that is subject to the requirements of Section 5.1 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates pursuant to Section 5.1.1.		
	7.5 Compliance Schedule for a Non-AO Compression-Ignited Engine 7.5.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, and Authority-to-Construct for a Non-AO Compression-Ignited Engine 7.5.1.1 The owner of an engine that is subject to Section 4.2 or Section 4.3 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than June 1, 2006. 7.5.1.2 The owner of an engine that is subject to Section 5.1 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) by June 1, 2006 or six months before the engine is required to be in compliance with the requirements of Section 5.1 of Rule 4702, whichever is later. 7.5.2 Compliance Schedule - General for a Non-AO Compression-Ignited Engine 7.5.2.1 On and after June 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.1, Section 4.2, or Section 4.3 of Rule 4702 shall be in full compliance with Rule 4702. 7.5.2.2 Unless otherwise specified, the owner of an engine that is subject to the requirements of Section 5.1 of Rule 4702 shall be in full compliance with Rule 4702 by the indicated dates pursuant to Section 5.1.2. 7.5.2.3 The owner of an engine that is subject to the requirements of Section 4.0 or Section 5.0 of Rule 4701 (Internal Combustion Engines – Phase 1) shall no longer be subject to the requirements of Rule 4701 pursuant to the following requirements: 7.5.2.3.1 For an engine that is subject to the requirements of Section 4.1, Section 4.2, or	7.4 Non-AO Compression-Ignited Engine 7.4.1 The operator of a non-AO compression-ignited engine that is subject to Section 5.2 and that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with rule requirements, shall submit such document(s) no later than six months before the engine is required to be in compliance with the requirements of Section 5.2. 7.4.2 Unless otherwise specified, the operator of an engine that is subject to the requirements of Section 5.2 shall be in full compliance with Rule 4702 by the indicated dates in Table 4.	**The Non-SIP approved version of this rule only includes current requirements from the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	Section 4.3 of Rule 4702, the requirements of Rule 4701 shall not apply effective on the date that such engine is required to be in full compliance with Rule 4702, or 7.5.2.3.2 For an engine that is subject to the requirements of Section 5.1 of Rule 4702, the requirements of Rule 4701 shall not apply effective on the date that such engine is required to be in full compliance with Rule 4702.		
	7.6 Compliance Schedule for a Non-AO Spark-Ignited Engine 7.6.1 Compliance Schedule - Submission of Emission Control Plan, I&M Plan, and Authority-to-Construct for a Non-AO Spark-Ignited Engine Effective on and after June 16, 2005, the owner of an engine that is required to submit an Emission Control Plan, an I&M Plan, or an Authority-to-Construct in order to comply with the requirements of Rule 4702, shall submit such document(s) no later than six months before the engine is required to be in full compliance with Rule 4702. 7.6.2 Compliance Schedule – Emission Limits for a Non-AO Spark-Ignited Engine The owner of a non-AO spark-ignited engine subject to the requirements of Rule 4702 shall not operate the engine unless the owner demonstrates and maintains the engine in compliance with the applicable requirements of Rule 4702 by the indicated dates below. Compliance Schedule 1 – Non-AO Spark-Ignited Engine For the purposes of Section 7.6, the total number of non-AO spark-ignited engines at a stationary source on a specified date includes those non-AO spark-ignited engines subject to Rule 4702 pursuant to Section 2.0 and excludes any engines exempt from Rule 4702 pursuant to Section 4.1 on the specified date. 7.6.3 Compliance Schedule - General for a Non-AO Spark-Ignited Engine 7.6.3.1 On and after January 1, 2006, unless otherwise specified, the owner of an engine that is subject to the requirements of Section 4.1 of Rule 4702 shall be in full compliance with Rule 4702.	Note: This section refers to Table 5. Table 5 can be found as an attachment to this document. 7.5 Non-AO Spark-Ignited Engine 7.5.1 An operator with non-AO spark-ignited engines at a stationary source subject to Table 2 or Section 8.0 emission limits, SOx control requirements of Section 5.7, and the SOx monitoring requirements of Section 5.10 shall comply with the schedule specified in Table 5. 7.5.2 As shown in Table 5, the column labeled: 7.5.2.1 “Emission Control Plan” identifies the date by which the operator shall submit an emission control plan pursuant to the applicable provisions of Section 6.1. The emission control plan shall identify all the Non-AO spark-ignited engines subject to Table 2 emission limits, SOx control and monitoring requirements. The emission control plan shall identify all the steps to be taken to comply with this rule. If there is no change to the previously approved emission control plan, the operator does not need to submit a new emission control plan. However, the operator shall submit a letter to the District indicating that previously approved plan is still valid. 7.5.2.2 “Authority to Construct and Inspection and Maintenance Plan” identifies the date by which the operator shall submit an Authority to Construct (if needed) and an Inspection and Monitoring Plan as specified in the applicable provisions of Section 6.5 for each engine subject to Table 2 emission limits, SOx control and monitoring requirements. If there is no change to the previously approved I&M plan, the operator does not need to submit a new I&M Plan. However, the operator shall submit a letter to the District indicating that previously approved I&M plan is still valid. 7.5.2.3 “Full Compliance” identifies the date by which the operator shall demonstrate that each unit is in compliance with Table 2	**The Non-SIP approved version of this rule only includes current requirements from the SIP approved version. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	7.6.3.2 Unless otherwise specified, the owner of an engine subject to the requirements of Rule 4702 shall be in full compliance with Rule 4702 by the applicable compliance date pursuant to Section 7.6.2. 7.6.3.3 The owner of an engine that is subject to the requirements of Rule 4701 shall no longer be subject to the requirements of Rule 4701 pursuant to the following requirements: 7.6.3.3.1 For an engine that is subject to the requirements of Section 4.1 of Rule 4702, the requirements of Rule 4701 shall not apply effective on and after January 1, 2006, or 7.6.3.3.2 For an engine that is subject to the requirements of Section 4.2, Section 4.3, or Section 5.1 of Rule 4702, the requirements of Rule 4701 shall not apply effective on the date that such engine is required to be in full compliance with Rule 4702.	emission limits, SOx control and monitoring requirements.	
		7.6 Operator of Non-AO Spark-Ignited Engine Who Elects to Pay Fees In lieu of complying with Table 2 NOx emission limits, the operator of a non-AO spark-ignited engine who elects to pay annual fees under Section 5.2.2.2 and Section 5.6 shall comply with the following requirements: 7.6.1 By the date specified in Table 5, submit an Emission Control Plan which includes the following information: 7.6.1.1 Number of engines at a stationary source that will comply under Section 5.2.2.2, 7.6.1.2 Location of each engine, 7.6.1.3 Engine manufacturer, model designation, engine serial number, and Permit-to-Operate number, and 7.6.1.4 Each engine's rated brake horsepower, fuel type, and type of ignition. 7.6.2 The total annual fees shall be paid to the District in the following manner: 7.6.2.1 Payment shall be paid no later than June 30 of each year, for the emissions of the previous calendar year, 7.6.2.2 The first payment is due to the District no later than June 30 of the year in which full compliance is required for the specified percent of engines at a stationary as specified in Table 5 that the operator has opted to pay the annual fees,	**This section was added to address a new unit category. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

		7.6.2.3 Should June 30 fall on a day when the District is closed, the payment shall be made by the next District working day after June 30, and 7.6.2.4 Payments shall continue annually until the engine either is permanently removed from use in the San Joaquin Valley Air Basin and the Permit-to-Operate is surrendered or the operator demonstrates compliance with the applicable Table 2 emission limits. 7.6.2.5 The emissions fee for units that operate for less than the full calendar year before demonstrating compliance under Section 5.2, shall be based on the actual fuel used during the portion of the calendar year prior to demonstrating compliance or removing the unit from operation within the San Joaquin Valley Air Basin.	
8.0 Alternative Emission Control Plan (AECP)	An owner may comply with the NOx emission requirements of Section 5.1 for a group of engines by meeting the requirements below. An owner that is subject to the requirements below shall also comply with all the applicable requirements of Sections 5.0, 6.0, and 7.0. An engine that is not subject to Section 5.1 is not eligible for inclusion in an AECP. 8.1 During any 7 (seven) consecutive calendar day period, the owner shall operate all engines in the AECP to achieve an actual aggregate NOx emission level that is not greater than 90 percent of the NOx emissions that would be obtained by controlling the engines to comply individually with the NOx limits in Section 5.1. The owner shall operate engines in the AECP such that $AE_{Actual} <= 0.90 (AE_{Limit})$ and shall notify the APCO within 24 hours of a violation of this section. 8.1.1 The actual aggregate NOx emissions (AE_{Actual}) is the sum of the actual NOX emissions, over a 7 (seven) consecutive calendar day period, from all engines in the AECP which were actually operated during that period. AE_{Actual} shall be calculated as follows: $$AE_{Actual} = \sum_i (EF_i)(F_i)(k_i)$$ where: i identifies each engine in the AECP. EF_i is the NOx emission factor of the engine established pursuant to Section 8.2 and approved by the APCO. F_i is the actual total fuel used by the engine	An operator may comply with the NOx emission requirements of Section 5.2 for a group of engines by meeting the requirements below. An operator that is subject to the requirements below shall also comply with all the applicable requirements of Sections 5.0, 6.0, and 7.0. Only engines subject to Section 5.2 are eligible for inclusion in an AECP. 8.1 During any seven (7) consecutive calendar day period, the operator shall operate all engines in the AECP to achieve an actual aggregate NOx emission level that is not greater than 90 percent of the NOx emissions that would be obtained by controlling the engines to comply individually with the NOx limits in Section 5.2. The operator shall operate engines in the AECP such that $AE_{Actual} \leq 0.90 (AE_{Limit})$ and shall notify the APCO within 24 hours of any violation of this section. 8.1.1 The actual aggregate NOx emissions (AE_{Actual}) is the sum of the actual NO_X emissions, over a seven (7) consecutive calendar day period, from all engines in the AECP which were actually operated during that period. AE_{Actual} shall be calculated as follows: $$AE_{Actual} = \sum_i (EF_i)(F_i)(k_i)$$ where: i identifies each engine in the AECP. EF_i is the NOx emission factor of the engine established pursuant to Section 8.2 and approved by the APCO. F_i is the actual total fuel used by the engine	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	during the 7 (seven) consecutive calendar day period. k_i is a constant used to convert an engine's fuel use and NOx emission factor to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO. 8.1.2 The estimated aggregate NOx emissions limit (AE_{Limit}) is the sum of the NOx emissions, over a 7 (seven) consecutive calendar day period, for the same engines in the AECP which were actually operated during the same period as considered in Section 8.1.1, calculated with the NOx limits of Section 5.1 and the actual fuel usage during that 7 (seven) consecutive calendar day period. AE_{Limit} shall be calculated as follows: $$AE_{Limit} = \sum_i (EL_i)(F_i)(k_i)$$ where: i identifies each engine in the AECP. EL_i is the NOx emission limit from Section 5.1 for each engine. F_i is the actual total fuel used by the engine during the 7 (seven) consecutive calendar day period. k_i is a constant used to convert an engine's fuel use and NOx emission limit to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO. 8.1.3 Only engines in the AECP which were operated during the 7 (seven) consecutive calendar day period shall be included in the calculations of AE_{Limit} and AE_{Actual}. 8.1.4 The owner shall, at least one time each day the AECP is used, calculate and record the actual aggregate NOx emissions (AE_{Actual}) and the aggregate NOx emission limit (AE_{Limit}) for the preceding 7 (seven) consecutive calendar day period.	during the 7 (seven) consecutive calendar day period. k_i is a constant used to convert an engine's fuel use and NOx emission factor to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO. 8.1.2 The estimated aggregate NOx emissions limit (AE_{Limit}) is the sum of the NOx emissions, over a seven (7) consecutive calendar day period, for the same engines in the AECP which were actually operated during the same period as considered in Section 8.1.1, calculated with the NOx limits of Section 5.2 and the actual fuel usage during that seven (7) consecutive calendar day period. AE_{Limit} shall be calculated as follows: $$AE_{Limit} = \sum_i (EL_i)(F_i)(k_i)$$ where: i = identifies each engine in the AECP. EL_i = the NOx emission limit from Section 5.2 for each engine. F_i = the actual total fuel used by the engine during the seven (7) consecutive calendar day period. k_i = a constant used to convert an engine's fuel use and NOx emission limit to the amount of NOx emitted. k_i is dependent on the engine and the pollutant emitted. Calculation of k_i shall be accomplished using 40 CFR Part 60, Appendix A, Method 19, or an equivalent method approved by EPA, ARB and the APCO. 8.1.3 Only engines in the AECP which were operated during the seven (7) consecutive calendar day period shall be included in the calculations of AE_{Limit} and AE_{Actual}. 8.1.4 The operator shall, at least one time each day the AECP is used, calculate and record the actual aggregate NOx emissions (AE_{Actual}) and the aggregate NOx emission limit (AE_{Limit}) for the preceding seven (7) consecutive calendar day period.	
	8.2 The owner shall establish a NOx emission factor limit for each engine. The established NOx emission factor of an engine shall be no less than the NOx emission factor of the engine from the most recent source test conducted pursuant to Section 6.3 and approved by the APCO. The owner shall not operate an AECP engine in such a manner that NOx emissions exceed the established NOx emission factor of the engine.	8.2 The operator shall establish a NOx emission factor limit for each engine. The established NOx emission factor of an engine shall be no less than the NOx emission factor of the engine from the most recent source test conducted pursuant to Section 6.3 and approved by the APCO. The operator shall not operate an AECP engine in such a manner that NOx emissions exceed the established NOx emission factor of the engine.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	8.3 The owner shall submit the AECP to the APCO at least 18 months before compliance with the emission limits in Section 5.1 is required. The AECP shall: 8.3.1 Not be implemented prior to APCO approval. 8.3.2 Be enforceable on a daily basis by the District. 8.3.3 Contain any information necessary to determine eligibility of the engines for alternative emission control, including, but not limited to: 8.3.3.1 A list of engines subject to the AECP. All engines in an AECP shall be under the operational control of a single owner and shall be located at a single stationary source. 8.3.3.2 The NOx emission factor established by the engine owner for each engine pursuant to Section 8.2. 8.3.3.3 The estimated aggregate NOx emissions calculated according to Section 8.1.2. 8.3.4 Present the methodology for determining equivalency of actual NOx emissions under the proposed AECP as compared to the estimated NOx emissions allowed by this rule. 8.3.5 Detail the method of recording and verifying daily compliance with the AECP. 8.3.6 Demonstrate to the satisfaction of the APCO that the difference between the NOx emission limits of this rule and any lower actual NOx emissions will not be used to increase emissions from the same or another source. 8.3.7 Demonstrate that the engines subject to the requirements of Section 5.1 are in compliance with or on an approved schedule for compliance with all applicable District rules.	8.3 The operator shall submit the AECP to the APCO at least 18 months before compliance with the emission limits in section 5.2 is required. The AECP shall: 8.3.1 Not be implemented prior to APCO approval. 8.3.2 Be enforceable on a daily basis by the District. 8.3.3 Contain any information necessary to determine eligibility of the engines for alternative emission control, including, but not limited to: 8.3.3.1 A list of engines subject to the AECP. All engines in an AECP shall be under the operational control of a single operator and shall be located at a single stationary source, 8.3.3.2 The NOx emission factor established by the engine operator for each engine pursuant to Section 8.2, and 8.3.3.3 The estimated aggregate NOx emissions calculated according to Section 8.1.2. 8.3.4 Present the methodology for determining equivalency of actual NO_X emissions under the proposed AECP as compared to the estimated NO_X emissions allowed by this rule. 8.3.5 Detail the method of recording and verifying daily compliance with the AECP. 8.3.6 Demonstrate to the satisfaction of the APCO that the difference between the NOx emission limits of this rule and any lower actual NOx emissions will not be used to increase emissions from the same or another source. 8.3.7 Demonstrate that the engines subject to the requirements of Section 5.2 are in compliance with or on an approved schedule for compliance with all applicable District rules.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	8.4 The owner shall submit an updated or modified AECP for approval by the APCO prior to any of the following: 8.4.1 Modification of the engine(s) which would require an Authority-to-Construct. 8.4.2 When new or amended rules are adopted which regulate the emissions from the engines. 8.4.3 When the NOx emission factor established by the engine owner for an engine pursuant to Section 8.2 is modified.	8.4 The operator shall submit an updated or modified AECP for approval by the APCO prior to any of the following: 8.4.1 Modification of the engine(s) which would require an Authority-to- Construct; 8.4.2 When new or amended rules are adopted which regulate the emissions from the engines; or 8.4.3 When the NOx emission factor established by the engine operator for an engine pursuant to Section 8.2 is modified.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	8.5 In addition to the records kept pursuant to Section 6.2, the owner shall maintain records, on a daily basis, of the parameters needed to demonstrate compliance with the applicable NOx emission limits when operating under the AECP. These records shall be retained for at least five years, shall be readily available, and be made available to the APCO upon request. The records shall include, but are not limited to, the following for each engine unless otherwise indicated: 8.5.1 Total hours of operation. 8.5.2 Type and quantity (cubic feet of gas or gallons of liquid) of fuel used. 8.5.3 The actual NOx emissions limits to be included in the calculation of AE_{Actual} pursuant to Section 8.1.1. 8.5.4 The actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECP calculated pursuant to Section 8.1.1. 8.5.5 The estimated NOx emissions limits to be included in the calculation of AE_{Limit} pursuant to Section 8.1.2. 8.5.6 The estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECP calculated pursuant to Section 8.1.2. 8.5.7 The comparison of the actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECP and 90 percent of the estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECP to demonstrate compliance with Section 8.1. 8.5.8 Any other parameters needed to demonstrate daily compliance with the applicable NOx emission limits when operating under the AECP.	8.5 In addition to the records kept pursuant to Section 6.2, the operator shall maintain records, on a daily basis, of the parameters needed to demonstrate compliance with the applicable NOx emission limits when operating under the AECP. These records shall be retained for at least five years, shall be readily available, and be made available to the APCO upon request. The records shall include, but are not limited to, the following for each engine unless otherwise indicated: 8.5.1 Total hours of operation, 8.5.2 Type and quantity (cubic feet of gas or gallons of liquid) of fuel used, 8.5.3 The actual NOx emissions limits to be included in the calculation of AE_{Actual} pursuant to Section 8.1.1, 8.5.4 The actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECP calculated pursuant to Section 8.1.1, 8.5.5 The estimated NOx emissions limits to be included in the calculation of AE_{Limit} pursuant to Section 8.1.2, 8.5.6 The estimated aggregate NOx emissions (AE_{Limit}) for all the engines in the AECP calculated pursuant to Section 8.1.2, 8.5.7 The comparison of the actual aggregate NOx emissions (AE_{Actual}) for all the engines in the AECP and 90 percent of the estimated aggregate NO_X emissions (AE_{Limit}) for all the engines in the AECP to demonstrate compliance with Section 8.1, and 8.5.8 Any other parameters needed to demonstrate daily compliance with the applicable NOx emission limits when operating under the AECP.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	8.6 For the purpose of determining the quantity of spark-ignited engines in compliance pursuant to Section 7.6, a spark-ignited engine in an AECP shall not be considered to be in compliance until all spark-ignited engines in the AECP that have been designated to meet more stringent NOx emission factors pursuant to Section 8.2 are in compliance with the rule.	8.6 For the purpose of determining the quantity of spark-ignited engines in compliance pursuant to Section 7.5, a spark-ignited engine in an AECP shall not be considered to be in compliance until all spark-ignited engines in the AECP that have been designated to meet more stringent NOx emission factors pursuant to Section 8.2 are in compliance with the rule.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

9.0 Exhaust Control System Certification Requirements	9.1 To be considered for APCO certification, the manufacturer or operator shall comply with all of the following requirements: 9.1.1 Certification shall be based upon the emission source testing results of a specific exhaust control system. 9.1.2 A source testing protocol shall be submitted in accordance with the provisions of Rule 1081 (Source Sampling) for approval by the APCO prior to conducting the source test. The source testing protocol approved by the APCO shall be strictly adhered to during certification source testing. 9.1.3 Source testing shall be conducted over the range of operating parameters for which the unit(s) will be operated. 9.1.4 The source testing results shall demonstrate compliance with the emission limits of this rule for each model of exhaust control system(s) to be certified. 9.1.5 The source testing procedure and reports shall be prepared by an ARB- approved independent testing laboratory, and shall contain all the elements identified in the APCO-approved source testing protocol. 9.1.6 Source testing shall be conducted no more than 90 days prior to the date of submission of request for certification by the APCO. 9.1.7 Any additional supporting information required by the APCO to address other performance parameters.	9.1 To be considered for APCO certification, the manufacturer or operator shall comply with all of the following requirements: 9.1.1 Certification shall be based upon the emission source testing results of a specific exhaust control system, 9.1.2 A source testing protocol shall be submitted in accordance with the provisions of Rule 1081 (Source Sampling) for approval by the APCO prior to conducting the source test. The source testing protocol approved by the APCO shall be strictly adhered to during certification source testing, 9.1.3 Source testing shall be conducted over the range of operating parameters for which the unit(s) will be operated, 9.1.4 The source testing results shall demonstrate compliance with the emission limits of this rule for each model of exhaust control system(s) to be certified, 9.1.5 The source testing procedure and reports shall be prepared by an ARB approved independent testing laboratory, and shall contain all the elements identified in the APCO-approved source testing protocol, 9.1.6 Source testing shall be conducted no more than 90 days prior to the date of submission of request for certification by the APCO, and 9.1.7 Any additional supporting information required by the APCO to address other performance parameters.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	9.2 The manufacturer or operator requesting certification shall submit to the APCO the following information: 9.2.1 Copies of the source testing results conducted pursuant to the requirements of Section 9.1, and other pertinent technical data to demonstrate compliance with the emission limits of this rule. 9.2.2 The applicant shall sign and date the statement attesting to the accuracy of all information in the statement. 9.2.3 Name and address of the exhaust control system manufacturer or operator, brand name of the exhaust control unit, model number, and description of model of system(s) being certified.	9.2 The manufacturer or operator requesting certification shall submit to the APCO the following information: 9.2.1 Copies of the source testing results conducted pursuant to the requirements of Section 9.1, and other pertinent technical data to demonstrate compliance with the emission limits of this rule, 9.2.2 The applicant shall sign and date the statement attesting to the accuracy of all information in the statement, and 9.2.3 Name and address of the exhaust control system manufacturer or operator, brand name of the exhaust control unit, model number, and description of model of system(s) being certified.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

	9.3 The APCO will only approve an application for certification to the extent that the requirements of Sections 9.1 through 9.2 are met and the source testing results demonstrate that the emission limits of this rule are met.	9.3 The APCO will only approve an application for certification to the extent that the requirements of Sections 9.1 through 9.2 are met and the source testing results demonstrate that the emission limits of this rule are met.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	9.4 The APCO-approved certification is valid only for the range of operating parameters and conditions for which certification is issued.	9.4 The APCO-approved certification is valid only for the range of operating parameters and conditions for which certification is issued.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**
	9.5 The APCO shall publish a list of certified exhaust control systems after the certification process is completed.	9.5 The APCO shall publish a list of certified exhaust control systems after the certification process is completed.	**There is no change in the requirements of this section. Therefore, the non-SIP version of the rule is as stringent as the SIP version of the rule.**

District Rule 4702 was amended (8/18/2011). As analyzed, each amended section of the non-SIP version of the rule is at least as stringent as, or more stringent than the corresponding section of the SIP version of the rule. Therefore, it is concluded that overall the non-SIP version of the rule is more stringent than the SIP version of the rule

SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 1 Emission Limits/Standards for a Spark-Ignited Internal Combustion Engine and Emission Limits/Standards and Compliance Schedule for a Spark-Ignited Engine Used Exclusively in Agricultural Operations (corrected to 15% oxygen on a dry basis)

Engine Type	NOx	CO	VOC
1. Rich-Burn			
a. Waste gas fueled	50 ppmv or 90% reduction	2000 ppmv	250 ppmv
b. Cyclic loaded, field gas fueled	50 ppmv	2000 ppmv	250 ppmv
c. All other engines	25 ppmv or 96% reduction	2000 ppmv	250 ppmv
2. Lean-Burn			
a. Two stroke, gaseous fueled, less than 100 horsepower	75 ppmv or 85% reduction	2000 ppmv	750 ppmv
b. All other engines	65 ppmv or 90% reduction	2000 ppmv	750 ppmv
3. Rich-Burn Engine Used Exclusively in Agricultural Operations			
a. Comply by 1/1/2009, or if owner has an agreement to electrify, comply by 1/1/2010	90 ppmv or 80% reduction	2000 ppmv	250 ppmv
4. Lean-Burn Engine Used Exclusively in Agricultural Operations			
a. Comply by 1/1/2009 or if owner has an agreement to electrify comply by 1/1/2010	150 ppmv or 70% reduction	2000 ppmv	750 ppmv
5. Certified Spark-Ignited Engine Used Exclusively in AO and installed on or before June 16, 2005			
a. Comply by 6/1/2006	Meet Certified Spark-Ignited Engine Standard of HC+NOx < 0.6 g/bhp-hr		

SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 2 Emission Limits/Standards and Compliance Schedule for a Compression-Ignited Internal Combustion Engine (corrected to 15% oxygen on a dry basis)

Engine Type	Emission Limit/ Standard	Compliance Date
1. Non-Certified Compression-Ignited Engine		
a. Greater than 50 bhp but not more than 500 bhp	EPA Tier 3 or Tier 4	1/1/2010
b. Greater than 500 bhp but not more than 750 bhp and less than 1000 annual operating hours	EPA Tier 3	1/1/2010
c. Greater than 750 bhp and less than 1000 annual operating hours	EPA Tier 4	7/1/2011
d. Greater than 500 bhp and greater than or equal to 1000 annual operating hours	80 ppm NOx, 2,000 ppm CO, 750 ppm VOC	1/1/2008 or, if owner has an agreement to electrify, comply by 1/1/2010
2. Certified Compression-Ignited Engine		
a. EPA Certified Tier 1 or Tier 2 Engine	EPA Tier 4	1/1/2015 or 12 years after installation date, whichever is later
b. EPA Certified Tier 3 or Tier 4 Engine	Meet Certified Compression-Ignited Engine Standard in effect at time of installation	At time of installation

SIP APPROVED VERSION OF DISTRICT RULE 4702

Compliance Schedule 1 – Non-AO Spark-Ignited Engine

Quantity of Non-AO Spark-Ignited Engines to be in Compliance at a Stationary Source	Compliance Date
a. 25% or more of the total number of non-AO spark-ignited engines at a stationary source on June 1, 2005	6/1/05
b. 62.5% or more of the total number of non-AO spark-ignited engines at a stationary source on June 1, 2006	6/1/06
c. 100% of the total number of non-AO spark-ignited engines at a stationary source on June 1, 2007	6/1/07

NON-SIP APPROVED VERSION OF DISTRICT RULE 4702

Table 1 Emission Limits/Standards for a Spark-Ignited Internal Combustion Engine rated at >50 bhp Used Exclusively in Non-AO (All ppmv limits are corrected to 15% oxygen on a dry basis.).			
Engine Type	NOx	CO	VOC
1. Rich-Burn			
a. Waste gas fueled	50 ppmv or 90% reduction	2000 ppmv	250 ppmv
b. Cyclic loaded, field gas fueled	50 ppmv	2000 ppmv	250 ppmv
c. All other engines	25 ppmv or 96% reduction	2000 ppmv	250 ppmv
2. Lean-Burn			
a. Two stroke, gaseous fueled, less than 100 horsepower	75 ppmv or 85% reduction	2000 ppmv	750 ppmv
b. All other engines	65 ppmv or 90% reduction	2000 ppmv	750 ppmv

Table 2 Emission Limits for a Spark-Ignited Internal Combustion Engine Rated at >50 bhp Used Exclusively in Non-AO (All ppmv limits are corrected to 15% oxygen on a dry basis). Emission Limits are effective according to the compliance schedule specified in Section 7.5.			
Engine Type	NOx (ppmv)	CO (ppmv)	VOC (ppmv)
1. Rich-Burn			
a. Waste Gas Fueled	50	2000	250
b. Cyclic Loaded, Field Gas Fueled	50	2000	250
c. Limited Use	25	2000	250
d. Rich-Burn Engine, not listed above	11	2000	250
2. Lean-Burn Engines			
a. Two-Stroke, Gaseous Fueled, >50 bhp and < 100 bhp	75	2000	750
b. Limited Use	65	2000	750
c. Lean-Burn Engine used for gas compression	65 ppmv or 93% reduction	2000	750
d. Lean-Burn Engine, not listed above	11	2000	750

Table 3 Emission Limits/Standards and Compliance Schedule for a Spark-Ignited Internal Combustion Engine >50 bhp Used Exclusively in AO (All ppmv limits are corrected to 15% oxygen on a dry basis).			
Engine Type	NO_X Limit	CO Limit	VOC Limit
1. Rich-Burn	90 ppmv or 80% reduction	2000 ppmv	250 ppmv
2. Lean-Burn	150 ppmv or 70% reduction	2000 ppmv	750 ppmv
3. Certified and installed on or before June 16, 2005	Meet a Certified Spark-Ignited Engine Standard of HC + NOx < 0.6 g/bhp-hr		

Table 4 Emission Limits/Standards and Compliance Schedule for Compression-Ignited Internal Combustion Engine (corrected to 15% oxygen on a dry basis)		
Engine Type	Emission Limit/ Standard	Compliance Date
1. Non-Certified Compression-Ignited Engine Installed on or before June 1, 2006		
a. Greater than 50 bhp but not more than 500 bhp	EPA Tier 3 or Tier 4	1/1/2010
b. Greater than 500 bhp but not more than 750 bhp and less than 1000 annual operating hours	EPA Tier 3	1/1/2010
c. Greater than 750 bhp and less than 1000 annual operating hours	EPA Tier 4	7/1/2011
d. Greater than 500 bhp and greater than or equal to 1000 annual operating hours	80 ppmv NOx, 2,000 ppmv CO, 750 ppmv VOC	1/1/2008 or, if owner has an agreement to electrify, comply by 1/1/2010
2. Certified Compression-Ignited Engine		
a. EPA Certified Tier 1 or Tier 2 Engine	EPA Tier 4	1/1/2015 or 12 years after installation date, but not later than 6/1/2018
b. EPA Certified Tier 3 or Tier 4 Engine	Meet Certified Compression-Ignited Engine Standard in effect at time of installation	At time of installation

Table 5 Compliance Schedule for Non-AO Spark-Ignited Engines Subject to Table 2 Emission Limits, and SOx Control and Monitoring Requirements			
Engines to be in Compliance at a Stationary Source	Emission Control Plan	Authority to Construct and Inspection and Monitoring Plan	Full Compliance
Operator with a single engine at a stationary source			
Single Engine	1/1/12	1/1/13	1/1/14
Operator with at least two engines, but less than 12 engines at a stationary source			
33% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/13	1/1/14
66% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/14	1/1/15
100% of the engines subject to Table 2 emission limits	7/1/12	1/1/15	1/1/16
Operator with at least 12 engines at a stationary source			
25% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/13	1/1/14
50% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/14	1/1/15
75% or more of the engines subject to Table 2 emission limits as of August 18, 2011	7/1/12	1/1/15	1/1/16
100% of the engines subject to Table 2 emission limits	7/1/12	1/1/16	1/1/17