

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.1*

Last Update: 10/26/2009

Boiler: < or = 20.0 MMBtu/hr, Natural Gas or Propane Fired *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.2*

Last Update: 10/26/2009

Boiler: > 20.0 MMBtu/hr, Natural gas fired, base-loaded or with small load swings. *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.3*

Last Update: 10/26/2009

**Boiler - > 20.0 MMBtu/hr, Natural gas fired, with highly variable loads or high
turndown ratios. *RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.4*

Last Update: 10/26/2009

Digester Gas Fired Boiler *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.5*

Last Update: 10/26/2009

Boiler-Dual Fuel for Facilities Requiring Liquid Backup Fuel *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.6*

Last Update: 10/26/2009

Boiler - Fired with a High-Ammonia Fuel *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.7*

Last Update: 10/26/2009

Limited Use Boiler - Natural Gas Fired, < 9 Billion Btu/yr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.1.8*

Last Update: 10/26/2009

Biomass-fired Boiler - Grate Systems *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.2.1*

Last Update: 3/24/2014

Oilfield Steam Generator (> or =20 MMBtu/hr)

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Gaseous fuel		
SOx	Fired on PUC quality natural gas, commercial propane, and/or commercial LPG; or gaseous fuel treated to remove 95% by weight of sulfur compounds; or treated such that the sulfur content of all fuel streams combined does not exceed 1 gr of sulfur compounds (as S) per 100 dscf; or use of a continuously operating SO2 scrubber and either achieve 95% by weight control of sulfur compounds or achieve an emission rate of 9 ppmvd SO2 @ 3% O2		
PM10	Fired on PUC quality natural gas, commercial propane, and/or commercial LPG; or gaseous fuel treated to remove 95% by weight of sulfur compounds; or treated such that the sulfur content of all fuel streams combined does not exceed 1 gr of sulfur compounds (as S) per 100 dscf; or use of a continuously operating SO2 scrubber and either achieve 95% by weight control of sulfur compounds or achieve an emission rate of 9 ppmvd SO2 @ 3% O2		
NOx	<ul style="list-style-type: none"> •Units rated 85 MMBtu/hr and fired solely on PUC quality natural gas: 6 ppmvd @ 3% O2; or •Units firing on > or = 50% PUC quality natural gas; commercial propane; and/or LPG: 7 ppmvd @ 3% O2, except units rated 85 MMBtu/hr and fired solely on PUC quality natural gas; or •Units firing on <50% PUC quality natural gas; commercial propane; and/or LPG: 9 ppmvd @ 3% O2 	5 ppmvd @ 3% O2	
CO	25 ppmvd @ 3% O2		

**San Joaquin Valley
Unified Air Pollution Control District**

CO2e

FEDERAL BACT
=====

FEDERAL BACT
=====

FEDERAL BACT
=====

Federal BACT (40CFR52.21 (b)(23)) for Sources Subject to District Rule 2410 (Prevention of Significant Deterioration)

Variable frequency drive high efficiency electrical motors driving the blower; and
•When firing on $\geq 50\%$ PUC quality natural gas, commercial propane, and/or LPG: a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr (HHV) of maximum rated heat input (verified by manufacturer or independent engineering/construction firm) or an overall thermal efficiency rating of 88% (verified by manufacturer or independent engineering/construction firm); or,
•When firing on $< 50\%$ PUC quality natural gas, commercial propane, and/or LPG: split flow dual pass water feed configuration, a convection section having at least 128 square feet of heat transfer surface area per MMBtu/hr (HHV) of maximum rated heat input (verified by the manufacturer or independent engineering/construction firm) and at least six inches of castable refractory or an overall thermal efficiency rating of at least 85% (verified by manufacturer or independent engineering/construction firm);

Variable frequency drive high efficiency electrical motors driving the blower; and,
•When firing on $\geq 50\%$ PUC quality natural gas, commercial propane, and/or LPG: a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr (HHV) of maximum rated heat input (verified by manufacturer or independent engineering/construction firm) or an overall thermal efficiency rating of 88% (verified by manufacturer or independent engineering/construction firm); or,
•When firing on $< 50\%$ PUC quality natural gas, commercial propane, and/or LPG: split flow dual pass water feed configuration, a convection section having at least 128 square feet of heat transfer surface area per MMBtu/hr (HHV) of maximum rated heat input (verified by the manufacturer or independent engineering/construction firm) and at least six inches of castable refractory or an overall thermal efficiency rating of at least 85% (verified by manufacturer or independent engineering/construction firm);

Or other emission reduction technique determined on a case by case basis that meets the requirements of 40 CFR52.21(b)(23)

1.2.1

San Joaquin Valley Unified Air Pollution Control District

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.2.2*

Last Update: 10/26/2009

**Steam Generator - >20.0 MMBtu/Hr Vertically Oriented w/Counterflow Heat
Transfer *RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.2.3*

Last Update: 5/1/2004

Oilfield Steam Generator/TEOR Gas Incinerator ~~RESCINDED~~ - part of 5/04
update to guideline 1.2.1****

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.3.1*

Last Update: 8/27/2005

**Fluidized-Bed Combustor => 272 MMBtu/hr, Cogeneration Operation, Fired with
Delayed Petroleum Coke (DPC)**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	0.008 lb/MMBtu, natural gas and fuel oil as auxiliary fuel		
SOx	20.2 ppmvd (as SO ₂ corrected to 3% O ₂) (DPC with 2% sulfur by weight) or lowest sulfur content fuel available when 2% sulfur by weight fuel is not available, Sorbent injection and natural gas and low-sulfur fuel oil (15 ppmvd sulfur or less), as auxiliary fuel	lowest sulfur content DPC fuel available, with Sorbent Injection and scrubber; natural gas and low-sulfur fuel oil (15 ppmvd sulfur or less), as auxiliary fuel	
PM10	0.005 gr/dscf corrected to 12% CO ₂ , baghouse, natural gas and low sulfur fuel oil as auxiliary fuel		
NOx	28 ppmvd (as NO ₂ corrected to 3% O ₂), ammonia injection (less than 30 ppmvd ammonia slip) and natural gas and fuel oil as auxiliary fuel)		
CO	natural gas and fuel oil as auxiliary fuel		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.3.2*

Last Update: 3/12/2012

Fluidized Bubbling Bed Combustor (biomass-fired) *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.1*

Last Update: 11/7/2016

**Waste Gas Flare - 15.3 MMBtu/hr, Serving a Tank Vapor Control System
*RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.2*

Last Update: 11/7/2016

Waste Gas Flare - Incinerating Produced Gas *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.3*

Last Update: 1/12/2021

Landfill Gas Vapor Collection System

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Use of an enclosed ultra-low NOx flare with a control efficiency of $\geq 98\%$ or a controlled VOC emissions concentration of ≤ 20 ppmvd @ 3% O ₂ (as hexane, equivalent to 0.038 lb-VOC/MMBtu) and a NOx emissions rate of ≤ 0.025 lb-NOx/MMBtu		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.4*

Last Update: 11/7/2016

Digester Gas-Fired Flare *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.5*

Last Update: 11/7/2016

Oilfield Waste Gas Incinerator *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.6*

Last Update: 11/7/2016

Biogas-Fired Flare: = or > 10.9 MMBtu/hr, Limited Use * RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.7*

Last Update: 11/7/2016

**Waste Gas Flare - Oilfield Well Drilling and Testing Operation, < 50 MMscf/day
*RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.4.8*

Last Update: 11/7/2016

Refinery Flare *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.1*

Last Update: 8/17/2006

Fiberglass Production Furnace and Manufacturing Line, Natural Gas-Fired

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Natural gas firing and use of cullet (scrap glass) > 30% annual average; 0.25 lb-VOC/ton		electric furnace with cullet > 30% annual average
SOx	Scrubber, natural gas firing with low sulfur backup fuel oil (< 0.0015% sulfur by weight), and use of cullet > 30% annual average		electric furnace with cullet > 30% annual average
PM10	Electrostatic Precipitator in series with Scrubber (98% CE); 0.25 lb-PM10/ton		
NOx	1.45 lb/ton with no nitrate, 4.0 lb/ton with nitrate (Oxy-fuel natural gas or equivalent) at final stack (including manufacturing line except forehearths)		electric furnace with cullet > 30% annual average
CO	Natural gas firing and use of cullet > 30% annual average; 1.0 lb-CO/ton		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.2*

Last Update: 4/26/2006

Flat Glass Production Float Furnace

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	< or = 0.028 lb/ton of glass pulled (Natural gas fired Furnace)	Oxidation Catalyst	Electric Furnace
SOx	< or = 2.18 lb/ton of glass pulled (block 24-hour average) and < or = 1.88 lb/ton of glass pulled (30-day rolling average) (Natural gas fired Furnace with Dry Scrubber or Equivalent)	<p>1. < or = 0.3 lb/ton of glass pulled (Natural gas fired Furnace with Dry Scrubber in series with Semi-Wet Scrubber or Equivalent)</p> <p>2. < or = 0.6 lb/ton of glass pulled (Natural gas fired Furnace with Semi-Wet Scrubber and Supplemental Burner or Equivalent)</p> <p>3. < or = 1.7 lb/ton of glass pulled (block 24-hour average) and < or = 1.2 lb/ton (30-day rolling average) (Natural gas fired Furnace with Dry Scrubber or Equivalent)</p>	Electric Furnace
PM10	< or = 0.7 lb/ton of glass pulled (Natural gas fired Furnace with Electrostatic Precipitator or Equivalent)		Electric Furnace
NOx	< or = 3.82 lb/ton of glass pulled (block 24-hour average) and < or = 3.6 lb/ton of glass pulled (30-day rolling average) (Natural gas fired Furnace with Selective Catalytic Reduction (SCR) or Equivalent)		Electric Furnace
CO		Oxidation Catalyst	Electric Furnace

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.3*

Last Update: 5/11/2022

Existing flat glass furnace with a 3R system and a backup thermal De-NOx system *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.4*

Last Update: 5/18/2020

Metal Melting Crucible/Furnace *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.5*

Last Update: 10/19/2000

Glass Bottle Label Curing Lehr - < 10 MMBtu/hr, Natural Gas Fired

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	Natural Gas or LPG Fuel		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.6*

Last Update: 10/15/2014

Metal Heat Treatment Oven**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	50 ppmvd @ 3% O2 (0.061 lb/MMBtu) and use natural gas fuel	5 ppmvd @ 3% O2 (0.006 lb/MMBtu) with the use of an SCR System***	Use of electric furnace

**BACT will be established on a case-by-case basis to assure the lowest achievable emission rate, taking into account unique facility characteristics.

***Use of SCR system is feasible only when the unit's exhaust temperature is greater than or equal to 500 'F.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.7*

Last Update: 8/17/2006

Glass Furnace Forehearth

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	natural gas/propane-fired and good combustion practices		electric forehearth
SOx	natural gas/propane-fired and good combustion practices		electric forehearth
NOx	natural gas/propane-fired and good combustion practices		electric forehearth

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.8*

Last Update: 6/19/2006

Container Glass Production - Container Glass Distributor

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC			Electric glass distributor
SOx			Electric glass distributor
PM10			Electric glass distributor
NOx	Natural gas-fired container glass distributor with good combustion practices, using LPG backup fuel, and NOx emissions of 0.10 lb/MMBtu		Electric glass distributor
CO	Natural gas-fired container glass distributor with good combustion practices, using LPG backup fuel, and CO emissions of 0.084 lb/MMBtu		Electric glass distributor

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.9*

Last Update: 12/9/2014

Container Glass Melting Furnace

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	0.02 lb-VOC/ton of glass pulled, except during periods of startup, shutdown and idling; And compliance with District Rule 4354 requirements for startup, shutdown, and idling.		Electric Furnace
SOx	<p>1. Oxy-fuel fired furnaces while processing material where > or = 25.0 percent of the total cullet is mixed color cullet: 0.99 lb-SOx/ton of glass pulled on a rolling 30-day average; And compliance with District Rule 4354 requirements for startup, shutdown, and idling.</p> <p>2. All other Container Glass Furnaces: 0.8 lb-SOx/ton of glass pulled on a rolling 30-day average; And compliance with District Rule 4354 requirements for startup, shutdown, and idling.</p>		Electric Furnace
PM10	0.45 lb-PM10/ton of glass pulled, except during periods of startup, shutdown, and idling; And compliance with District Rule 4354 requirements for startup, shutdown, and idling.		Electric Furnace
NOx	1.3 lb-NOx/ton of glass pulled on a rolling 30-day average, except during periods of startup, shutdown, and idling; And compliance with District Rule 4354 requirements for startup, shutdown, and idling.		Electric Furnace
CO	0.20 lb-CO/ton of glass pulled, except during periods of startup, shutdown, and idling; And compliance with District Rule 4354 requirements for startup, shutdown, and idling.		Electric Furnace

San Joaquin Valley Unified Air Pollution Control District

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.10*

Last Update: 10/9/2018

Container Glass Annealing Lehr

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Utilize PUC quality natural gas fuel with LPG as backup fuel		Electric Annealing Lehr
SOx	Utilize PUC quality natural gas fuel with LPG as backup fuel		Electric Annealing Lehr
PM10	Utilize PUC quality natural gas fuel with LPG as backup fuel		Electric Annealing Lehr
NOx	Utilize burner system with 60 ppmvd NOx @ 3% O2 or 0.073 lb-NOx/MMBtu fired on PUC quality natural gas, and LPG as backup fuel		Electric Annealing Lehr
CO	Utilize burner system with 20 ppmv CO @ 3% O2 or 0.015 lb-CO/MMBtu fired on PUC quality natural gas, and LPG as backup fuel		Electric Annealing Lehr

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.11*

Last Update: 5/21/2020

Container Glass Production - Mold Swabbing Operation

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
PM10	Using best management practices and the judicious use of mold swabbing material (< or = 0.211 lb of material per ton of glass produced) with PM10 emissions of 0.19 lb/ton of glass formed		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.12*

Last Update: 7/7/2020

Secondary Aluminum Melting: Sweat Furnace, Holding Furnace and Reverb Furnace

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Sweat Furnaces: Afterburner (≥0.3 sec retention time at ≥1,400°F) or secondary combustion chamber Holding and Reverb Furnaces (non-sweating): None		
SOx	Use natural gas fuel		
PM10	Sweat Furnaces: Use of natural gas fuel, afterburner with 1400°F chamber temperature, and a baghouse with fabric filters Holding and Reverb Furnaces (non-sweating): Use of natural gas fuel and a baghouse with fabric filters		
Nox	Sweat Furnaces: 50 ppmvd @ 3% O2 (Use of Low-NOx Burners) Holding Furnaces: 40 ppmvd @ 3% O2 (Use of Low-NOx Burners) Reverb Furnaces (non-sweating): 53 ppmvd @ 3% O2 (Use of Low-NOx Burners)	Sweat, Holding, and Reverb Furnaces: 1) 6.0 ppmvd @ 3% O2 (Use of Low-NOx Burners and Selective Catalytic Reduction) 2) 12.0 ppmvd @ 3% O2 (Use of Low-NOx Burners and Regenerative Selective Catalytic Reduction) 3) 30 ppmvd @ 3% O2 (Use of Low-NOx Burners and Selective Non-Catalytic Reduction)	Use of Electric Furnaces
CO	Use natural gas fuel	1) 5 ppmvd @ 3% O2, Oxidation catalyst or equivalent control; 2) 50 ppmvd @ 3% O2	Use of Electric Furnaces

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.5.13*

Last Update: 3/7/2016

Aluminum Diecasting Furnace

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
PM10	<p>Reverb Furnaces (non-sweating):</p> <p>Use of "clean charge" without addition of any flux, and the use of natural gas fuel in the furnace.</p>	<p>Reverb Furnaces (non-sweating):</p> <p>Use of baghouse and natural gas fuel in the furnace</p>	
NOx	<p>Reverb Furnaces (non-sweating):</p> <p>53 ppmvd @ 3% O2 (0.0643 lb/MMBtu) with the use of Low-NOx Burners</p>	<p>Reverb Furnaces (non-sweating):</p> <p>1. 6.0 ppmvd @ 3% O2 (0.0073 lb/MMBtu) with use of Low-NOx Burners and Selective Catalytic Reduction</p> <p>2. 12.0 ppmvd @ 3% O2 (0.0146 lb/MMBtu) with use of Low-NOx Burners and Regenerative Selective Catalytic Reduction</p> <p>3. 30 ppmvd @ 3% O2 (0.0364 lb/MMBtu) with use of Low-NOx Burners and Selective Non-Catalytic Reduction</p>	<p>Use of Electric Furnaces</p>

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.1*

Last Update: 4/14/2020

Vegetable Dry Roasting Operation

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOX	60 ppmv @ 3% O2 (equivalent to 6.5 ppmv @ 19% O2 or 0.073 lb- NOX/MMBtu)	9 ppmv @ 3% O2 (equivalent to 1.0 ppmv @ 19% O2 or 0.011 lb-NOX /MMBtu) or less with Selective Catalytic Reduction	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.2*

Last Update: 4/20/2020

Oven - Tortilla, <= 5 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.3*

Last Update: 2/21/2020

Snack Chip Fryer with Indirect-Fired Heat Transfer System

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	<p>COMBUSTION EMISSIONS: Use PUC quality natural gas fuel with LPG/Propane as backup fuel</p> <p>FRYING PROCESS EMISSIONS: None</p>	<p>FRYING PROCESS EMISSIONS: 1) 85% control (combined VOC and PM control by thermal oxidizer, or equal); 2) 80% control (combined VOC and PM control by carbon adsorber, or equal)</p>	
SOx	Use PUC quality natural gas fuel with LPG/Propane as backup fuel		
PM10	<p>COMBUSTION EMISSIONS: Use PUC quality natural gas fuel with LPG/Propane as backup fuel</p> <p>FRYING PROCESS EMISSIONS: 75% control (oil mist eliminator or equal)</p>	<p>FRYING PROCESS EMISSIONS: 1) 85% control (combined VOC and PM control by thermal oxidizer, or equal); 2) 80% control (combined VOC and PM control by carbon adsorber, or equal)</p>	
NOx	<p>9 ppmvd @ 3% O2 for units greater than 5 MMBtu/hr to less than or equal to 20 MMBtu/hr</p> <p>7 ppmvd @ 3% O2 for units greater than 20 MMBtu/hr</p>		
CO	100 ppmvd @ 3% O2		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.4*

Last Update: 5/11/2022

Oven - Snack Food *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.5*

Last Update: 4/20/2020

Cornnut (tm) cooker *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.6*

Last Update: 4/20/2020

Peanut Roasting Operation *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.7*

Last Update: 5/11/2022

Pistachio Roasting Operation *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.8*

Last Update: 3/13/2015

Nut and Seed Column Dryer

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	1) Natural gas, or 2) LPG for operations with no access to a natural gas fuel source		
SOx	1) PUC quality natural gas, or 2) LPG for operations with no access to a PUC quality natural gas fuel source		
PM10	1) Natural gas, or 2) LPG for operations with no access to a natural gas fuel source		
NOx	1) Low NOx burner and natural gas @ 0.0832 lb-NOx/MMBtu, or 2) Low NOx burner and LPG @ 0.1248 lb-NOx/MMBtu for operations with no access to a natural gas fuel source		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.9*

Last Update: 5/11/2022

Dryer - Almond Processing, < 10 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.10*

Last Update: 5/11/2022

Oven - Wheat Drying, < or = 10 MMBtu/hour *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.11*

Last Update: 5/9/2019

Direct-Fired Dairy Products Spray Dryer

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Use of PUC quality natural gas fuel with LPG as backup fuel		
SOx	Use of PUC quality natural gas fuel with LPG as backup fuel		
PM10	Use of a baghouse/dust collector and PUC quality natural gas fuel with LPG as backup fuel		
NOx	Use of a 2.2 ppmv NOx @ 19% O2 (equivalent to 20 ppmv NOx @ 3% O2 or 0.0243 lb-NOx/MMBtu) low NOx burner (or equivalent) fired on PUC quality natural gas with LPG as backup fuel	Use of a 1.0 ppmv NOx @ 19% O2 (equivalent to 9 ppmv NOx @ 3% O2 or 0.0109 lb-NOx/MMBtu) ultra low NOx burner (or equivalent) fired on PUC quality natural gas with LPG as backup fuel	
CO	Use of a 42 ppmv CO @ 19% O2 (equivalent to 387 ppmv CO @ 3% O2 or 0.286 lb-CO/MMBtu) burner (or lower) fired on PUC quality natural gas with LPG as backup fuel		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.12*

Last Update: 5/11/2022

Dryer - Whey, Filtermat, < 50 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.13*

Last Update: 11/17/2020

Dehydrator - Vegetable, Continuous Process *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.14*

Last Update: 5/11/2022

Dehydrator Tunnel - Fruit, Natural Gas Fired *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.16*

Last Update: 5/11/2022

Dryer - Seed Processing, < 20 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.17*

Last Update: 4/20/2020

**Food Preparation Oven, <800 degrees Fahrenheit, = or < 3.7 MMBtu/hr
*RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.18*

Last Update: 4/20/2020

**Chicken Fryer - Natural Gas-Fired, Continuous Process, = or < 7 tons/hr
*RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.19*

Last Update: 4/20/2020

Meat Smokehouse - Natural Gas-Fired, < or = 2 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.20*

Last Update: 7/11/2001

Feather Meal Processing Rotary Dryer - Natural Gas Fired, High Ammonia Environment

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Natural gas fired with LPG as a backup fuel		
SOx	Natural gas fired with LPG as a backup fuel.		
PM10	Natural gas fired with LPG as a backup fuel		
NOx		1. 9 ppmvd @ 3% oxygen (Selective Catalytic Reduction system) 2. 30 ppmvd @ 3% oxygen (Low NOx burner system)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.21*

Last Update: 4/20/2020

Flake Cereal Dryer - < 20 MMBtu/hr, Conveyor-fed *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.22*

Last Update: 7/1/2020

Wood Drying Kiln

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Natural gas (good operating practice and maintenance)	1) 98% or greater capture and control (thermal oxidizer, catalytic oxidizer or equivalent) 2) 95% or greater capture and control (carbon adsorption, provided the contaminated air stream does not contain any ingredient that could combust as a result of adsorption to carbon or equivalent)	
SOx	Natural gas (good operating practice and maintenance)		
PM10	Natural gas (good operating practice and maintenance)		
Nox	Natural gas (good operating practice and maintenance)	1) ≤ 10 ppmvd @ 3% O ₂ (equivalent to 0.012 lb/MMBtu or less) 2) ≤ 15 ppmvd @ 3% O ₂ (equivalent to 0.018 lb/MMBtu or less)	
CO	Natural gas (good operating practice and maintenance)	≤ 25 ppmvd @ 3% O ₂	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.23*

Last Update: 7/10/2007

Pistachio, Almond, and Walnut Dryers (<10 MMBtu/hr and <2,160 hr/yr)

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Natural gas with LPG as backup fuel		
SOx	PUC quality natural gas with LPG as backup fuel		
PM10	Natural gas with LPG as backup fuel		
NOx	0.06 lb/MMBtu, natural gas-fired with low NOx burner	1) 0.012 lb/MMBtu, natural gas-fired with low NOx burner 2) 0.024 lb/MMBtu, natural gas-fired with low NOx burner	
CO	Natural gas with LPG as backup fuel		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.24*

Last Update: 12/30/2020

Commercial Bakery Oven

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Overall 98% capture and control efficiency with the use of thermal/catalytic incineration (or equivalent) with NOx emissions ≤ 60 ppmvd @ 3% O2 (0.073 lb-NOx/MMBtu) for thermal/catalytic incinerator units rated equal to or greater than 0.325 MMBtu/hr, and CO emissions of 800 ppmvd @ 3% O2 (or less) for thermal/catalytic incinerator units		
SOx	Use PUC quality natural gas fuel		
PM10	Use PUC quality natural gas fuel		
Nox	30 ppmvd @ 3% O2 equivalent to 0.036 lb/MMBtu and use of PUC quality natural gas fuel	Use of low Temperature – Selective Catalytic Reduction	Electric Oven
CO	800 ppmvd @ 3% O2 and use of PUC quality natural gas fuel		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.25*

Last Update: 12/29/2021

Blood Drying Operation

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	95% Overall Capture and Control Efficiency (Incineration at 1,600 °F for not less than 0.5 seconds, or equal)		
PM10	0.579 lb-PM10/ton of dried blood		
NH3	0.6 lb-NH3/ton of dried blood (Venturi Scrubber vented to Packed Bed Scrubber, thermal oxidizer, or equal)	Wet scrubber for NH3 removal prior to thermal oxidizer (only if thermal oxidizer is used and the oxidation of NH3 results in more than 2.0 lb/day of NOx emissions)	
H2S		Wet scrubber for H2S removal prior to thermal oxidizer (only if thermal oxidizer is used and the oxidation of H2S results in more than 2.0 lb/day of SOx emissions)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.26*

Last Update: 3/25/2008

Rotary Kiln Dryer for Poultry Litter* Processing

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC		1. thermal oxidizer 2. catalytic oxidizer 3. biotrickling filter 4. wet scrubber	
PM10	baghouse or equal technology		
NH3		1. catalytic oxidizer 2. wet scrubber 3. biotrickling filter	

For the purposes of this guideline, poultry litter is defined as a mixture of poultry manure and bedding material such as rice hulls

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.28*

Last Update: 7/2/2012

Direct-Fired Conveyorized Hotdog Cooking Oven

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Oven vented to a regenerative thermal oxidizer (or an equivalent control system with at least 70% control efficiency)		
PM10	Oven vented to a regenerative thermal oxidizer (or an equivalent control system)		
NOx	70.0 ppmvd @ 3% O2 (0.085 lb/MMBtu) and natural gas fuel	1) 9.0 ppmvd @ 3% O2 using ultra-low Nox burner system, or equivalent control technology 2) 20.0 ppmvd @ 3% O2 using ultra-low or low-Nox burner system, or equivalent control technology	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.29*

Last Update: 7/12/2012

Indirect-fired Impingement Meatball Cooking Oven

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Cooking chamber exhaust vented to a wet scrubber (rotoclone) and regenerative thermal oxidizer system (or an equivalent control with at least 70% control efficiency)		
PM10	Cooking chamber exhaust vented to a wet scrubber (rotoclone) and regenerative thermal oxidizer system (or an equivalent control system)		
Nox	80.0 ppmvd @ 3% O2 (0.097 lb/MMBtu)	1) 8.0 ppmvd @ 3% O2 (0.010 lb/MMBtu) Selective Catalytic Reduction, or equal	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.6.30*

Last Update: 3/24/2022

Heat-Sterilizing Kiln for Wood, Gaseous Fuel Fired

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Use of natural gas-fired kiln, or LPG-fired kiln (for operations with no access to a natural gas fuel source)		
SOx	Use of natural gas-fired kiln, or LPG-fired kiln (for operations with no access to a natural gas fuel source)		
PM10	Use of natural gas-fired kiln, or LPG-fired kiln (for operations with no access to a natural gas fuel source)		
NOx	Use of natural gas-fired kiln, or LPG-fired kiln (for operations with no access to a natural gas fuel source)	1) Ultra-low NOx burner rated at ≤ 10 ppmvd @ 3% O ₂ using natural gas or LPG 2) Low NOx burner rated at ≤ 30 ppmvd @ 3% O ₂ using natural gas, or ≤ 40 ppmvd @ 3% O ₂ using LPG (for operations with no access to a natural gas fuel source)	
CO	Use of natural gas-fired kiln, or LPG-fired kiln (for operations with no access to a natural gas fuel source)	Burner rated at ≤ 25 ppmvd @ 3% O ₂	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.7.1*

Last Update: 4/3/2000

Oven - Polyethylene Curing, = or < 20 MMBtu/hr

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	Natural Gas or Propane Fuel	1. 20 ppmv @ 3% O2 (low-NOx Burner) 2. 30 ppmv @ 3% O2 (low-NOx Burner)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.7.2*

Last Update: 5/11/2022

Oven - Plastisol curing/fusing, = or < 2.5 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.7.3*

Last Update: 5/11/2022

Oven - Parts Cleaning, Burnoff or Burnout *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.8.1*

Last Update: 10/26/2009

**Refinery Heater, fired on refinery fuel gas and/or natural gas (< or = 50 MM
Btu/hr) ~~**RESCINDED**~~**

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.8.2*

Last Update: 10/26/2009

**Refinery Heater, fired on refinery fuel gas and/or natural gas (> 50 MM Btu/hr)
RESCINDED**

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.8.3*

Last Update: 10/26/2009

Gas Dehydration - Glycol Reboiler ~~RESCINDED**~~**

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.8.4*

Last Update: 10/26/2009

Heater Treater < 20 MMBtu/hr, Natural Gas Fired **RESCINDED**

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.8.5*

Last Update: 10/26/2009

Process Heater (non-refinery, < or = 20 MMBtu/hr) ~~RESCINDED**~~**

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.1*

Last Update: 5/11/2022

Metal Parts Washer - Natural Gas-fired *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.2*

Last Update: 4/20/2020

Sulfuric Acid Plant Start-up Heater - < 15 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.3*

Last Update: 6/9/2022

**Crematory (Funeral Service and Crematories, Animal Crematory) - Gaseous Fuel
Fired**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Natural Gas/LPG fuel and a secondary combustion chamber (afterburner) > 1,600 ° F		
SOx	Natural Gas/LPG fuel	Natural Gas/LPG fuel with a Dry Scrubber and a Baghouse	
PM10	Natural Gas/LPG fuel and a secondary combustion chamber (afterburner) > 1,600 ° F	Natural Gas/LPG fuel with a Baghouse	
NOx	Natural Gas/LPG fuel and 60 ppmv @ 3% O2 (0.073 lb/MMBtu) without charge		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.4*

Last Update: 5/11/2022

**Dryer - Natural Gas Fired, Solvent-Laden Towels, = or < 950 lb towels/day
*RESCINDED***

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.5*

Last Update: 5/11/2022

Gas Absorption Chiller - Natural Gas Fired, < 20 MMBtu/hr *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.6*

Last Update: 1/6/2000

Asphalt-Surface-Repair Heater, Propane Fired, < 20 MMBtu/hr

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	0.15 lb NOx /MMBtu propane fired burner	0.036 lb NOx /MMBtu Low-NOx burner	
CO	0.021 lb NOx /MMBtu propane fired burner		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.7*

Last Update: 3/14/2000

**Auxiliary Burner System, Dryer, Natural Gas Fired,
< 20 MMBtu/hr**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
PM10	Natural Gas Fuel		
NOx		1. 9.0 ppmv @ 3% O2 (Low Temperature Oxidation, SCR, or equal) 2. 15 ppmv @ 3% O2 (Low NOx burner, or equal) 3. 20 ppmv @ 3% O2 (Low NOx burner, or equal)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.8*

Last Update: 4/20/2020

Municipal-waste Incinerator - < 750 lb waste/hr feed rate *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.9*

Last Update: 2/20/2001

**Molded Paper Products Dryer - Natural Gas Fired,
< 20 MMBtu/hr**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	80 ppmv @ 3% O2 (standard burner)	1. 9 ppmv @ 3% O2 (Ultra low-NOx Burner, SCR, or equal) 2. 20 ppmv @ 3% O2 (low-NOx burner)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.10*

Last Update: 2/2/2001

**Mineral Products Spray Dryer - Natural Gas Fired,
< or = 20 MMBtu/hr**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	20 ppmv NOx @ 3% O2 (low NOx burner)	15 ppmv NOx @ 3% O2 (low NOx burner)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.11*

Last Update: 7/1/2020

Commercial Laundry Dryer, Natural Gas-Fired - < 5.0 MMBtu/hr

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Use of PUC quality natural gas fuel		
SOx	Use of PUC quality natural gas fuel		
PM10	Use of a lint collector with a control efficiency of $\geq 75\%$ or equivalent and PUC quality natural gas fuel	1) Use of a baghouse with a control efficiency of $\geq 99\%$ or equivalent and PUC quality natural gas fuel 2) Use of a venturi scrubber with a control efficiency of $\geq 90\%$ or equivalent and PUC quality natural gas fuel	
Nox	Use of 30 ppmvd NOx @ 3% O2 (equivalent to 0.0365 lb-NOx/MMBtu) low NOx burner (or equivalent) fired on PUC quality natural gas fuel	Use of 9.2 ppmvd @ 3% O2 (equivalent to 0.0111 lb-NOx/MMBtu) ultra-low NOx burner (or equivalent) fired on PUC quality natural gas fuel	
CO	Use of 114 ppmvd CO @ 3% O2 (equivalent to 0.084 lb-CO/MMBtu) burner (or lower) fired on PUC quality natural gas fuel	Use of 4.6 ppmvd CO @ 3% O2 (equivalent to 0.0034 lb-CO/MMBtu) burner fired on PUC quality natural gas fuel	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.12*

Last Update: 4/20/2020

Transportable Diesel-Fired Nitrogen Vaporizer *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.13*

Last Update: 10/19/2006

Blood Meal Processing Ring Dryer Burner

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	Natural gas fired with LPG as a backup fuel	9.0 ppmvd @ 3% O2 (0.011 lb-NOx/MMBtu) low NOx burner system 30 ppmvd @ 3% O2 (0.036 lb-NOx/MMBtu) burner system	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.14*

Last Update: 2/9/2007

Natural Gas Fired Dryer with High Turndown Ratio**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
NOx	<= 8.9 ppmvd*** @ 19% O2 (0.1 lb/MMBtu) low NOx burner	4.3 ppmvd @ 19% O2 (0.048 lb/MMBtu) low NOx burner, or equal	Electric Dryer

**For the purpose of this determination, a "high turndown ratio" is one that exceeds the turndown ratio of an ultra-low NOx burner system operating at 2.2 ppmv NOx @ 19% O2 or 1.1 ppmv NOx @ 19% O2.

***BACT will be established on a case-by-case basis to assure the lowest achievable emission rate, taking into account unique facility characteristics

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.15*

Last Update: 4/20/2020

Jet Aircraft Fire Training Facility *RESCINDED*

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.16*

Last Update: 4/26/2016

Power Oxidizer - VOC Incineration and Power Generation, < or = 35 MMBtu/hr

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	0.0064 lb/MMBtu	0.0055 lb/MMBtu	
NOx	9 ppmvd @ 15% O2 (equivalent to 0.0332 lb/MMBtu or 0.5 lb/MW-hr)	0.8 ppmvd @ 15% O2 (equivalent to 0.0062 lb/MMBtu or 0.1 lb/MW-hr)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 1.9.17*

Last Update: 1/30/2017

Stationary Air Curtain Incinerator

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Air curtain incinerator (electric powered), complying with visible emissions of 10% opacity or less after start-up (per 40 CFR Part 60 Subpart CCCC, sections 60.2250 and 60.2255)		<ol style="list-style-type: none"> 1. Biomass Power Plant 2. Landfill 3. Composting
SOx	Air curtain incinerator (electric powered), complying with visible emissions of 10% opacity or less after start-up (per 40 CFR Part 60 Subpart CCCC, sections 60.2250 and 60.2255)		<ol style="list-style-type: none"> 1. Biomass Power Plant 2. Landfill 3. Composting
PM10	Air curtain incinerator (electric powered), complying with visible emissions of 10% opacity or less after start-up (per 40 CFR Part 60 Subpart CCCC, sections 60.2250 and 60.2255)		<ol style="list-style-type: none"> 1. Biomass Power Plant 2. Landfill 3. Composting
NOx	Air curtain incinerator (electric powered), complying with visible emissions of 10% opacity or less after start-up (per 40 CFR Part 60 Subpart CCCC, sections 60.2250 and 60.2255)		<ol style="list-style-type: none"> 1. Biomass Power Plant 2. Landfill 3. Composting

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**