

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.1.2\***

Last Update: 12/30/2021

**Feed Mill - Truck Loadout**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Enclosed loading and 99% control, vented to a baghouse or equivalent		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.1.5\***

Last Update: 4/27/2020

**Railcar Receiving Pit - Dry Grain/Products, = or > 1,700 tons/day**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
PM10	Receiving pit using choke feeding and vented to a baghouse/dust collector	1) Receiving operation housed in an enclosed building or structure with receiving pit using choke feeding and vented to a baghouse/dust collector  2) Receiving operation housed in structure with doors open with receiving pit using choke feeding and vented to a baghouse/dust collector	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.1.6\***

Last Update: 4/20/2020

**Ship Unloading System - Bulk Cottonseed Receiving Hopper**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Receiving hopper vented to 1D-3D cyclone collectors exhausting to a baghouse		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.1.7\***

Last Update: 5/4/2020

**Railcar Unloading - Transportable, Material Conveying Equipment**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
PM10	Railcar choke feeding or railcar drop height less than 12 inches, enclosed conveyor vented to a control device with at least 99% control (baghouse or equivalent), and loadout served by a flexible spout. Opacity not to exceed 5%.		1) Pneumatic unloader vented to a control device with at least 99% control (baghouse or equivalent)  2) Receiving pit vented to a control device with at least 99% control (baghouse or equivalent) and loadout served by a flexible spout  3) Receiving pit vented

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.1.8\***

Last Update: 9/27/2021

**Non-Delinted Cottonseed - Truck Loadout Operation**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Visible emissions from the truck loadout operation not to exceed 10% opacity for any 3 minutes in any one hour period	1. Enclosed loadout area vented to pre-cleaning cyclone(s) and a baghouse 2. Enclosed loadout area vented to 1D-3D or equivalent cyclone(s)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.1\***

Last Update: 9/12/2022

**Almond Hulling and Shelling**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	>=99% Control (Fabric Filter Baghouse, Cartridge-Type Dust Collector, or equivalent)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.2\***

Last Update: 6/14/2022

**Almond Processing - Sizing Operation (In-shell Almonds and Shelled Almond Meats)**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	>= 99% Control (Fabric Filter Baghouse, Cartridge-Type Dust Collector, or Equivalent)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.3\***

Last Update: 11/1/2022

**Pistachio Nut Processing - Precleaning Operations, >= 375 tons/day in-hull  
pistachios**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	1D-3D cyclone, high- efficiency cyclone, or equivalent achieving at least 80% control		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.4\***

Last Update: 3/6/2020

**Feed Mill - Grain Grinding, Dry Process**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Baghouse, or equivalent (99% or greater control efficiency)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.5\***

Last Update: 3/6/2020

**Feed Mill - Grain Cleaner with Aspirator**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Aspirator exhausted to a fabric filter baghouse, or equivalent (99% or greater control efficiency)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.8\***

Last Update: 5/14/2020

**Propylene Oxide Fumigation - Fumigation Chamber**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
VOC	98% Control Efficiency (wet scrubber, flare, or equal)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.9\***

Last Update: 5/14/2020

**Propylene Oxide Fumigation - Off-Gassing Process\*\***

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
VOC		1) 98% Control Efficiency (Wet Scrubber, or equal)  2) 95% Control Efficiency (Carbon Adsorption or equal)  3) 80% Control Efficiency (Refrigerated vapor condenser, or equal)	

\*\*This operation does not include the initial fumigation operation in the chamber which is covered by Guideline 5.2.8.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.12\***

Last Update: 6/28/2023

**Phosphine fumigation of nuts, dried fruit, grain, and beans**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
Phosphine (T-BACT)		Carbon Absorption or Equivalent (95% control)	
Ammonia (NH3)	Stacked Bins, Bins with Plastic Liners, Palletized Stacks, Shipping Containers, Fumigation Chambers, Warehouses, Storage Silos and Stockpiles: phosphine gas or a mixture of phosphine gas and carbon dioxide from pressurized cylinders, fumigated inside gas tight tarps, gas tight bin liners or a gas tight enclosure**	Ammonia Scrubber (98% control) (not applicable to infield operations)	

\*\*If it is suitably demonstrated that it is infeasible for a facility to obtain or use phosphine gas pressurized cylinders, aluminum phosphide based solid fumigants can be used in place of phosphine gas to satisfy BACT.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.13\***

Last Update: 3/29/2023

**Walnut Receiving and Precleaning**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	70% Overall Capture and Control (Cyclone or Equivalent)	1.99% Overall Capture and Control (Fabric Filter Baghouse Dust Collector, Cartridge-Type Dust Collector, or Equivalent)  2. 88% Overall Capture and Control (Enhanced 1D-3D Cyclone or Equivalent)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.2.14\***

Last Update: 9/12/2022

**Almond Receiving and Precleaning**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	>=99% Control (Fabric Filter Baghouse, Cartridge-Type Dust Collector, or equivalent)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.3.1\***

Last Update: 6/15/2020

**Cotton Gin Operation**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Enhanced 1D-3D cyclone collectors, or 1D-3D cyclone collectors with expansion chambers, or rotary drum filter, or equivalent		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.1\***

Last Update: 6/18/2020

**Fruit Storage and SO<sub>2</sub> Fumigation: = or > 21,760 cu. ft. Fumigation Rooms**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
SO <sub>x</sub>	Pre-cooling and cold storage SO <sub>2</sub> fumigation of fruits using total utilization method of fumigation, and/or "Defrost Cycle" scrubbing		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.2\***

Last Update: 6/18/2020

**Fruit Drying and SO<sub>2</sub> Fumigation: = or > 21,760 cu. Ft. Fumigation Rooms**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
SO <sub>x</sub>	Packed bed scrubber using recirculated caustic liquid (pH 8 to 10)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.5\***

Last Update: 4/30/2020

**Garlic and Onion Seed Processing**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Aspirators and vacuum collectors vented to a baghouse		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.6\***

Last Update: 4/30/2020

**Garlic Grading Line**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Fabric Filter Baghouse (99% Control Effectiveness)  or  Hand-picked Garlic with 1D-3D Cyclone (99% Control Effectiveness)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.8\***

Last Update: 9/27/2021

**Fruit Fumigation - Ethanol Soaking Tank**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
VOC		<ol style="list-style-type: none"><li>1. Wet scrubber with 99% or greater control efficiency</li><li>2. Thermal incinerator with 98% or greater control efficiency</li><li>3. Biofilter with 90% or greater control efficiency</li></ol>	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.9\***

Last Update: 4/17/2020

**Tomato Powder Manufacturing**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	1D-3D cyclone with wet scrubber (87% control efficiency)	1) 1D-3D cyclone with venturi wet scrubber (99% control efficiency)  2) 1D-3D cyclone with electrostatic precipitator (95% control efficiency)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.13\***

Last Update: 9/7/2018

**Wine Storage Tank - Non-Wood Material\*\***

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Insulation or Equivalent***, Pressure Vacuum Relief Valve (PVRV) set within 10% of the maximum allowable working pressure of the tank; "gas-tight" tank operation; and continuous storage temperature not exceeding 75 degrees F, achieved within 60 days of completion of fermentation	<ol style="list-style-type: none"> <li>1. Capture of VOCs and thermal or catalytic oxidation (98% control)</li> <li>2. Capture of VOCs and carbon adsorption (95% control)</li> <li>3. Capture of VOCs and absorption (90% control)</li> <li>4. Capture of VOCs and condensation (70% control)</li> </ol>	

\*\*This guideline is applicable to a wine storage tank that is not constructed out of wooden materials.  
 \*\*\*Tanks made of heat-conducting materials such as stainless steel may be insulated or stored indoors (in a completely enclosed building, except for vents, doors and other essential openings) to limit exposure of diurnal temperature variations. Tanks made entirely of non-conducting materials such as concrete (except for fittings) are considered self-insulating.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.15\***

Last Update: 5/6/2020

**Distilled Spirits Storage Tank**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Insulation or Equivalent**, Pressure Vacuum Relief Valve (PVRV) set within 10% of the maximum allowable working pressure of the tank; "gas-tight" tank operation	1) Capture of VOCs and thermal or catalytic oxidation or equivalent (98% control)  2) Capture of VOCs and carbon adsorption or equivalent (95% control)  3) Capture of VOCs and absorption or equivalent (90% control)  4) Refrigerated Storage (70% control)	

\*\*Tank may be insulated or stored indoors (in a completely enclosed building except for vents doors and other essential openings) to limit exposure to diurnal temperature variations.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.16\***

Last Update: 5/13/2020

**Ethanol Evaporator System**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
VOC		1) Capture of VOCs and refrigerated condensation or equivalent (99% control)  2) Capture of VOCs and thermal or catalytic oxidation or equivalent (>95% control)  3) Capture of VOCs and refrigerated absorption or equivalent (95% control)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.4.17\***

Last Update: 9/18/2019

**Wine Storage Tank - Wood Material**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Maintain wine temperature in the tank at or below 75 degrees F, achieved within 60 days of completion of fermentation	1. 98% overall control (properly designed capture system vented to a regenerative thermal oxidizer or equal)  2. 95% overall control (properly designed capture system vented to a carbon adsorption system or equal)  3. 80% overall control (properly designed capture system vented to a scrubber system or equal)  4. 70% overall control (properly designed capture system vented to a condensation system or equal)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.5.3\***

Last Update: 6/10/2020

**Candy Panning (Engrossing) Operation\*\***

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC		1) 98% or greater overall control (100% capture with permanent total enclosures designed in accordance with EPA Method 204 and at least 98% destruction using regenerative thermal oxidizer, catalytic oxidizer, carbon adsorption or equivalent overall control technology  2) 90% or greater overall control (100% capture with permanent total enclosures designed in accordance with EPA Method 204 and at least 90% destruction using bio filter or equivalent overall control technology	

\*\*A process in which candy center is coated to a desired thickness with a mixture of sugar syrup, coloring, flavoring etc. in a rotating pan.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.5.4\***

Last Update: 7/1/2020

**Candy Polishing Operation\*\***

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	At least 98% overall control (100% capture with permanent total enclosures designed in accordance with EPA Method 204 and 98% control using regenerative thermal oxidizer, catalytic oxidizer) or equivalent overall control achieving technology		

\*\*A process in which a final color coat and/or glaze is applied and the candy exterior is polished to a shiny finish.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.5.5\***

Last Update: 10/6/2022

**Snack Chip Seasoning System**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10		At least 95% reduction of captured particulate matter emissions using wet scrubber, or equivalent dust control system	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.5.6\***

Last Update: 10/6/2022

**Snack Chip Ambient Air Cooler**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
PM10	Use properly engineered high velocity air filtration system with oil baffle type filters, or equivalent filter system (70% control)		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.6.2\***

Last Update: 3/12/2026

**Animal Feed Supplement Manufacturing - Palm Oil & Calcium Oxide Process**

<b>Pollutant</b>	<b>Achieved in Practice or contained in the SIP</b>	<b>Technologically Feasible</b>	<b>Alternate Basic Equipment</b>
VOC	98% control (thermal incineration, scrubber with biofiltration system, or equivalent)		
PM10	Wet scrubber or equivalent technology achieving >= 95% control efficiency		

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.7.1\***

Last Update: 6/22/2022

**Poultry Broiler House**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	<p>1. a) Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors, or b) Use of acidifying litter amendments; AND</p> <p>2. Comply with applicable District Rule 4570 Feed and Housing Mitigation Measures; AND</p> <p>3. Houses completely cleaned out at least twice per year; AND</p> <p>4. All mortality removed from houses at least once per day</p>	<p>1. 98% Overall Capture and Control (Thermal/Catalytic Incineration with a Concentrator)</p> <p>2. 95% Overall Capture and Control (Carbon Adsorption)</p> <p>3. 80% Overall Capture and Control (Biofiltration)</p> <p>4. 70% Overall Capture and Control (Wet Scrubber)</p>	
PM10	<p>Use of the following broiler house design and management practices:</p> <p>1. Weatherproof housing structure, AND</p> <p>2. Minimum disturbance of manure/litter, AND</p> <p>3. Covered manure/litter piles</p>	<p>1. 99% Overall Capture and Control (Cyclones followed by Electrostatic Precipitator or Baghouse)</p> <p>2. 95% Overall Capture and Control: (Cyclones Followed by Wet Scrubber)</p> <p>3. 60% Overall Capture and Control (High Efficiency Cyclones)</p>	
Ammonia (NH3)	<p>1. a) Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors, or b) Use of acidifying litter amendments; AND</p> <p>2. Comply with applicable District Rule 4570 Feed and Housing Mitigation Measures; AND</p> <p>3. Houses completely cleaned out at least twice per year; AND</p> <p>4. All mortality removed from houses at least once per day</p>	<p>1. 80% Overall Capture and Control (Biofiltration or Wet Scrubber)</p>	

## San Joaquin Valley Unified Air Pollution Control District

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.7.2\***

Last Update: 6/10/2026

**Poultry - Layer House**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	<p>Use of the following practices:</p> <p>a. Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors; AND</p> <p>b. Belt manure removal and aeration/drying system with belts that advance at least a full length every 48 hours and manure removal at least twice per week; AND</p> <p>c. Applicable District Rule 4570 Feed and Housing Mitigation Measures; AND</p> <p>d. All mortality removed from houses at least once per day</p>	<p>1. 80% Control (Capture and Biofiltration)</p> <p>2. 70% Control (Capture and Wet Scrubber)</p>	
PM10	<p>Use of the following practices:</p> <p>a. Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors; AND</p> <p>b. Belt manure removal and aeration/drying system with belts that advance at least a full length every 48 hours and manure removal at least twice per week; AND</p> <p>c. Directing poultry house exhaust to a system that reduces PM10 emissions by at least 40% (Manure drying tunnel(s), Dry filter(s) using centrifugal force, or equivalent)</p>	<p>1. 85% Control (Capture and Electrostatic Precipitator)</p> <p>2. 80% Control (Capture and Wet Scrubber)</p> <p>3. 70% Control (Capture and High Efficiency Cyclones or Cyclonic De-Duster)</p>	

# San Joaquin Valley Unified Air Pollution Control District

NH3	Use of the following practices:	80% Control (Capture and Biofiltration or Wet Scrubber)
	a. Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors; AND	
	b. Belt manure removal and aeration/drying system with belts that advance at least a full length every 48 hours and manure removal at least twice per week; AND	
	c. Applicable District Rule 4570 Feed and Housing Mitigation Measures; AND	
	d. All mortality removed from houses at least once per day	

---

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**

San Joaquin Valley  
Unified Air Pollution Control District

**Best Available Control Technology (BACT) Guideline 5.7.3\***

Last Update: 5/7/2026

**Turkey House**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	<p>- Use of the following poultry house design and management practices:</p> <p>a. i) Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors; or ii) use of acidifying litter amendments; AND</p> <p>b. Compliance with applicable District Rule 4570 Feed and Housing Mitigation Measures; AND</p> <p>c. Houses completely cleaned out at least twice per year; AND</p> <p>d. All mortality removed from houses at least once per day</p>	<p>1. 80% Control (Capture and Biofiltration)</p> <p>2. 70% Control (Capture and Wet Scrubber)</p>	
PM10	<p>- Use of the following poultry house design and management practices:</p> <p>a. Weatherproof housing structure; AND</p> <p>b. Minimum disturbance of manure/litter; AND</p> <p>c. Covering manure/litter stockpiles</p>	<p>1. 85% Control (Capture and Electrostatic Precipitator)</p> <p>2. 80% Control (Capture and Wet Scrubber)</p> <p>3. 70% Control (Capture and Cyclones)</p> <p>4. 40% Control (Dry Filters Using Centrifugal Force for PM Removal)</p>	

## San Joaquin Valley Unified Air Pollution Control District

NH3	- Use of the following poultry house design and management practices:  a. i) Enclosed housing with mechanical ventilation and computerized control of environmental conditions using sensors; or ii) use of acidifying litter amendments; AND  b. Compliance with applicable District Rule 4570 Feed and Housing Mitigation Measures; AND  c. Houses completely cleaned out at least twice per year; AND  d. All mortality removed from houses at least once per day	80% Control (Capture and Biofiltration or Wet Scrubber)
-----	--	---

---

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in a State Implementation Plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

**\*This is a Summary Page for this Class of Source**