

April 21, 2022

Mr. Eric Squire
Vitro Flat Glass LLC
3333 S Peach Ave
Fresno, CA 93725

Re: Notice of Final Action - Title V Permit Renewal
Facility Number: C-948
Project Number: C-1212592

Dear Mr. Squire:

The District has issued the Final Renewed Title V Permit for Vitro Flat Glass LLC (see enclosure). The preliminary decision for this project was made on February 9, 2022.

No comments were received subsequent to the District's preliminary decision. However, the District has made an administrative change to the permit to remove references to outdated non-federally enforceable county rules. Therefore, the District has administratively revised conditions #2, 3, and 40 on PTO C-948-0-4 of the renewed operating permit to remove the aforementioned rules. The public notice for issuance of the Final Title V Permit will be posted on the District's website (www.valleyair.org).

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,



Brian Clements
Director of Permit Services

Enclosures

cc: Courtney Graham, CARB (w/enclosure) via email
cc: Laura Yannayon, EPA (w/enclosure) via EPS

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-8000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (861) 392-5500 FAX: (861) 392-5585



Facility # C-948
VITRO FLAT GLASS LLC
3333 S PEACH AVE
FRESNO, CA 93725

Notice of Permit Issuance

The enclosed permit unit requirements authorize the operation of the equipment as described. These permit unit requirements supersede any and all previous permits for the specified equipment.* Please insert these documents into the Facility Permit to Operate, and post copies on or near the equipment as required by District Rule 2010.

Please contact any of our Small Business Assistance (SBA) staff at the numbers below if you have any questions:

| | |
|--------------|----------------|
| Modesto: | (209) 557-6446 |
| Fresno: | (559) 230-5888 |
| Bakersfield: | (661) 392-5665 |

*Failure to comply with the permit unit requirements may result in enforcement action.

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: (661) 392-5500 FAX: (661) 392-5585

Permit to Operate

FACILITY: C-948

EXPIRATION DATE: 02/28/2027

LEGAL OWNER OR OPERATOR: VITRO FLAT GLASS LLC
MAILING ADDRESS: 3333 S PEACH AVE
FRESNO, CA 93725

FACILITY LOCATION: 3333 S PEACH AVE
FRESNO, CA 93725

FACILITY DESCRIPTION: GLASS MANUFACTURING

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Samir Sheikh
Executive Director / APCO

Brian Clements
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: C-948-0-4

EXPIRATION DATE: 02/28/2027

FACILITY-WIDE REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1]
3. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0]
4. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
5. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
6. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
7. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
8. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
10. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: VITRO FLAT GLASS LLC
Location: 3333 S PEACH AVE, FRESNO, CA 93725
C-948-0-4 : Apr 12 2022 1:53PM -- GARCIAJ

11. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
12. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
13. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
14. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
15. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
16. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
17. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
18. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
22. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
23. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
25. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
26. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
27. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
28. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
29. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
30. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
31. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
32. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
33. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
34. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
35. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
36. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

37. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
38. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
39. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (San Joaquin), and Rule 109 (Merced). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
42. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin November 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-2-5

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

1,577 BHP DETROIT DIESEL MODEL 12E-9885 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR (GENERATOR #3)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed in concentration at the point of discharge 0.1 gr/dscf. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR Part 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR Part 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR Part 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-3-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

238 BHP DETROIT MODEL RC6061A (SN 6A228427) DIESEL-FIRED EMERGENCY IC ENGINE POWERING A WATER PUMP FOR FIRE SUPPRESSION

PERMIT UNIT REQUIREMENTS

1. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
4. The permittee shall maintain records of hours of emergency and non-emergency operation. Records shall include the date, the initial start-up hours, the number of hours of operation, and the purpose of the operation (e.g., load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rules 4701 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-4-6

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

517.0 KGAL SILICA SAND CONCRETE STORAGE SILO #1, 38'D X 61'9"H, WITH ONE BIN VENT FILTRATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Maximum daily amount of material received in the silo shall not exceed 3,455 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall perform a complete vent filter inspection on an annual basis. Dust collector filters shall be inspected thoroughly for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions prior to further loading. Corrective action shall eliminate visible emissions before next loading event. The results of inspection shall be kept in a record and shall be made available to the District upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
7. Permittee shall maintain daily records of material received in the silo and shall make such records available for District inspection upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
8. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-5-6

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

517.0 KGAL SILICA SAND CONCRETE STORAGE SILO #2, 38'D X 61'9"H, WITH ONE BIN VENT FILTRATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Maximum daily amount of material received in the silo shall not exceed 3,455 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall perform a complete vent filter inspection on an annual basis. Dust collector filters shall be inspected thoroughly for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions prior to further loading. Corrective action shall eliminate visible emissions before next loading event. The results of inspection shall be kept in a record and shall be made available to the District upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
7. Permittee shall maintain daily records of material received in the silo and shall make such records available for District inspection upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
8. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-6-12

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

TRAIN SHED UNLOADING OPERATION WITH 6 UNDERGROUND RECEIVING PITS, 6 SHAKER CONVEYORS, 6 BUCKET ELEVATORS, AND STORAGE SILOS #3 AND #5 (TOTAL OF 1,034,000 GAL); ALL SERVED BY PANGBORN CORPORATION DC-2 BAGHOUSE DUST COLLECTOR (SN #63-CH3-6664) SHARED WITH PERMIT UNIT '-10 OR PANGBORN CORPORATION DC-6 BAGHOUSE DUST COLLECTOR (SN 63-CH3-6671) UNDER PERMIT UNIT '-10

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from the dust collector shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rules 2201 and 4101] Federally Enforceable Through Title V Permit
3. The baghouse dust collectors shall be maintained and operated according to manufacturer's specifications. [District Rule 2201]
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Material removed from baghouse dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The baghouse dust collectors cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Replacement filters numbering at least 10% of the total number of filters in the baghouse dust collector shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The baghouse dust collector shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The Train Shed Pangborn DC-2 baghouse dust collector shall operate at all times with a minimum differential pressure of 1 inch water column and a maximum differential pressure of 9 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Differential operating pressure shall be monitored and recorded on each day that the baghouse dust collectors operate. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emissions shall be controlled by a baghouse dust collector: either the Mixer Level Pangborn DC-6 or the Train Shed Pangborn DC-2. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The amount of dry material received from the underground pits into the storage silos shall not exceed 10,080 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Maximum daily amount of cullet received in the silos shall not exceed 1,728 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. PM10 emissions from the receiving of materials through the underground pits into the storage silos shall not exceed 0.0003 lb/ton of material transferred. [District Rule 2201] Federally Enforceable Through Title V Permit
15. PM10 emissions from the silo transfer shall not exceed 0.00025 lb/ton of material transferred. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Baghouse dust collector filters shall be inspected annually while in operation for evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
17. Baghouse dust collector filters shall be inspected annually while not in operation for tears, scuffs, abrasions or holes which might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
18. Records of baghouse dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
19. Visible emissions shall be inspected monthly during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions prior to further loading. Corrective action shall eliminate visible emissions before next loading event. The results of inspection shall be kept in a record and shall be made available to the District upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of the quantity of the material received in the silos & through underground receiving pits and shall make such records available for District inspection upon request. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
21. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-7-9

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

517,000 GALLON CULLET STORAGE SILO #4 AND CULLET CRUSHING OPERATION WITH CULLET CRUSHER, CULLET ELEVATOR SERVED BY A PANGBORN CORPORATION BAGHOUSE FABRIC COLLECTOR #DC-5, SERIAL #42-CH3-6656, AND CULLET SCREENING BOX

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from the baghouse shall not exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The baghouse shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The cleaning frequency and duration for the baghouse shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Replacement bags numbering at least 10% of the total number of bags in the baghouse shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The differential pressure gauge reading range for the baghouse shall be maintained between 0.5 and 9 inches of water column. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Differential operating pressure for the baghouse shall be monitored and recorded on each day that the baghouse operates. Upon detecting any excursion from the acceptable range pressure readings, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Maximum daily amount of material throughput shall not exceed 2,769 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
12. PM10 emissions rate from the cullet crushing operation shall not exceed 0.0012 lb-PM10/ton-material. [District Rule 2201] Federally Enforceable Through Title V Permit
13. PM10 emissions rate from the cullet screening box shall not exceed 0.00074 lb-PM10/ton-material. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. PM10 emissions rate from the belt conveyor serving the cullet screening box shall not exceed 0.000046 lb-PM10/ton-material. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Dust collector filters shall be inspected annually while in operation for evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Dust collector filters shall be inspected annually while not in operation for tears, scuffs, abrasions or holes which might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records of all maintenance of the dust collector, including all change outs of filter media, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Permittee shall maintain daily records of material throughput and shall make such records available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
20. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-8-8

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

517 KGAL SODA ASH STORAGE SILO #6, 38' D X 61'9" H, SERVED BY A DONALDSON TORIT MODEL CPC-8 DUST COLLECTOR AND A DONALDSON TORIT MODEL CPV-3 BIN VENT FILTER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Material removed from dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The dust collectors cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The dust collectors shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The Donaldson Torit CPC-8 dust collector shall operate at all times with a minimum differential pressure of 1 inches water column and a maximum differential pressure of 6 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The Donaldson Torit model CPV-3 bin vent filter shall operate at all times with a minimum differential pressure of 0 inches water column and a maximum differential pressure of 6 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Differential operating pressure shall be monitored and recorded on each day that the dust collectors operate. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The Donaldson Torit CPC-8 dust collector air flow rate shall not exceed 4,400 scfm. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The Donaldson Torit CPV-3 bin vent filter air flow rate shall not exceed 1,200 scfm. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Controlled PM10 emissions from Donaldson Torit CPC-8 and Donaldson Torit CPV-3 dust collectors shall not exceed 0.001 gr/scf. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Permittee shall perform a complete vent filter inspection on an annual basis. Dust collector filters shall be inspected thoroughly for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions prior to further loading. Corrective action shall eliminate visible emissions before next loading event. The results of inspection shall be kept in a record and shall be made available to the District upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
14. Permittee shall maintain daily records of material throughput and shall make such records available for District inspection upon request. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
15. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-9-8

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

ELECTROSTATIC PRECIPITATOR RESIDUE DELIVERY SYSTEM WITH A 40 HP BLOWER, PNEUMATIC TRANSFER TO 50 CU FT RECEIVING HOPPER VENTING TO CYCLONAIRE MODEL 36-FRC-18 BIN VENT FILTER, SCREW CONVEYOR AND SCALE HOPPER DISCHARGING TO BATCH HOUSE MIXER (C-948-10)

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The throughput of EP residue to the hopper shall not exceed 3 tons/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The dust collector shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The dust collector shall operate at all times with a minimum differential pressure of 1 inch water column and a maximum differential pressure of 7 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Visible emissions from the dust collector serving the EP residue hopper shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Material removed from dust collector shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The permittee shall perform a complete dust collector inspection on an annual basis. Dust collector filters shall be inspected thoroughly for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
9. Visible emissions shall be inspected monthly during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. Corrective action shall eliminate visible emissions within 24 hours. [District Rule 2520] Federally Enforceable Through Title V Permit
10. Daily records of the throughput (tons/day) of EP residue to the hopper shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. Differential operating pressure shall be monitored and recorded on each day that the dust collector operates. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of all maintenance of the dust collector, including all change-outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
13. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-10-15

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

SILO UNLOADING AND MIXING OPERATION INCLUDING BATCH GATHERING BELT SERVED BY MACPROCESS MODEL 39AVSC16 DUST COLLECTOR, PANGBORN CORP DC-6 BAGHOUSE DUST COLLECTOR (SN 63-CH3-6671) SHARED WITH PERMIT UNIT '6 OR DC-2 BAGHOUSE DUST COLLECTOR (SN 67 CH3-6664) UNDER PERMIT UNIT '6, AND A BATCH ELEVATOR, TOTALIZING SCALE, AND GLASS MASTER TURBIN MODEL 12000 MIXER SERVED BY A TORIT DOWN FLO-II MODEL #DFT-2-4 BAGHOUSE DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from each of the baghouse dust collectors shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rules 2201 and 4101] Federally Enforceable Through Title V Permit
3. The baghouse dust collectors shall be maintained and operated according to manufacturers' specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Material removed from the baghouse dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Each baghouse dust collector's cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Replacement bags numbering at least 10% of the total number of bags in each baghouse dust collector shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The baghouse dust collectors shall each be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The Mixer Level Pangborn DC-6 baghouse dust collector shall operate at all times with a minimum differential pressure of 1 inch water column and a maximum differential pressure of 9 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The Torit Down Flo-II baghouse shall operate at all times with a minimum differential pressure of 1 inch water column and a maximum differential pressure of 6 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The Macprocess 39AVSC16 baghouse dust collector shall operate at all times with a minimum differential pressure of 1 inch water column and a maximum differential pressure of 7 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Differential operating pressures shall be monitored and recorded on each day that the baghouse dust collectors operate. Upon detecting any excursion from the acceptable range pressure readings, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
13. Emissions shall be controlled by a baghouse dust collector: Macprocess 39AVSC16, and either Mixer Level Pangborn DC-6, Trainshed Pangborn DC-2, or Torit Down Flo-II. [District Rule 2201] Federally Enforceable Through Title V Permit
14. PM10 emissions from the transfer of materials from the storage silos to the mixer shall not exceed 0.00012 lb/ton of material throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
15. PM10 emissions from mixing and weighing shall not exceed 0.003 pound per ton of material throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
16. PM10 emissions from the mixer loadout shall not exceed 0.00004 pound per ton of material throughput. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Maximum material throughput shall not exceed 1,180 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Baghouse dust collector filters shall be inspected annually while in operation for evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Baghouse dust collector filters shall be inspected annually while not in operation for tears, scuffs, abrasions or holes which might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Records of baghouse dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2201] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records of the material throughput and such records shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-11-20

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

208 MMBTU/HR OXY-FUEL FIRED FLOAT GLASS FURNACE, FIRING ON NATURAL GAS WITH #2 FUEL OIL AS STANDBY, VENTED THROUGH A UNITED MCGILL DRY SCRUBBER/COOLING TOWER AND A UNITED MCGILL MODEL 3-500 ELECTROSTATIC PRECIPITATOR USING SO₂ AS A LUBRICANT FOR THE GLASS AND EQUIPPED WITH A SELECTIVE NON-CATALYTIC REDUCTION (SNCR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 (amended 12/17/92) using the equation $E=3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E=17.37 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. The furnace and burners shall be operated so as to minimize the NO_x emissions to the maximum extent possible without adversely affecting the product quality and furnace integrity. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The glass furnace shall be vented to a dry scrubber/electrostatic precipitator system anytime the furnace is operating. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The addition of liquid caustic soda to cooling tower water may be allowed to reduce corrosion and solid build-up, and ensure good working conditions for electrostatic precipitator. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Daily glass pull rate for this facility shall not exceed 650 U.S. short tons per day. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
10. Particulate Matter emissions (as PM₁₀) shall not exceed 18.80 pounds per hour from the electrostatic precipitator. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Particulate Matter emissions (as PM₁₀) shall not exceed 0.70 pounds per ton glass pulled on a block 24-hour average from the glass melting furnace. [District Rule 4354] Federally Enforceable Through Title V Permit
12. Oxides of nitrogen (NO_x) emissions shall not exceed 3.4 lb NO_x/ton, based on a 24-hour block average, as defined by Rule 4354. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
13. Oxides of nitrogen (NO_x) emissions shall not exceed 2.9 lb NO_x/ton, based on a 30-day rolling average, as defined by Rule 4354. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. SO_x emissions from the dry scrubber/electrostatic precipitator system shall not exceed 16.25 pounds per hour based on a 24-hour rolling average when firing the furnace on natural gas, nor 49.9 pounds per hour based on a 24-hour rolling average when firing the furnace on standby fuel oil #2. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Oxides of sulfur (SO_x) emissions shall not exceed 1.7 lb SO_x/ton, based on a 24-hour block average, as defined by Rule 4354. In no case shall SO_x emissions exceed 1.2 lb SO_x/ton on a rolling 30-day average. [District Rule 4354] Federally Enforceable Through Title V Permit
16. Sulfur compound emissions shall not exceed 2000 ppmv as SO₂. [District Rule 4801] Federally Enforceable Through Title V Permit
17. SO_x emissions from the surface passivation process shall not exceed 10 pounds per hour. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Volatile Organic Compounds (VOC) emissions shall not exceed either of the following limits: 1.51 pounds per hour or 0.1 pounds per ton of glass pulled (as defined by Rule 4354), based on a rolling three-hour average. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
19. Carbon monoxide (CO) emissions shall not exceed either of the following limits: 21.13 pounds per hour or 0.9 pounds per ton (as defined by Rule 4354), based on a rolling three-hour average. [District Rules 2201 and 4354] Federally Enforceable Through Title V Permit
20. Ammonia (NH₃) emissions shall not exceed 1.25 lb/hr based on a 24 hour rolling average. [District Rule 2201] Federally Enforceable Through Title V Permit
21. The permittee shall utilize a continuous in-stack ammonia monitor to verify compliance with the ammonia emissions limit. [District Rule 2201] Federally Enforceable Through Title V Permit
22. NO_x, CO, VOC, SO_x and PM₁₀ emission limitations of District Rule 4354 shall not apply during periods of start-up, shutdown, and idling, as defined by Rule 4354, 3.0. Permittee shall notify the District at least 24 hours before initiating idling, shutdown and startup and this notification shall include: date and time of the start of the exempt operation, reason for performing the operation, and an estimated completion date. The permittee shall notify the District by telephone within 24 hours after completion of the operation and shall maintain operating records and/or support documentation necessary to claim exemption. [District Rule 4354] Federally Enforceable Through Title V Permit
23. NO_x, CO, VOC, SO_x and PM₁₀ emission limitations of District Rule 4354 shall not apply during periods of routine maintenance of an add-on emission control system as long as the routine maintenance does not exceed 144 hours total per calendar year for all add-on controls and the routine maintenance is conducted in a manner consistent with good air pollution control practices for minimizing emissions. [District Rule 4354] Federally Enforceable Through Title V Permit
24. Annual source testing shall be conducted for VOC (lb/ton of glass pulled and lb/hr); CO (lb/ton of glass pulled and lb/hr); PM₁₀ (lb/ton of glass pulled and lb/hr); SO_x (lb/ton of glass pulled and lb/hr); and NO_x (lb/ton of glass pulled); and NH₃ (lb/hr) emissions at least once every calendar year. To qualify as an annual performance test, the test date shall be at least 6 months after, and not more than 18 months after the initial and the previous annual performance test. [District Rules 1070, 1081 and 4354] Federally Enforceable Through Title V Permit
25. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. Source testing shall be conducted using following test methods: (1) Oxides of Nitrogen: EPA Method 7E, EPA Method 19, or ARB Method 100; (2) Carbon Monoxide: EPA Method 10, or ARB Method 100; (3) VOC (ppmv): EPA Method 25A expressed in terms of carbon, or ARB Method 100, EPA Method 18 or ARB method 422 to determine emissions of exempt compounds; (4) Stack Gas Oxygen, Carbon Dioxide, Excess Air, and Dry Molecular Weight: EPA Method 3 or 3A, or ARB Method 100; (5) Stack Gas Flow rate - EPA Method 2; (6) Stack Gas Moisture Content - EPA Method 4; (7) Fuel Heating Value - ASTM Method D2015-85 or E711; (8) Oxides of Sulfur: EPA Method 6C, EPA Method 8, or ARB Method 100; (9) Filterable PM10: EPA Method 5, EPA Method 201, or EPA Method 201A; (10) Ammonia: BAAQMD ST-1B. An operator choosing EPA Method 5 shall count all PM collected as PM10; (11) Condensable PM10: EPA Method 202 with the following procedures, (11a) Purge the impinger with dry nitrogen for one hour. The one hour purge with dry nitrogen shall be performed as soon as possible after the final leak check of the system, (11b) Neutralize the inorganic portion to a pH of 7.0. Use the procedure, "Determination of NH₄ Retained in Sample by Titration" described in Method 202 to neutralize sulfuric acid, (11c) Evaporate the last 1 ml of the inorganic fraction by air drying following evaporation of the bulk of the impinger water in a 105 degrees C oven as described in the first sentence of the Method 202 section titled "Inorganic Fraction Weight Determination". [District Rule 4354] Federally Enforceable Through Title V Permit
27. Furnace conditions during source testing shall be representative of normal operations, with a glass production rate equal to or greater than 60 percent of the permitted glass production capacity. The source test may be conducted at a glass production rate lower than 60 percent of the permitted glass production capacity, provided that the permittee demonstrates that the proposed alternative glass production rate is representative of normal operations and the proposed alternative glass production rate is approved by the APCO in writing. [District Rule 4354] Federally Enforceable Through Title V Permit
28. For source testing purposes, the arithmetic average of three 30-consecutive-minute test runs shall be used to determine compliance with NO_x, CO, VOC, SO_x, and NH₃ emission limits. [District Rule 4354] Federally Enforceable Through Title V Permit
29. For source testing purposes, the arithmetic average of three 60-consecutive-minute test runs shall be used to determine compliance with PM10 emission limits. [District Rule 4354] Federally Enforceable Through Title V Permit
30. During source testing, for a given pollutant, if two of the three runs individually demonstrate emissions above the applicable limit, the test cannot be used to demonstrate compliance for the furnace, even if the averaged emissions of all three test runs is less than the applicable limit. [District Rule 4354] Federally Enforceable Through Title V Permit
31. Source testing shall be witnessed or authorized by District personnel. Test results must be submitted to the District within 60 days of performance testing. [District Rule 1081] Federally Enforceable Through Title V Permit
32. The continuous emission monitor system (CEMS) shall be properly installed in the electrostatic precipitator stack and operated in accordance with the manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
33. The CEMS and data acquisition system shall monitor for NO_x, CO, SO_x, and opacity. [District Rule 2201] Federally Enforceable Through Title V Permit
34. The CEMS shall meet the performance specification requirements in 40 CFR Parts 60.7 and 60.13, 40 CFR Part 60 Appendix B (Performance Specifications) and Appendix F (Quality Assurance Procedures); and 40 CFR 51, Appendix P, or shall meet equivalent specifications established by mutual agreement of the District, the ARB, and the EPA. [District Rules 1080 and 4354] Federally Enforceable Through Title V Permit
35. Results of CEMS must be reduced according to the procedure established in 40 CFR, Part 51, Appendix P, paragraphs 5.0 through 5.3.3, or by other methods deemed equivalent by mutual agreement with the District, the ARB, and the EPA. [District Rule 1080] Federally Enforceable Through Title V Permit
36. Records of CEMS shall be maintained and shall contain: the occurrence and duration of any start-up, shutdown or malfunction, performance testing, evaluations, calibrations, checks, adjustments, maintenance of CEMs, and emission measurements. [District Rule 1080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Permittee shall submit a CEMS written report for each calendar quarter to the District. The report is due on the 30th day following the end of the calendar quarter. Quarterly report shall include: time intervals, data and magnitude of excess emissions, nature and cause of excess (if known), corrective actions taken and preventive measures adopted; averaging period used for data reporting corresponding to the averaging period specified in the emission test period used to determine compliance with an emission standard; applicable time and date of each period during which the CFM was inoperative (except for zero and span checks) and the nature of system repairs and adjustments; and a negative declaration when no excess emissions occurred. [District Rules 1080 and 2520] Federally Enforceable Through Title V Permit
38. Any emissions in excess of the limits imposed by conditions in this permit, as measured by the CEMS constitutes a violation of District Rules and Regulations and shall be reported by the operator to the APCO within 96 hours. [District Rule 1080] Federally Enforceable Through Title V Permit
39. Operator shall notify the District no later than eight hours after the detection of a breakdown of the CEMS. The operator shall inform the District of the intent to shut down the CEMS at least 24 hours prior to the event. [District Rule 1080] Federally Enforceable Through Title V Permit
40. The facility shall maintain equipment, facilities, and systems compatible with the District's CEM data polling software system and shall make CEM data available to the District's automated polling system on a daily basis. [District Rule 1080] Federally Enforceable Through Title V Permit
41. Upon notice by the District that the facility's CEM system is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEM data is sent to the District by a District-approved alternative method. [District Rule 1080] Federally Enforceable Through Title V Permit
42. The permittee shall operate and maintain a monitoring and recording system to accurately measure and record the furnace melter crown temperature at least once per day. [District Rule 4354] Federally Enforceable Through Title V Permit
43. The furnace melter crown temperature shall be maintained at or above 1,800 °F. If the measured furnace temperature is less than 1,800 °F, the permittee shall conduct a certified VOC source test within 60 days to re-establish the minimum temperature limit. In lieu of conducting a certified VOC source test, the permittee may stipulate that a violation has occurred, subject to enforcement action. The permittee must then correct the violation (return the furnace temperature to or above the minimum temperature limit), show compliance has been re-established, and resume monitoring procedures. If the deviation is a result of a qualifying breakdown condition pursuant to District Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rule 4354] Federally Enforceable Through Title V Permit
44. The permittee shall operate and maintain a monitoring and recording system to accurately measure and record the secondary current and secondary voltage across each field of the electrostatic precipitator at least once per hour. [District Rule 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
45. The average hourly total power input into the electrostatic precipitator shall be maintained at or above 0.23 kW. The average hourly total power input shall be the sum of the average power inputs to each field of the electrostatic precipitator. The average power inputs to each field shall be calculated by multiplying the average hourly secondary current for that field by the average hourly secondary voltage for that field, both recorded by the continuous monitoring system. [District Rule 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
46. If the measured average total power input into the electrostatic precipitator falls below the acceptable level specified within this permit, the permittee shall conduct a certified source test within 60 days to re-establish the acceptable secondary voltage and/or secondary current range/level. In lieu of conducting a certified PM10 source test, the permittee may stipulate that a violation has occurred, subject to enforcement action. The permittee must then correct the violation (return the average hourly voltage and/or current input to or above the minimum acceptable levels), show compliance has been re-established, and resume monitoring procedures. If the deviation is a result of a qualifying breakdown condition pursuant to District Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rule 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

47. The permittee shall maintain daily records of total hours of operation, quantity of glass pulled, NO_x and SO_x emission rates in lb/ton of glass pulled (both block 24-Hr & rolling 30-day averages), CO emission rate in lb/ton of glass pulled (rolling 3-hour average) and quantity & type of fuel used. The permittee shall also maintain records of source tests, the acceptable range for each approved key system operating parameter as established by source testing, all instances of maintenance and repair, any malfunction, and records of all periods of idling, startup, or shutdown. [District Rule 4354] Federally Enforceable Through Title V Permit
48. The permittee shall keep records of the date and time of the furnace melter crown temperature readings and the furnace melter crown temperature measured during the most recent source test that demonstrated ongoing compliance with the VOC emission limit. [District Rule 4354] Federally Enforceable Through Title V Permit
49. The permittee shall keep records of the date and time of the electrostatic precipitator total power input readings and the minimum electrostatic precipitator total power input measured during the source test that demonstrated ongoing compliance with the PM₁₀ emission limit. [District Rule 4354 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
50. The permittee shall maintain records of SO_x usage (lb/hr) in the surface passivation process. [District Rule 2201] Federally Enforceable Through Title V Permit
51. The permittee shall maintain daily records of NH₃ emission rates in lb/hr. [District Rule 2201]
52. The facility shall not use commercial arsenic as a raw material in the production process. [40 CFR Part 61, Subpart N] Federally Enforceable Through Title V Permit
53. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202, Fresno County Rule 405, District Rule 4801, and Fresno County Rule 406. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
54. The requirements of District Rule 4301, 40 CFR 60, Subpart CC & 40 CFR 61, Subpart N were determined to be not applicable to this unit. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
55. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District, ARB, or EPA inspection upon request. [District Rules 1070 and 4354] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-14-8

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

GLASS PACKING AND CULLET SYSTEM WITH ASSOCIATED CONVEYORS AND ELEVATORS AND 4 PACKING MACHINES SERVED BY THE FOLLOWING DUST COLLECTORS: INTERNATIONAL CLEAN AIR, MODEL 6800AE (S/N 6032), PANGBORN CORP (S/N 57CH366759), SENECA, MODEL 121-AM-10 (S/N 871082) AND SENECA MODEL 132-FMTS-100 (S/N 962503)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Daily glass pull rate for this facility shall not exceed 650 US short tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Visible emissions from the Seneca Model 132-FMTS-100 dust collector serving LEAP packing machine shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The dust collector shall be equipped with an operational pressure differential gauge to indicate the pressure drop across the bags. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Particulate matter emissions (as PM10) shall not exceed 0.0254 pound per ton of glass pulled. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain daily records of glass pull rate and shall make this information available to the District upon request. [District Rule 2520] Federally Enforceable Through Title V Permit
9. Dust collector filters shall be inspected annually while in operation for evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
10. Dust collector filters shall be inspected annually while not in operation for tears, scuffs, abrasions or holes which might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
11. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520] Federally Enforceable Through Title V Permit
12. Visible emissions from the dust collector shall be checked monthly, while in operation. If visible emissions are observed, corrective action shall be taken eliminate visible emissions. Corrective action shall eliminate visible emissions within 24 hours. [District Rule 2520] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-15-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

25.0 HP EMERGENCY CULLET SYSTEM (CD0) AND ASSOCIATED CONVEYORS AND ELEVATORS LOCATED BETWEEN THE LEHR AND THE WARE ROOM, SERVED BY A PANGBORN CORPORATION FABRIC COLLECTOR, SN 53-CH3-6657

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Material removed from dust collector(s) shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Dust collector filters shall be inspected annually while in operation for evidence of particulate matter leaks and replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
5. Dust collector filters shall be inspected annually while not in operation for tears, scuffs, abrasions or holes which might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
6. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520] Federally Enforceable Through Title V Permit
7. Visible emissions from the dust collector shall be checked monthly, while in operation. If visible emissions are observed, corrective action shall be taken eliminate visible emissions. Corrective action shall eliminate visible emissions within 24 hours. [District Rule 2520] Federally Enforceable Through Title V Permit
8. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-17-9

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

"W" AND "IW" INTERLEAVING SOLUTION MIXING BOOTH AND APPLICATION BOOTH WITH ULTRASONIC SPRAY SYSTEM FOR THE APPLICATION OF INTERLEAVING SOLUTION TO THE GLASS RIBBON; BOTH MIXING BOOTH AND APPLICATION BOOTH SERVED BY ONE DUAL DIVISION MODEL FW300-5 PVC FUME SCRUBBER AND REMOTE RECIRCULATION TANK

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall only mix and apply either "W" or "IW" interleaving solutions. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The "W" interleaving solution shall not contain more than 3.0% by weight of adipic acid and malic acid. The remainder of the solution shall be water. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The "IW" interleaving solution shall not contain more than 6.0% by weight of adipic acid, malic acid, maleic acid, surfactant(s), and biocide(s). The surfactant(s) and biocide(s) shall not comprise more than 0.1% of the solution by weight. The remainder of the solution shall be water. [District Rule 2201] Federally Enforceable Through Title V Permit
6. On any day when any "IW" interleaving solution is applied, the amount of interleaving solution applied shall not exceed 107 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
7. On any day when only "W" interleaving solution is applied, the amount of interleaving solution applied shall not exceed 216 gallons. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The fume scrubber shall be operated whenever interleaving solution is being mixed or applied. [District Rule 2201] Federally Enforceable Through Title V Permit
9. PM10 emissions shall not exceed 1.4 lb per day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Visible emissions from the exhaust stack shall be checked annually. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If excessive visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520] Federally Enforceable Through Title V Permit
11. The permittee shall keep a daily record of (1) the name ("W" or "IW") of the interleaving solution used, (2) the amount in gallons used, and (3) the composition of the interleaving solution. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The permittee shall measure and record the pressure drop across the scrubber at least once each quarter. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
14. Compliance with the conditions in the permit requirements for this unit shall be deemed compliance with District Rule 4201, Fresno County Rule 404, District Rule 4202 and Fresno County Rule 405. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-18-6

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

240 BHP JOHN DEERE MODEL 6076AF DIESEL-FIRED EMERGENCY STANDBY IC ENGINE WITH TURBOCHARGER, AFTERCOOLER, AND TIMING RETARD (SIX DEGREES) POWERING AN AIR COMPRESSOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. Emissions from this IC engine shall not exceed any of the following limits: 7.01 g-NOx/bhp-hr, 12.8 g-CO/bhp-hr, or 0.19 g-VOC/bhp-hr. [District Rule 2201 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed 0.67 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
18. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-22-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

1,500 BHP DETROIT MODEL 16E-4930 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR (GENERATOR #2)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed in concentration at the point of discharge 0.1 gr/dscf. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Emission limits while firing No. 2 fuel oil shall not exceed the following: NO_x = 29.8 lb/hr, SO_x = 0.2 lb/hr, VOC (NMHC) = 1.1 lb/hr, CO = 21.6 lb/hr and PM₁₀ = 0.2 lb/hr. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel consumption shall not exceed 77.3 gallons of diesel fuel per hour. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17CCR 93115] Federally Enforceable Through Title V Permit
6. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
11. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
16. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
19. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
20. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-23-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

105 BHP DETROIT DIESEL MODEL 5043-7001 DIESEL-FIRED EMERGENCY STANDBY IC ENGINE USED AS PART OF AN EMERGENCY LIGHTING SYSTEM PROVIDING LIGHT THROUGHOUT THE FACILITY DURING PERIODS OF UTILITY POWER INTERRUPTION (LIGHTING GENERATOR)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed in concentration at the point of discharge 0.1 gr/dscf. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
7. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
8. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
14. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
18. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-24-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

286 BHP DETROIT DIESEL MODEL 8083-7000 DIESEL-FIRED EMERGENCY IC ENGINE POWERING A WATER PUMP USED TO MAINTAIN THE MILL USE WATER FLOW DURING PERIODS OF UTILITY POWER INTERRUPTION (MILL USE PUMP #1 - SOUTH)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed in concentration at the point of discharge 0.1 gr/dscf. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115 and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801, and 17CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee that affects the mill water flow. [District Rule 4702] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-25-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

286 BHP DETROIT DIESEL MODEL 8V-92 (8083-7000) DIESEL-FIRED EMERGENCY IC ENGINE POWERING A WATER PUMP USED TO MAINTAIN THE MILL USE WATER FLOW DURING PERIODS OF UTILITY POWER INTERRUPTION (MILL USE PUMP #2)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed in concentration at the point of discharge 0.1 gr/dscf. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
3. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801, and 17CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
5. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
6. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee that affect the mill water flow. [District Rule 4702] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
8. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
10. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
12. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
13. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801, and 17 CCR 93115] Federally Enforceable Through Title V Permit
15. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-28-4

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

1,804 BHP CATERPILLAR MODEL 3512 STD DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR (GENERATOR #1)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed in concentration at the point of discharge 0.1 gr/dscf. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The diesel engine shall be operated with an initial injection timing setting of 16 degrees BTDC (Before Top Dead Center) or less. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Engine shall be equipped with a turbocharger w/aftercooler or intercooler. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The engine shall be equipped with a positive crankcase ventilation (PCV) system or a crankcase emissions control device of at least 90% control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
5. PM-10 emission rate shall not exceed 0.193 g/hp-hr. [District Rule 4102]
6. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
7. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801, and 17CCR 93115] Federally Enforceable Through Title V Permit
8. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
9. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
10. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
11. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
12. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
14. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee has the option of utilizing an oil analysis program in order to extend the oil changing requirement of every 500 hours of operation or every 12 months, whichever comes first. The oil analysis must be performed every 500 hours of operation or every 12 months, WHICHEVER comes first. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
16. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit
18. This engine shall be operated only for maintenance, testing, and required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 30 hours per calendar year. [District Rules 4701 and 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
19. The permittee shall maintain monthly records of the type of fuel purchased. [District Rules 4702 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
20. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63 Subpart ZZZZ] Federally Enforceable Through Title V Permit
21. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements of SJVUAPCD Rule 4201; Rule 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
22. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 402 (Madera) and 404 (Fresno, Merced, Kern, Kings, San Joaquin, Stanislaus, Tulare). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-29-3

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

GLASS CUTTING OPERATION WITH AUTOMATIC LUBRICANT APPLICATION

PERMIT UNIT REQUIREMENTS

1. Permittee shall keep monthly and annual records of type and quantity of cutting aid used in gallons, as well as maintain onsite a copy of the Safety Data Sheet (SDS) for each cutting aid used. [District Rule 1070]
2. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-30-5

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

CULLET HANDLING SYSTEM CONSISTING OF A CULLET TOWER (HOPPER) AND DISCHARGE FEEDER, A BELT CONVEYOR/WEIGHER SYSTEM WITH TWO CONVEYORS, A MIXER DISCHARGE VIBRATING FEEDER, AND THREE ASSOCIATED DUST COLLECTORS: ONE (1) DONALDSON TORIT MODEL DLM-V4/7F1 AND TWO (2) J.D.B. DENSE FLOW MODEL DF110R

PERMIT UNIT REQUIREMENTS

1. Visible emissions from each baghouse shall not exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Material removed from each dust collector shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 4102]
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. Each baghouse shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The cleaning frequency and duration for each baghouse shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Replacement bags numbering at least 10% of the total number of bags in each baghouse shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Each baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The differential pressure gauge reading ranges shall be maintained between 0 and 5 inches of water column for the Donaldson-Torit dust collector and between 2 and 9 inches of water column for the JDB dust collectors. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Controlled PM10 emissions from the dust collector shall not exceed 0.001 gr/scf. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Differential operating pressure for each baghouse shall be monitored and recorded on each day that the baghouse operates. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of all maintenance of each baghouse, including all change outs of filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Particulate matter emissions from each source operation shall not exceed the maximum allowable emission rate (lb/hr), as determined using the following formula: $E = 3.59 \times P^{0.62}$, where E equals the maximum allowable emission rate (lb/hr) and P equals the process weight rate (tons/hr) and is less than or equal to 30 tons/hr. [District Rule 4202] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. Dust collector filters for each baghouse shall be inspected annually while in operation for evidence of particulate matter breakthrough and replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
15. Dust collector filters for each baghouse shall be inspected annually while not in operation for tears, scuffs, abrasions or holes which might interfere with the PM collection efficiency and shall be replaced as needed. [District Rule 2520] Federally Enforceable Through Title V Permit
16. Records of dust collector maintenance, inspections, and repair for each baghouse shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Visible emissions from each baghouse shall be inspected quarterly during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520] Federally Enforceable Through Title V Permit
18. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-948-35-2

EXPIRATION DATE: 02/28/2027

EQUIPMENT DESCRIPTION:

418 BHP (INTERMITTENT) MTU MODEL 6R1600G70S TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING AN ELECTRICAL GENERATOR

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with a non-resettable hour meter with a minimum display capability of 9,999 hours, unless the District determines that a non-resettable hour meter with a different minimum display capability is appropriate in consideration of the historical use of the engine and the owner or operator's compliance history. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed any of the following limits: 2.32 g-NOx/bhp-hr, 1.12 g-CO/bhp-hr, or 0.19 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed 0.14 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4102, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
10. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 50 hours per calendar year. [District Rules 2201, 4102, and 4702; 17 CCR 93115; and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
12. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702, 17 CCR 93115, and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.